

Duct & Drain

JET-CAT







[The Grease Duct Cleaning Robot JET-CAT] is used for cleaning environments such as school cafeterias, factory canteens, hotel kitchens, government facilities, and grease ducts. It supports cleaning ducts with diameters ≥280mm. It is easy to operate, efficient, and user-friendly.



ROBOT JET-CAT



ROBOT CONTROL BOX

PRODUCT FEATURES



The JET-CAT Grease Duct Cleaning Robot cleans grease ducts with diameters of 28 cm and above. It features a "one-button start" for 360° rotational cleaning, powered by a high-performance motor, which effectively navigates obstacles. Equipped with high-definition cameras, it records real-time video for quick inspection of the duct interior. The robot also includes a waste oil recycle system for efficient removal of grease from the ducts.



Oil suction

cleaning and suction simultaneously



High-definition recording

front and rear infrared HD cameras



Innovative feature

unique offline operation



High quality body

304 stainless steel material



360° cleaning

Supports targeted location cleaning



Powerful magnetic tracks

Non-slip during cleaning

MAIN PARAMETER



JET-CAT



Applicable	Round pipes: ≥300mm Rectangular pipes: ≥300x200mm
LED Light	Illuminates the interior of the pipe from all angles
Camera	Infrared night vision HD camera, 1920×1080 resolution
Material	304 stainless steel
Size	280 (W) · 175 (H) · 410
Climb ability	<30
Cleaning way	360-degree spiral cleaning
Waterproof	IP68
Drive mode	Powerful magnetic tracks
Working distance	15 meter
Operating height	28-75CM
Oil suction way	Negative pressure oil suction
Weight	15.25KG



JET-CAT ROBOT

* Obstacle-Crossing Ability: <30°

* Rated Voltage: 220V / 110V / 230V

* Travel Speed: 7-8 m/min

* Spray Gun Rotation Angle: 360° spiral cleaning

* Product Dimensions: 280 (W) \times 175 (H) \times 410 (L) mm



ROBOT CONTROL BOX

·Screen resolution : $1920 \times 1080 \text{ P}$ ·size : 400(W)*180(H)*320(L)mm



High pressure washer with suction function

Oil Suction Power: 3000W

Motor Power: 4.5KW

Water Flow Rate: 20 L/minWater Pressure: 180-200 BAR

- Product Dimensions: 710 (W) \times 730 (H) \times 710 (L) mm







AQUAHOT Diesel heater

Fuel Tank Capacity: 12L

Operating Temperature: 0-90°C

Product Power: 300WHeating Rate: 10L/min

- Product Dimensions: 380 (W) \times 670 (H) \times 580 (L) mm



JET-SPRAY

Spraying machine (dual pump model)

Inlet Hose Length: 2mOutlet Hose Length: 15m

Wire Cross-Section: 0-2.2mm²
Voltage/Power: 24V/100W × 2

- Product Dimensions: 310 (W) \times 148 (H) \times 330 (L) mm



WASTE-BIN

Waste oil recycling bucket


Product Weight: 11.65 kgProduct Capacity: 20L

- Product Dimensions: $330 \text{ (W)} \times 450 \text{ (H)} \times 360 \text{ (L)} \text{ mm}$



APPLICATION










Combo 1







Combo 2





Combo 3







TRIUMPH360 DEGREE GLOBAL CONSULTANCY PVT. LTD.

Duct & Drain

PHONE: +91 7303020978;

+91 7303800978

EMAIL: info@triumph360deg.com;

triumph360degree@gmail.com

Website: www.triumph360deg.com