

Rubber-like look and feel enhances flexibility while maintaining durability and cost efficiencies of PVC.

#### POTENTIAL USE:

- Multipurpose applications
- Air & water (up to 150° F)
- Pneumatic tools
- Air service for painting equipment
- Coolant lines

#### FEATURES:

- UV & Ozone Resistant
- Non-Marking Cover
- Lightweight
- Long continuous lengths
- Silicone free tube & cover
- Chemical resistance of PVC
- Meets RMA (Class B) oil resistance

#### CONSTRUCTION:

- **Tube:** Specially Formulated PVC Compound
- **Reinforcement:** High Tensile Strength Textile Cord
- **Cover:** Specially Formulated PVC Compound



**TEMPERATURE:** -15° F (-26° C) to +150° F (+65° C) continuous service

**BRANDING:** Flex-Tech RT Multipurpose - 3/8" ID  
300 psi W.P. (2.1 MPa) Made in USA

Part#	I.D.	O.D.	Max W.P.	Wt./ft.	Length	Type	End Conn.
RT-0250XX-RL	1/4"	0.5	300 psi	0.095	500 ft	Reel	None
ART0250XX25MM	1/4"	0.5	300 psi	0.095	25 ft	Assembly	MNPT
ART0250XX50MM	1/4"	0.5	300 psi	0.095	50 ft	Assembly	MNPT
ART0250XX100MM	1/4"	0.5	300 psi	0.095	100 ft	Assembly	MNPT
ART0250XX25QP	1/4"	0.5	300 psi	0.095	25 ft	Assembly	Quick/Plug
ART0250XX50QP	1/4"	0.5	300 psi	0.095	50 ft	Assembly	Quick/Plug
ART0250XX100QP	1/4"	0.5	300 psi	0.095	100 ft	Assembly	Quick/Plug
RT-0375XX-RL	3/8"	0.595	300 psi	0.105	500 ft	Reel	None
ART0375XX25MM	3/8"	0.595	300 psi	0.105	25 ft	Assembly	MNPT
ART0375XX50MM	3/8"	0.595	300 psi	0.105	50 ft	Assembly	MNPT
ART0375XX100MM	3/8"	0.595	300 psi	0.105	100 ft	Assembly	MNPT
ART0375XX25QP	3/8"	0.595	300 psi	0.105	25 ft	Assembly	Quick/Plug
ART0375XX50QP	3/8"	0.595	300 psi	0.105	50 ft	Assembly	Quick/Plug
ART0375XX100QP	3/8"	0.595	300 psi	0.105	100 ft	Assembly	Quick/Plug
RT-0500XX-RL	1/2"	0.785	300 psi	0.132	500 ft	Reel	None
ART0500XX25MM	1/2"	0.785	300 psi	0.132	25 ft	Assembly	MNPT
ART0500XX50MM	1/2"	0.785	300 psi	0.132	50 ft	Assembly	MNPT
ART0500XX100MM	1/2"	0.785	300 psi	0.132	100 ft	Assembly	MNPT
RT-0625XX-RL	5/8"	0.915	300 psi	0.185	500 ft	Reel	None
RT-0625XX-50	5/8"	0.915	300 psi	0.185	50 ft	Coil	None
RT-0625XX-100	5/8"	0.915	300 psi	0.185	100 ft	Coil	None
RT-0750XX-RL	3/4"	1.07	300 psi	0.29	600 ft	Reel	None
RT-0750XX-50	3/4"	1.07	300 psi	0.29	50 ft	Coil	None
RT-0750XX-100	3/4"	1.07	300 psi	0.29	100 ft	Coil	None
RT-1000XX-RL	1"	1.44	200 psi	0.45	400 ft	Reel	None
RT-1000XX-50	1"	1.44	200 psi	0.45	50 ft	Coil	None
RT-1000XX-100	1"	1.44	200 psi	0.45	100 ft	Coil	None

\* 300 psi (2.1 MPa) at 70° F (21° C), 250 psi (.72 MPa) at 150° F (+66° C)

\* Weight Per Foot does not include fittings

\* **Strain Relief(s) / Bend Restrictor(s)** are available and may be added to assemblies at a Net (\$) increase per assembly

**TO PLACE AN ORDER:**

Use the above **Item Number** and appropriate letters for **color** choice in the blank space indicated by **XX**.

**EX:** A reel of 3/8" Flex RT with Red cover would be ordered as: **RT-0375RD-RL**

**RD = Red, GR = Green, BL = Blue, YW = Yellow, BK = Black**