

Since 1861
Keenan

Acoustical Ceiling Tile Paint MK278

Keenan Acoustical Ceiling Tile Paint is designed to restore old acoustical tiles, with minimal effect on their acoustical properties. It is formulated with high hiding pigments to cover most imperfections present on tiles. Its low odor and fast drying characteristics make this the perfect product for schools, office buildings, hospitals, nursing homes, stores and other commercial buildings.



- Spatter resistant
- Low reflective flat finish
- Low odor
- Low VOC formula meets or exceeds Green Seal and LEED[®] green building requirements.

Distributed by Keenan Paint Co.
1851 Flatbush Avenue, Brooklyn, NY 11210 • 718.338.7800

Scanned with

Recommended Uses:	Keenan Acoustical Ceiling Tile Paint is designed to restore old acoustical tiles, with minimal effect on their acoustical properties.
Surface Preparation:	PROPER SURFACE PREPARATION IS ESSENTIAL TO EVERY SATISFACTORY PAINT JOB. Loose soot, dust, peeling paint and dirt should be removed from the ceiling surface prior to applying Keenan Acoustical Ceiling Tile Paint. Badly damaged, stained or discolored tiles should be replaced. Grease and other substances that might interfere with adhesion of the tile paint to the grids and t-bars should be removed with a premium quality surface cleaner. All glossy surfaces should be lightly sanded before applying Acoustical Ceiling Tile Paint. Metal tracks subject to rusting should be primed with a premium quality rust preventive primer. WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead . Caution: Water stains should be completely dry and spot primed with a premium quality stain blocking primer. Any active water problems present in the ceiling should be corrected before applying the product. Nicotine on the surface may result in yellow discoloration - Nicotine stains should be removed from the tracks using a damp sponge and detergent as needed, then primed with a premium quality stain blocking primer to prevent bleed thru into the Acoustical Ceiling Tile Paint.
Application:	DO NOT USE ADDITIVES IN THIS PRODUCT! Keenan Acoustical Ceiling Tile Paint is formulated for ideal performance. Any additions to it will hurt its performance. Stir thoroughly. Designed for spray application, using an airless sprayer at a pressure only high enough to achieve a solid spray fan and using a 0.013-0.017 spray tip. It should be applied at 1-mil wet, with 50% overlap. Follow equipment manufacturer's instructions for proper use. Apply only when surface and air temperature are greater than 50°F and less than 95°F.
Finish:	Flat
Colors:	White. Can be tinted with maximum 2oz. of universal colorants per gallon. This product is not controlled as a tinting base, so final color may vary.
Viscosity:	70-75 KU
Weight per Gal.:	11.37lbs. +/- 0.15
Coverage:	On flat acoustical tiles, coverage is approximately 300 sq. ft. per gallon (less on extremely textured porous tiles). Spread rate will also be affected by the application method and thinning of the paint.
Dry Time:	Tack free: 30 minutes; Recoat: 4-hours; Full cure: 7 days. High humidity and low temperature will prolong dry time.
Clean-up:	Wash tools and equipment immediately with soap and warm water.
Thinning:	Thinning is not required, but up to 1/2 pint of water per gallon of paint may be added.
Flash Point:	None, water-based paint.
Fire Retardant Rating:	N.F.P.A. Class "A" on non-combustible surfaces.
V.O.C. (V.O.S):	This product contains less than 25 grams VOC/VOS per liter of coating (0.21 lbs. per gallon).
Caution:	CAUTION! Avoid prolonged contact with skin or breathing of spray mist. Close container after each use. Do not take internally. KEEP OUT OF REACH OF CHILDREN. Free of lead, mercury and pollution hazards. Disposal information: Small amounts of this product may be dried on newspaper or rags, and then disposed of as regular trash. Empty containers can be recycled in your local recycling program. FOLLOW LOCAL COMMUNITY WASTE DISPOSAL GUIDELINES.
First Aid:	If you experience difficulty in breathing, eye watering, headache or dizziness, increase fresh air, wear an appropriate NIOSH/MSHA approved mask during application; or leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. Do not breathe vapors or spray mist. Ensure good cross ventilation during application and drying. In case of eye contact, flush with water for 15 minutes; for skin, wash with soap and water. In case of spill: Absorb with inert material and dispose of as explained in "Disposal information" above.
Disclaimer:	The information contained herein is presented in good faith. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must take independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.
Limited Warranty:	Keenan Paint Co. warrants the performance of this product when applied in complete accordance to label directions and will refund the purchase price or replace this product within one year of date of purchase if defective. Keenan Paint Co. will not be liable for cost of labor or any incidental or consequential damages.