

Keenan

HOLBRO C.E. VAULT PAINT

Keenan Holbro C.E. Vault Paint is a fast drying waterborne acrylic paint, designed for all types of interior and exterior surfaces. It dries in approximately 1 to 2 hours to a long lasting, durable Semi-Gloss finish, with excellent adhesion and water resistance. It flows smoothly and levels away brush marks like an alkyd enamel. Its film is not affected by alkalinity in masonry, which makes this an ideal all purpose floor finish for all substrates.



- Meets or Exceeds LEED green building requirements;
- Interior/exterior
- Fire retardant rating N.F.P.A. Class "A" when tested on non-combustible substrates, non-flammable;
- Toughest long-wearing finish;
- Self-priming;
- Fast drying;
- Low odor, no solvent fumes.

Distributed by Eastern Paint Industries
1851 Flatbush Avenue, Brooklyn, NY 11210 • 718.338.7800

Recommended Uses:

Ideal inside or outside, on new or old masonry or properly primed metal surfaces.

Surface Preparation:

All surfaces must be clean and free of wax, dirt, dust, oil, grease and peeling paint. Efflorescence (a white powdery deposit) often found on masonry surfaces should be removed by brushing with a stiff wire brush, then etched with muriatic acid. Rinse thoroughly with clean water and allow to dry before painting.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

NEW OR UNPAINTED SURFACES: No priming is necessary on these surfaces if they are in sound condition. Unpainted concrete surfaces frequently exhibit a fine dust of cement particles that result from surface drying as the concrete sets. This condition should be treated like efflorescence as mentioned above. Allow new concrete to set for 30 days before painting.

PREVIOUSLY PAINTED SURFACES: No priming is needed unless the surface is deteriorating or chalking, in which case it should be cleaned and primed with an alkyd primer. Dull all glossy or smooth surfaces by lightly sanding.

Note: Keenan Holbro C.E. Vault Paint is not recommended for painting new pressure treated lumber.

Application:

- Mix thoroughly before using. Do not thin. It can be applied by brush, roller or spray. For brush application, a good quality synthetic or nylon bristle brush is recommended.
- For roller application, use a 1/4 nap roller for smooth surfaces and 3/8" to 3/4" nap roller for rough surfaces.
- For spray application, tip sizes and atomization pressures will vary with the type of equipment, viscosity and temperature. Use equipment manufacturer's recommendations for spray application.
- Do not apply when air or surface temperature is below 50°F.

Finish:

Medium Gloss 60°Gloss = 20 to 30

Colors:

Available in White and New Gray.

Viscosity:

80 - 90 ku

Weight per Gal.:

9.7 + 0.2 lbs per gallon

Coverage:

One coat is usually sufficient in most cases. Contrasting colors and rough surfaces may require more than one coat.

Spreading Rate:

One gallon covers approximately 400-450 Sq. Ft. per gallon.

Dry Time:

Dries in approximately 1-2 hours under normal conditions. High humidity and low temperatures may prolong dry time. Allow to dry overnight before recoating.

Clean-up:

Clean-up with warm water and soap.

Thinning:

Thinning not recommended.

Flash Point:

Water based paint.

V.O.C.(V.O.S.)

Contains max 100 gms./ltr. Or 0.83 lbs./gal VOC.

Cautions:

USE ONLY WITH ADEQUATE VENTILATION.

Avoid prolonged contact with skin or breathing of spray mist.

Do not take internally. Keep from freezing.

IMPORTANT SAFETY PRECAUTION: For surfaces that will be occasionally damp or wet, we recommend the addition of a good quality non-skid additive to Keenan Holbro C.E. Vault Paint before application. Not recommended for driveways or garage floors because of tire marking.

CAUTION! Do not take internally. Avoid contact with eyes and prolonged contact with skin or breathing of spray mist. Close container after each use.

KEEP OUT OF REACH OF CHILDREN.

Disposal information: Small amounts of this product may be dried on newspaper or rags, and then disposed of as regular trash. Empty containers can be recycled in your local recycling program. FOLLOW LOCAL COMMUNITY WASTE DISPOSAL GUIDELINES.

First Aid:

In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. If swallowed, do not induce vomiting. Call physician immediately. If spilled, contain spilled material and remove with inert absorbent.

Limited warranty:

Keenan Paint Co. warrants the performance of this product when applied in complete accordance to label directions and will refund the purchase price or replace this product within one year of date of purchase if defective. Keenan Paint Co. will not be liable for cost of labor or any incidental or consequential damages.

Disclaimer:

The information contained herein is presented in good faith. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must take independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.

Revised February 27, 2009