

# Keenan

## RUST PREVENTIVE MARINE FINISH

Rust Preventive Marine Finish is designed as a rust preventative coating for metal substrates. It is easy to apply, has tenacious adhesion, has excellent wetting properties and exhibits an excellent appearance once cured. Rust Preventive Marine Finish is ideal for a myriad of metal substrates anywhere beauty and performance is desirable. Not recommended for immersion service.



- Interior/exterior alkyd base gloss finish
- OTC Compliant
- Available in white/bases & ready made colors
- Highly durable finish
- Resistant to wear & scuff marks
- Use on metal surfaces

Distributed by Eastern Paint Industries  
1851 Flatbush Avenue, Brooklyn, NY 11210 • 718.338.7800

Scanned with

Recommended Uses:	Use on properly prepared metal, on exterior or interior surfaces where a quick drying, durable, high gloss finish is desired. Can be used on surfaces such as: walls, doors, windows, furniture, playgrounds, machinery, tools, farm and lawn equipment, fences, posts, etc.
Surface Preparation:	All surfaces must be clean and free from dirt, grease, oil or peeling paint. All glossy surfaces should be lightly sanded and cleaned before painting. <b>New or unpainted surfaces:</b> All new and unpainted surfaces should be primed with recommended primers. Unpainted metals subject to rusting should be primed with an anti-rust primer. <b>Previously painted surfaces:</b> Previously painted surfaces in sound condition do not require primer. <b>WARNING!</b> If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to <a href="http://www.epa.gov/lead">www.epa.gov/lead</a> .
Application:	<b>For best results, use:</b> <b>Brush:</b> Any good quality bristle brush. <b>Roller:</b> 1/4" nap roller cover for smooth surfaces, and 3/8" to 1/2" nap roller for rough surfaces. <b>Spray:</b> A tip size from 0.018 to 0.021 inches, and atomizing pressure required to maintain a 8" to 10" fan at 1 foot distance. For conventional spray, use 0.028" to 0.07" fluid nozzle with air pressure to give 6" to 12" spray pattern at 8" to 12" distance.
Finish:	High Gloss. 60° Gloss = over 90
Colors:	Available in popular ready-mixed colors.
Viscosity:	75-80 KU
Weight per Gal.:	7.4 – 9.9 lbs. per gallon depending on color selected.
Coverage:	One coat over most surfaces.
Spreading Rate:	400 sq. ft. per gallon over smooth surfaces. Coverage will be somewhat less on rough and textured surfaces.
Dry Time:	6 –8 hours under normal conditions. May take longer to dry when humidity is high. Recoat time 12-18 hours.
Clean-up:	Tools and equipment should be cleaned with mineral spirits.
Thinning:	Thinning not recommended.
Flash Point:	107°F
Federal Spec. Equivalent:	TTE-487
V.O.C.(V.O.S.)	Contains max 400 gms./ltr. Or 3.3 lbs./gal VOC.
Cautions:	<b>Combustible!!</b> Keep out of reach of children. Keep away from heat and flame. Avoid prolonged contact with skin or breathing of spray mist. Close container after each use. Do not take internally. Use adequate ventilation. Keep from Freezing. Do not apply when temperature is below 50°F. To avoid spontaneous combustion, be sure to dispose of rags into closed containers. <b>Contains Petroleum Distillate.</b> Keep away from heat, sparks and flame. To avoid breathing vapors or spray mist, open windows and doors and use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection. (NIOSH/MSHA TC 23C or equivalent) or leave the area. Close container after each use. Avoid contact with skin. <b>Contains Linseed Oil. Danger:</b> Rags, steel-wool, or waste soaked with linseed oil may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel-wool or waste in a sealed water filled container, and dispose of. <b>Disposal information:</b> Dry empty containers can be recycled in your local community recycling program. Follow Local Community Waste Disposal Guidelines.
First Aid:	In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. If swallowed, do not induce vomiting. Call physician immediately. If spilled, contain spilled material and remove with inert absorbent.
Disclaimer:	The information contained herein is presented in good faith. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must take independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.