



CLASSIC UV STERILIZER SERIES



CLASSIC UV SIZING CHART

MODEL	FRESH WATER TANK GALLONS	30,000 $\mu\text{w}/\text{cm}^2$ (EOL) GPH	SALT WATER TANK GALLONS	45,000 $\mu\text{w}/\text{cm}^2$ (EOL) GPH	60,000 $\mu\text{w}/\text{cm}^2$ (EOL) GPH	75,000 $\mu\text{w}/\text{cm}^2$ (EOL) GPH	90,000 $\mu\text{w}/\text{cm}^2$ (EOL) GPH
Classic 8 Watt	200	642	70	428	321	256	214
Classic 15 Watt	500	700	75	466	350	280	233
Classic 25 Watt	1,200	1,200	150	800	600	480	400
Classic 40 Watt	2,000	2,900	325	1,930	1,450	1,160	967
Classic 57 Watt	3,000	3,200	355	2,133	1,600	1,280	1,066
Classic 80 Watt	4,400	3,678	600	2,452	1,839	1,471	1,226
Classic 114 Watt	4,400	3,900	700	2,600	1,950	1,560	1,300
Classic 120 Watt	6,000	4,080	900	2,720	2,040	1,632	1,360



IMPORTANT FOR AQUARIUM APPLICATIONS

REEF TANKS

A UV rated in the 30,000 or 45,000 column is ideal for the reef environment. UV's used at higher kill rates will destroy the planktonic food supply for the reef.

MARINE FISH TANKS

(No reef or live rock) A UV rated in the 75,000 or 90,000 column will be the most effective at controlling fish disease. All UV dosages are calculated at the end of lamp life (14 month).