



Your most beautiful floor starts with Parkside Timber's highly impressive Australian hardwood flooring.





Introduction

Parkside Timber has been producing hardwood products for Australians for over 60 years. The natural durability of the species produced plus the high manufacturing standards we uphold means our products are among the highest quality in the marketplace.

PARKSIDE FLOORING is an end matched, tongue and groove flooring which has been used by generations to complete their most beloved possessions. Today PARKSIDE TIMBER FLOORING is popular due to its warmth, elegance and classic style.

Key Benefits

- Parkside products are grown in Australia and produced and manufactured for Australian conditions.
- Timber Floors have an environmental impact which creates five times less carbon emissions than ceramic tiles.
- Parkside flooring includes a stunning range of tongue and groove solid timber flooring, and 14mm three lamella solid overlay.
- Parkside flooring is easy to care for, once installed and sealed, your hardwood floor will look beautiful for years to come with just routine sweeping and maintenance.
- Quality Parkside floors are excellent for asthmatics and hay fever sufferers as they are not conducive to dust mites and other allergens.

Easy Installation

Once laid, Parkside flooring's superb qualities allows for traffic immediately, allowing other trades to apply their finishing touches before sanding and the final application of the desired finish.

Our tongue and groove boards widths up to 80mm can be secret nailed while boards 130mm are required to be top nailed as per the Australian Standard.

Timber flooring can be a do-it-yourself job as long as you understand your environment and correct installation practices.

For further information contact TIMBER QUEENSLAND to obtain copies of their Technical Data Sheets No.17 - Timber Floors Pre Installation Assessment and No.18 - Timber Floors Recommended Installation Practices.

Please note:

Timber flooring is Hygroscopic which means that when conditions where the floor is laid become moist or dry, the timber will adjust to that environment.

Please note: Colour variations within timber species in normal photography are only indicative of the colour range.



Species

Queensland Spotted Gum

Hardness 11



Grey and Red Ironbark

Hardness 14



Queensland Reds

Hardness 12



Mixed Blends

Hardness 10.5



Hardness refers to the Janka rating which is the hardness level given to each species. The higher the number, the greater the hardness.



Grades

Select | Standard | Feature



Sizes and Lengths

80 | 130 x 19mm - Lengths: 0.9m - 5.9m

75 | 125 x 14mm - Standard & Better | Feature Grade



Durability

Class 1 Above ground product



Certification

Manufactured to comply with AS 2796

Fire rated in accordance with AS 3959-2009 and BAL 19 as a minimum

Spotted Gum and Red Ironbark are fire rated to BAL 29

Chain of Custody as per AS 4707-2008 PEFC / AFS