



ES-852T22C-S6-S



ES-852T22C-S6-MI-S



ES-852T21C-S6-MI-S



EL-852T38I-S6-S



DL-852T28B-S6-S



BS-852T23T-S6-MI-S



BS-852T23C-S6-S



BS-852T23C-S6-MI-S



BS-852T12T-S6-C-MI-S



BS-852T11T-S6-C-MI-S



BL-852T48S-S6-S



BL-852T48A-S6-S



ES-855P22T-S8-MI-S



ES-855P22C-S8-S



ES-855P22C-S8-MI-S



ES-855P12T-S8-C-MI-S



ES-855P11T-S8-C-MI-S



EL-855P38I-S8-S



DL-855P28B-S8-S



BS-855P23T-S8-MI-S



BS-855P23C-S8-S



BS-855P22C-S8-MI-S



BS-855P12T-S8-C-MI-S



BS-855P11T-S8-C-MI-S





BL-35138S-MI

System Overview ZKTeco 5MP HD analog camera adopts advanced 4-in-1 ISP and 1/2.8" image sensor, featured by the excellent image details with wide FOV, compact and...





BL-35H44S-MI

System Overview ZKTeco 5MP HD analog camera adopts advanced 4-in-1 ISP and 1/2.5" image sensor, featured by the excellent image details with wide FOV, compact and...





BL-35H33S-MI

System Overview ZKTeco 5MP HD analog camera adopts advanced 4-in-1 ISP and 1/2.5" image sensor, featured by the excellent image details with wide FOV, compact and...



ES-32E11C/12C-C

 \cdot 1/2.8"2MP CMOS Sensor \cdot TVI / AHD / CVI / CVBS video output \cdot 10 ~ 20m white light range \cdot 2.8 / 3.6mm high-quality lens \cdot Lightning protection up to 6kV \cdot Supports...



ES-32E11C/12C-C

· 1/2.8"2MP CMOS Sensor · TVI / AHD / CVI / CVBS video output · 10 ~ 20m white light range · 2.8 / 3.6mm high-quality lens · Lightning protection up to 6kV · Supports...



BL-32G44S-MI

System Overview ZKTeco 1080p HD analog camera adopts advanced 4-in-1 ISP and 1/2.9" image sensor, featured by the excellent image details with wide FOV, compact and...



ES-32E11C/12C-C

- 1/2.8"2MP CMOS Sensor
- TVI/AHD/CVI/CVBS video output
- 10~20m white light range · 2.8/3.6mm high-quality lens



Z8516NEQ

ZKTeco's Z8508 / 516NEQ is a network video recorder (NVR) supports 8- channel or 16-channel 5MP IP camera input and preview. Z8508/516NEQ support H.265...



Z8508NEQ

ZKTeco's Z8508 / 516NEQ is a network video recorder (NVR) supports 8- channel or 16-channel 5MP IP camera input and preview. Z8508/516NEQ support H.26



Z8504NEQ

ZKTeco's Z8504NEQ is a network video recorder (NVR) offers a good quality for video surveillance. Z8504NEQ supports H.265 decoding and 4K HDMI output. Its user



Z8516/32NFR

Features • H.265 + / H.265 / H.264 + / H.264 Decoding • Support 16 / 32CH 4K Resolution Preview and Playback • Support HDMI up to 4K output • DHCP, FTP, DNS, DDNS, . . .



Z85128NTR

H.265 / H.264 decoding • Support 128-channel
4K IP cameras input • Support 16 channels real-time
playback synchronously • HDMI output up to 4K high...



Z8508NEQ-8P

ZKTeco's Z8508NEQ-8P is a network video recorder (NVR) supports 8-channel 5MP IP camera input and preview. Z8508NEQ-8P support H.265 decoding and Full HD HD.



Z8504NEQ-4P

ZKTeco's Z8504NEQ-4P is a network video recorder (NVR) with 4 Power over Ethernet (PoE) port for IP camera connection. This NVR can deliver 4K resolution an



Z8504/08NER-4P/8P

Features • H.265 + / H.265 / H.264 + / H.264 Decoding • Support 4 / 8CH 5MP Resolution Preview and Playback • Support HDMI up to 1080P output • DHCP, FTP, DNS, DDN . .



Z8516NFR-S



Z8516NFR-16P-S



Z8516NEQ-S



Z8508NEQ-S



Z8508NEQ-8P-S



Z8504NEQ-S



Z8504NEQ-4P-S



PL-852D30M

System Overview PL-852D30M is featured by the mini compact design which is only 6 inches and easy for installation. Powered by the cutting edge human detecti...



PL-852D18M

System Overview PL-852D18M is featured by the mini compact design which is only 6 inches and easy for installation. Powered by the cutting edge human detecti...



PS-855C30L

System Overview PS-855C30L is featured by the mini compact design which is only 5.1 inches and easy for installation. Powered by the cutting edge human detecti...



PS-855C18L

· 1/3" 5MP CMOS sensor · High quality 18X industrial camera module · Support dual stream encoding · Linkage with sound and auto track by human detection · Built in...



Z8404/08XEC-CL

- H.265 / H.264 decoding
- Support AHD / TVI / CVI / CVBS / IP video input
- Hybrid extra IP channels input up to 4 channels



Z8404/08XE-CL

• H.265 / H.264 decoding • Support AHD / TVI / CVI / CVBS / IP video input • Hybrid extra IP channels input up to 4 channels • Support 4- or 8-channel 5MP Lite resolution...



Z8416XF-CL

- H.265 / H.264 decoding
- Support AHD / TVI / CVI / CVBS / IP video input
- · Hybrid extra IP channels input up to 8 channels



PL-32C33D

System Overview The Pro series is a range of competitive PTZ with a sturdy design. The series is an ideal choice for industrial solutions, such as buildings, factories, schools,...



PL-35C33D

Functions · 1/2.7" 5MP low light CMOS · Max 25 / 30fps@5MP · AHD / TVI / CVI / CVBS video output · Support up to 33X optical zoom · IP66 · DWDR / BLC / 2D & 3D no...



PL-35C20D

System Overview Functions · 1/2.7" 5MP low light CMOS · Max 25 / 30fps@5MP · AHD / TVI / CVI / CVBS video output · Support up to 20X optical zoom · IP66 · DWDR / BLC / 2D...



ZD27-4K

· 27-inch UHD Monitor · LED backlit technology with ultra HD 3840 x 2160 · 16.7 million colors display images perfectly · Multiple interfaces: HDMI, VGA, RCA · Built-in...



ZD27-2K

· 27-inch FHD Monitor · LED backlit technology with Full HD 1920 * 1080 · 16.7 million colors display images perfectly · Multiple interfaces: HDMI, VGA, RCA · Built-in...



ZD19-2K

- · 19-inch HD monitor
- · LED backlit technology with HD 1440 x 900
- · 16.7-million colors display images perfectly



PE24-240

• 24 10 / 100BaseT RJ45 ports • 2 sets of 10 / 100 / 1000M gigabyte combo ports • The total power budget is 400W, and the max. PoE power output is 30W • Support IP-MAC...



PE16-180

System Overview PE16-180 is an advanced PoE switch providing a network point for data transmission and power supply. It has 16 PoE ports that can provide standard...



PE08-120

• Commercial standard switch with 2 layers of network artribute • 250 meters of PoE transmission distance of power and data • Max. PoE power output 30W for each...



PE04-60

 Commercial standard switch with 2 layers of network artribute • 250 meters of PoE transmission distance of power and data • Max. PoE power output 30W for each...



Pole mount L*W*H: 150mm * 150mm * 50mm (L*W*H), weight: 0.8KG For casing: BS -C, ES-C, BL-S, BL-L, EL-I, BS-B, ES-B, GB0



Corner mount L*W*H: 150mm * 150mm * 128mm (L*W*H), weight: 1KG For casing: BS -C, ES-C, BL-S, BL-L, EL-I, BS-B, ES-B, GB0



Corner mount 240mm * 143mm (L*W), weight: 1.7KG for analog PTZ model, PL-D



ZJ006

Corner mount: 180mm * 131mm * 127.25 (L*W*H), weight: 2.3KG for Human detection PTZ



ZJ007

Pole mount: 180mm * 138.8mm * 41.5mm (L*W*H), weight: 1KG for Human detection PTZ



PB06

Pendant bracket: length 200 * 89.5 * 110.5mm, top Φ46.7mm, weight: 0.52KG for 6 inch IP PTZ



PB04

Pendant bracket length 135mm, top Φ128mm, weight: 0.52KG for analog PTZ model, PS-J



PB05

Pendant bracket length 254mm, top Φ121mm, weight: 0.76KG for analog PTZ model, PL-D



Pole mount 195mm * 125mm (L*W), weight: 1.08KG for analog PTZ model, PL-D



GB01

Waterproof Junction box •135mm * 45.5mm (Φ*H),
weight 0.45kgs • For cases: BS-K, BS-B, ES-H, BL-L, El-I, BS-C,
ES-C, BL-S



YT3011-3MP

• CS lens, 3.6 - 11mm, F1.5, 1/1.8" • 3MP, Manual Zoom & Focus, Auto Iris



CS-D0550IR(6MP)

• CS lens, 5 - 50mm, F1.4, 1/2.7" • 6MP, Manual Zoom & Focus, Auto Iris



DV3.9x11SR4A-SA1L

• Fujinon C lens,11 - 43mm, F1.5, 1/1.8" • 8MP, Manual Zoom & Focus, Auto Iris