

FIX-O-FLEX HAFTGRUND

Properties:

FIX-O-FLEX HAFTGRUND is a solvent-containing cleaning agent for surfaces where *FIX-O-FLEX* adhesion and sealing compounds will be applied.

FIX-O-FLEX HAFTGRUND is dust binding and cleans surfaces with greasy and oily residues.

Technical data:**Substance data:**

Consistency	liquid	
Colour	colourless	
Odour	of ethanole	
Spec. density (23°C)	approx. 0.79 g/cm ³	DIN EN ISO 2811-1
Dyn. viscosity (23°C)	approx. 6 mPas	DIN EN ISO 2555
Processing temperature	5 - 30°C	substrate temperature

Processing:

FIX-O-FLEX HAFTGRUND is evenly applied on the surface. Once the residues are slightly loosened they are removed with an absorbent cloth or whipped off.

This should be repeated until the surface is completely clean.

Safety information:

FIX-O-FLEX HAFTGRUND is classified as hazardous according to Regulation (EC) 1272/2008 (CLP).

Danger: Highly flammable liquid and vapour.

It is therefore necessary, before beginning processing, to become familiar with the precautions and safety advice as indicated in the material safety data sheet.

Packaging:

500 ml tin
1000 ml tin

Bigger packaging on request.

Storage:

Shelf life at least 12 month in original packaging when stored in dry conditions between 15-25°C, protected from heat, frost and direct sunlight.

After the expiration the use of the product is generally not recommended, unless an approval has been provided by TPH. This approval can only be obtained by the quality assurance department of TPH releasing the material after verification of main properties being within specification..

Disposal:

Small quantities of cured product residues can be disposed of as normal domestic waste. Dispose of not cured product components must be effected in accordance with the corresponding local regulations. For further information please refer to the material safety data sheets.

**Legal notice:**

The correct and thus successful application of our products is not subject to our control. A guarantee can be issued for the quality of our products within the framework of our sales and supply conditions, however not for successful processing. All data and specifications in this specification sheet are based on the present state of the art and the right to changes and adaptations for the sake of development remains explicitly reserved. The consumption specifications designated by us can be only average empirical values, where deviations are possible on an individual basis and therefore cannot be excluded by us.

TPH Bausysteme GmbH
Nordportbogen 8
D-22848 Norderstedt

Tel.: +49 (0)40 / 52 90 66 78-0
Fax: +49 (0)40 / 52 90 66 78-78
e-mail info@tph-bausysteme.com
Web www.tph-bausysteme.com

TPH.
Waterproofing Systems