



TABLE OF CONTENTS

	\bigcirc IID	JOURNEY
h	()	
	OUN	JOUNIEL

6 OUR LEGACY AND MILESTONES

7 OUR MISSION

8 CRAFTING QUALITY

9 CERTIFICATES AND TESTS

10-11 COLOR PRODUCT GUIDE

SLIDING DOORS: 12-25

14-15 MOREVIEW S

16-17 MOREVIEW

18-19 PERFORMANCE LIFT'N'SLIDE

20-21 PERFORMANCE PRIMEVIEW

22-23 BI-FOLD TM 77

24-25 ECO DP SLIDE

WINDOWS: 26-37 -

28-29 MOREVIEW

30-31 INDUSTRIAL

32-33 PASSIVE TM 102

34-35 PERFORMANCE TM 77

36-37 ECO TM 62

DOORS: 38-51 -

40-41 MOREVIEW

42-43 PASSIVE TM 102

44-45 PERFORMANCE TM 77 PRESTIGE

46-47 PERFORMANCE TM 77

48-49 ECO TM 62

50-51 INTERIOR PBI 50

CURTAIN WALLS: 52-59

54-55 FA 50N DESIGN LINE

56-57 FA 50N SMOOTH LINE

58-59 PANORAMIC CW WINDOW

ADD-ONS: 60-77 —

62-63 SUNSHADES AND LOUVERS

64-65 JULIET BALCONY

66-67 VERTILINE

68-69 INSECTS SCREEN

70-71 GLASS RAILINGS

72-73 LED PROFILE

74-75 ECLIPSE 33

76-77 LINEAR DRAINAGE







OUR JOURNEY

Our history is deeply rooted in family values and began in 1990. At the heart of our company lies a commitment to transforming architectural dreams into tangible structures.

1.

From our humble beginnings in a small garage in Poland,

We have grown through our unwavering commitment to client satisfaction, rigorous research, and dedication to crafting superior products. This journey has established us as frontrunners in the European market of aluminum windows, doors, and facades.

3.

Enduring Commitment of Our U.S-Based Entity:

Delivering Timeless Products with Unmatched Technical and Maintenance Support Spanning over three decades in the industry, our brand has become synonymous with luxury, exceptional style, and a steadfast commitment to quality. Each product we create is a testament to precision and meticulous attention to detail, designed to align perfectly with your vision.

Our state-of-the-art manufacturing facility, effective warehousing strategies, and unwavering dedication to timely deliveries reflect our pursuit of excellence in every aspect of our business.



2.

We Expanded Beyond Europe with 30-year experience:

In a significant strategic step,
CEO Karolina Mzyk-Callias relocated
to the United States, opening a new
and exciting chapter in our journey.
This move introduced our high-quality products
to a dynamic new market. Today, our presence
stands as a testament to the fusion of European
design elegance with American innovative spirit.



4.

Choosing us is more than just a product choice;

It's entering a partnership rooted in trust, superior craftsmanship, and a pledge to exceed your expectations.



OUR LEGACY AND MILESTONES

A LEGACY OF INNOVATION AND GROWTH

YAWAL's journey began in September 1990, marking the start of a transformative era in aluminum joinery. We were pioneers in utilizing thermally insulated profiles from Western Europe, setting a new standard in the industry.

- EXPANSIONS AND TRANSFORMATIONS
- COMMITMENT TO SUSTAINABILITY
- INNOVATIVE BREAKTHROUGHS
- ADAPTING TO MARKET NEEDS

YAWAL's evolution features expansive growth, the introduction of the cutting-edge Moreview system, a strategic upscaling of production to meet market needs, and an enduring pledge to environmental stewardship.



OUR MISSION

MISSION

WE PROVIDE THE HIGHEST QUALITY EUROPEAN ALUMINUM SYSTEMS WITH THE BEST, DEDICATED CUSTOMER SERVICES FOR THE AMERICAN MARKET.

VALUES:



EXPERIENCE



CUSTOMER ORIENTATION



COMMITMENT



PROFESSIONALISM



INNOVATION



ECOLOGY





CRAFTING QUALITY

STEP BY STEP

AT OUR COMPANY, SUPERIOR CUSTOMER SERVICE IS AT THE CORE OF EVERYTHING WE DO. HERE'S A SIMPLE OVERVIEW OF THE PROCEDURES WE FOLLOW TO CATER TO YOUR NEEDS:









1. CLIENT CONSULTATION

We begin with an in-depth consultation with clients to understand their specific needs and preferences.

2. ESTIMATION

Following the consultation, we provide accurate and tailored estimations to align with your specifications.

3. EXTRUSION

Transitioning to the extrusion phase, we mold aluminum into precise profiles for windows and doors.

4. THERMAL INSULATION

Our attention then gravitates towards embedding advanced thermal insulation for top-tier energy efficiency.

5. VARNISHING

With the structure in place, protective and aesthetic coatings are applied to strike a balance between longevity and style.

6. FABRICATION OF WINDOWS

Meticulous assembly of window units follows.

7. GLAZING

Incorporating the right glass elements, we ensure clarity and robust functionality.

8. PACKAGING AND DELIVERY

Concluding our process, our products are securely packaged and delivered, reaching you in impeccable condition.

9. INSTALLATION SUPPORT AND TRAINING

We provide on-site training and supportduring installation, ensuring seamless integration of our products and empowering clients with essential knowledge.

10. ANNUAL MAINTENANCE CHECK

Our service extends to annual maintenance checks, offering post-sale verification to maintain the optimal performance and longevity of our products.

We are dedicated to exceeding your expectations with every order and interaction.

We anticipate a fruitful collaboration on future projects, and we hope to be your first choice time and again.



CERTIFICATES AND TESTS

ISO 9001: 2015COMPLIANT:

Guiding our design, production, and distribution to uphold the highest standards

ENVIRONMENTAL STEWARDSHIP:


Adhering to the ISO 14001:2004 Environmental Management System, reflecting our dedication to sustainability.

RECOGNIZED CERTIFICATIONS:

Proudly accredited by AAMA, NFRC, and Passive House, with hurricane certification in progress.

QUALICOAT LICENSED:

Including Seaside, guarantees consistent excellence in our aluminum powder varnishing.





COLOR PRODUCT GUIDE

STANDARD COLORS



RAL 9005 MATT



RAL 7016 MATT



RAL 9007 MATT



RAL 7021 MATT



RAL 7016 STRUCTURE



RAL 9006 MATT



RAL 7021 STRUCTURE



RAL DB703 MATT



RAL 9016 MATT

SPECIAL COLORS



CORTEN STEEL 1037029



RAL 7016 METALIC



SEPIA BROWN 029/69740



TWILIGHT 1226709

The colors shown above are for illustrative purposes only.

In the catalog presented only a part of the available color palette, for full color pattern inquire at support@yawalusa.com

COLOR PRODUCT GUIDE

WOODGRAIN COLORS



LIGHT OAK 916 1402 03



WALNUT 733 1829 11



OAK 797 2305 17



WINCHESTER 682 1403 01



PINE WITHOUT KNOTS 716 1501 01



CHERRY 716 1401 01



DARK WALNUT 755 2301 03



GOLDEN OAK 739 2301 02



PINE 451 2103 01



CHERRIES



DARK CHERRY 75 1403 01



MAHOGANY 742 1704 02

The colors shown above are for illustrative purposes only.

In the catalog presented only a part of the available color palette, for full color pattern inquire at support@yawalusa.com



SLIDING DORS

EXPERIENCE THE ELEGANCE OF OUR SLIDING & FOLDING DOORS, BLENDING FUNCTIONALITY WITH DESIGN TO CREATE BRIGHT, EXPANSIVE SPACES. EACH PIECE REFLECTS A COMMITMENT TO COMFORT AND MODERN INNOVATION.









SLIDING DOORS


MOREVIEW S



DISCOVER THE BEAUTY OF THE MOREVIEW S, WHERE BOLD DESIGN MEETS CRYSTAL-CLEAR VIEWS.
DESIGNED FOR EVERYDAY LIVING, ENJOY THE GREAT OUTDOORS FROM THE COMFORT OF YOUR HOME WITH THESE DOORS.



MOREVIEW S DOUBLE TRACK






Invisible track system is an ultra-modern solution that allows for an almost complete blurring of the boundary between the interior and exterior.

All structural elements are hidden under the floor. The user sees only narrow, gaps.' This solution enables virtually unlimited possibilities for arranging flooring at the junction of the home's interior and the external

environment, such as a terrace.







- Invisible track system
- Extremely high Visible Light Transmittance (VLT) with a minimal frame profile, offering a 98% unobstructed view
- 1-inch minimal interlock visible width
- Track frame profile seamlessly blended with the floor
- Motorized panels compatible with iOS and Android devices
- Fully integrated linear drainage system
- Capability for a full 90-degree corner opening
- Suitable for pocket installation
- Integrated insect screen




- Water Tightness: **5 psf**
- Designed Pressure: **LC 40 psf**
- Thermal Insulation: From 0.12 Btu/hft²F
- Acoustic Insulation: STC up to 42 dB
- Maximum Sash Weight: 3300 lbs (1500kg)
- Maximum Sash Height: 16 ft (5m)
- Maximum Sash Width: 21 ft (6,5m)
- Glazing: **Double and triple**






SLIDING DOORS

MOREVIEW



WORLD OF MOREVIEW, WHERE LIGHT AND SPACE UNITE IN STUNNING HARMONY. AN ARCHITECTURAL JOURNEY THAT CONNECTS YOU WITH THE GREAT OUTDOORS, FEATURING UP TO 98% TRANSPARENCY FOR A FLAWLESS FUSION OF INDOOR AND OUTDOOR LIVING.





[57.9mm]





FEATURES:

- Oversized dimension design with extremely large panel sizes
- Minimal frame profile offering exceptionally
- high Visible Light Transmittance (VLT), with a 98% non-obstructed view
- 1-inch minimal interlock visible width
- High resistance to wind loads
- Motorized panels compatible with iOS and Android devices
- Fully integrated linear drainage system
- Capability for a full 90-degree corner opening
- Suitable for pocket installation
- Integrated insect screen
- Static mullion supports for added stability
- Fixed glazing featuring an any-angle glass corner for versatile design options
- Easy maintenance without the need for panel removal




75/8" [192.4mm]

- Water Tightness: **5 psf**
- Designed Pressure: **LC 40 psf**
- Thermal Insulation: From 0.12 Btu/hft²F
- Acoustic Insulation: STC up to 42 dB
- Maximum Sash Weight: 3300 lbs (1500kg)
- Maximum Sash Height: 16 ft (5m)
- Maximum Sash Width: 13 ft (4m)
- Maximum Panel Width: 21 ft (6,5m)
- Glazing: Double and triple




SLIDING DOORS

PERFORMANCE LIFT'N'SLIDE



STEP INTO A BLEND OF STYLE AND
CONVENIENCE WITH OUR PERFORMANCE
LIFT'N'SLIDE SYSTEM. THIS DOOR GOES
BEYOND THE USUAL, FEATURING
EXTENSIVE GLAZING THAT OPENS UP YOUR
WORLD TO AN EXTRAORDINARY DISPLAY
OF LIGHT AND VIEWS.







FEATURES:

- Expansive glazing for enhanced light and views
- Advanced gasketing and Lift'n'Slide hardware for tightness
- 2" interlock for structural integrity
- Low-profile threshold design
- Automated systems with Bluetooth, eye-scan, and fingerprint access
- Customizable frame finishes,
- Including wood-like options
- Motorized panels compatible with iOS and Android devices
- Integrated linear drainage system



TECHNICAL PARAMETERS:


- Water Tightness: 12 psf
- Designed Pressure: **CW 60 psf**
- Thermal Insulation: From 0.12 Btu/hft²F
- Acoustic Insulation: STC up to 47 dB
- Maximum Panel Weight: 1000 lbs (450 kg)
- Maximum Panel Height: 11 ft (3,4m)
- Maximum Panel Width: 11 ft (3,4m)
- Glazing: Double and triple






SLIDING DOORS

PERFORMANCE PRIMEVIEW



ENHANCE YOUR EXPERIENCE WITH OUR PRIMEVIEW SOLUTION,
AN UPGRADE WITHIN THE
PERFORMANCE LINE. THIS VARIANT
REDEFINES MINIMALISM WITH
A MIRRORED DESIGN THAT BLENDS
IN WITH ITS SURROUNDINGS, OFFERING
A SEAMLESS AND VISUALLY STRIKING
EXPERIENCE.







FEATURES:

- Full glass, no visible profile slider, blending with wall structure
- Hardware invisible from outside
- Full glass house architecture
- Low-profile threshold design
- 2" interlock for structural integrity
- Motorized panels, iOS/Android compatible
- Advanced automation with Bluetooth, eye-scan, and fingerprint access
- Integrated linear drainage system



7½" [191.6mm]

TECHNICAL PARAMETERS:

- Water Tightness: 12 psf
- Designed Pressure: **CW 60 psf**
- Thermal Insulation: From 0.12 Btu/hft²F
- Acoustic Insulation: STC up to 47 dB
- Maximum Panel Weight: 1000 lbs (450kg)
- Maximum Panel Height: 11 ft (3,4m)
- Maximum Panel Width: 11 ft (3,4m)
- Glazing: **Double and triple**






SLIDING DOORS

BI-FOLD TM 77



BI-FOLD DOORS OFFER FLEXIBLE,
MULTI-PANEL DESIGNS FOR
DIVERSE CONFIGURATIONS,
OPTIMIZING SPACE UTILIZATION
AND BLENDING INDOOR-OUTDOOR
LIVING WITH STYLISH EFFICIENCY.







FEATURES:

- Best-in-class panel height
- Multiple panel options for various opening sizes
- Initial panel with pivot feature for easy access and folding
- Options for low thresholds
- Configurations include inward/outward and left/right opening
- Compact folding design for maximized open space
- Enhanced thermal efficiency
- Broad glazing surfaces for increased natural light




- Water Tightness: **5 psf**
- Designed Pressure: LC 35 psf
- Thermal Insulation: From 0.15 Btu/hft²F
- Acoustic Insulation: STC up to 42 dB
- Maximum Panel Weight: 440 lbs (200 kg)
- Maximum Panel Height: 12 ft (3,5m)
- Maximum Panel Width: 4 ft (1,2m)
- Glazing: **Double and triple**






SLIDING DOORS

ECO DP SLIDE




ELEVATE YOUR HOME'S AMBIANCE WITH OUR ECO DP SLIDE DOORS. THESE DOORS BLEND THE TIMELESS APPEAL OF SLIDING DOOR AESTHETICS WITH MODERN FUNCTIONALITY, SEAMLESSLY FITTING INTO A VARIETY OF RESIDENTIAL & COMMERCIAL ARCHITECTURAL STYLES.







ECO DP SLIDE WITH NARROW MULLION





FEATURES:


- Cost-efficient for light commercial and volume residential applications
- Options for Lift'n'Slide and sliding hardware
- High thermal performance
- Suitable for multi-unit residential construction
- Broad glazing surfaces to enhance natural light



TECHNICAL PARAMETERS:


- Water Tightness: **7.5 psf**
- Designed Pressure: LC 50 psf
- Thermal Insulation: From 0.23 Btu/hft²F
- Acoustic Insulation: STC up to 48 dB
- Maximum Panel Weight: 440 lbs (200 kg)
- Maximum Panel Height: 8 ft (2,44m)
- Maximum Panel Width: 4 ft (1,22m)
- Glazing: **Double**






WINDOWS

EXPLORE A FUSION OF STYLE AND ECO-CONSCIOUS DESIGNS WITH OUR WINDOWS COLLECTION. EACH WINDOW SHOWCASES A PERFECT BALANCE OF SCENIC ELEGANCE AND ENERGY EFFICIENCY. ENJOY BREATHTAKING VIEWS WHILE BENEFITING FROM TOP-NOTCH THERMAL AND ACOUSTIC PERFORMANCE, ALL DELIVERED WITH A STRONG COMMITMENT TO ENVIRONMENTAL RESPONSIBILITY.










WINDOWS

MOREVIEW WINDOW



ENTER THE REALM OF MINIMALISM AND CLARITY WITH THE MOREVIEW WINDOW SYSTEM. THIS INNOVATIVE DESIGN REDEFINES MODERN WINDOWS, BLENDING STREAMLINED AESTHETICS WITH FUNCTIONAL ADVANCEMENT. MOREVIEW OPENS UP VAST VIEWS AND INTEGRATES SUBTLY WITH CONTEMPORARY ARCHITECTURE, MAKING IT A TRANSFORMATIVE CHOICE.








FEATURES:

- Minimal frames and panel profiles
- Alternative to steel profiles
- Beveled glazing stop and SDL
- Visible width minimized to 2 inches (50mm)
- Super slim system, capable of fully replacing steel systems
- Modern design



TECHNICAL PARAMETERS:

- Water Tightness: 12psf
- Designed Pressure: CW 55psf
- Thermal Insulation: From 0.17 Btu/hft²F
- Acoustic Insulation: STC up to 48 dB
- Maximum Panel Weight: 330LB
- Maximum Panel Height: 9 ft (2,7m)
- Maximum Panel Width: 5 ft (1,5m)
- Glazing: Double and triple



WINDOWS

INDUSTRIAL



OUR INDUSTRIAL WINDOWS OFFER
A MODERN, ELEGANT CHARM. THE DESIGN
OF THIS SYSTEM ENHANCES SPACES
WITH MAXIMUM DAYLIGHT, ALIGNING
WITH MODERN ARCHITECTURAL TRENDS.
EXPERIENCE LIVING AREAS TRANSFORMED
BY ABUNDANT NATURAL LIGHT, ELEVATING
YOUR EVERYDAY.





INDUSTRIAL SLIM STYLE FIXED WINDOW

INDUSTRIAL SLIM STYLE TILT&TURN WINDOW









ONE SYSTEM THREE DIFFERENT STYLES:









FEATURES:

- Three industrial profile styles
- Variety of SDL (Simulated Divided Lite) and TDL (True Divided Lite) options
- Narrow sidelines, slim profile design
- Options for curved shapes
- Adaptive designs for windows and balcony doors, supporting multiple threshold types
- Hidden gravitational drainage with profile-driven condensate diversion
- Fully compatible with other Yawal systems
- Minimal visible width of 2.75" inches (71mm)
- Broad glazing surfaces for enhanced natural light



TECHNICAL PARAMETERS:

- Water Tightness: 12 psf
- Designed Pressure: CW 65 psf
- Thermal Insulation: From 0.13 Btu/hft2F
- Acoustic Insulation: STC up to 39-44 dB
- Maximum Panel Weight: 660 lbs (300 kg)
- Maximum Panel Height: 10 ft (3m)
- Maximum Panel Width: 5 ft (1,5m)
- Glazing: Double and triple

WINDOWS

PASSIVE TM 102





THE PASSIVE WINDOW EXEMPLIFIES
CUTTING-EDGE, ENERGY-EFFICIENT
CONSTRUCTION. TAILORED FOR AMBITIOUS
ARCHITECTURAL PROJECTS, IT PROVIDES
EXCEPTIONAL THERMAL INSULATION AND
VERSATILE GLAZING OPTIONS, CATERING
TO ECO-CONSCIOUS, LARGE-SCALE
DEVELOPMENTS.





PASSIVE TM 102 TILT&TURN WINDOW WITH INSECT SCREEN





PASSIVE TM 102 FIXED WINDOW



FEATURES:


- PHIUS certified
- Superior thermal performance
 - Suitable for passive buildings and net-zero energy applications
- and het-zero energy application
 - Supports up to 4-pane glazing
- configurations
- Advanced acoustic insulation
- Ideal for extensive structural designs
- Broad glazing surfaces for enhanced natural light



TECHNICAL PARAMETERS:

- Water Tightness: **15 psf**
- Designed Pressure: CW 75 psf
- Thermal Insulation: From 0.08 Btu/hft²F
- Acoustic Insulation: STC up to 48 dB
- Maximum Panel Weight: 660 lbs (300 kg)
- Maximum Panel Height: 10 ft (3m)
- Maximum Panel Width: 5 ft (1,5m)
- Glazing: Double and triple






WINDOWS

PERFORMANCE TM 77



THE PERFORMANCE TM 77 WINDOW SYSTEM EPITOMIZES SECURITY AND INNOVATION IN MODERN CONSTRUCTION. IT EXCELS IN THERMAL INSULATION, SOUNDPROOFING, AND WEATHER RESISTANCE. WITH SPECIALIZED SEPARATORS IN ITS ALUMINUM PROFILES, THIS SYSTEM STANDS OUT AS A DURABLE, HIGH-PERFORMING CHOICE FOR CONTEMPORARY ARCHITECTURE.









PERFORMANCE TM 77 TILT&TURN WINDOW WITH INSECT SCREEN

3¾ [86.4mm]
[mu6:72] %Z

PERFORMANCE TM 77 BALCONY TILT&TURN WINDOW




FEATURES:

- Passive Certified
- Suitable for passive buildings and net-zero energy applications
- Highest performance and tightness
 - Suitable for producing windows, doors,
- and display windows with enhanced security features
- Outward-opening option available
- Hidden panel option
- Broad glazing surfaces for enhanced natural light



TECHNICAL PARAMETERS:

- Water Tightness: **15 psf**
- Designed Pressure: CW 75 psf
- Thermal Insulation: From 0.12 Btu/hft²F
- Acoustic Insulation: STC up to 48 dB
- Maximum Panel Weight: 660 lbs (300 kg)
- Maximum Panel Height: 10 ft (3m)
- Maximum Panel Width: 5 ft (1,5m)
- Glazing: **Double and triple**



WINDOWS


ECO TM 62




ENGINEERED WITH A BUDGET APPROACH IN MIND, IT'S AN IDEAL SOLUTION FOR REDUCING HEAT AND ENHANCING COMFORT IN BOTH RESIDENTIAL AND COMMERCIAL SPACES, BLENDING FUNCTIONALITY WITH AESTHETIC APPEAL.



ECO TM 62 TILT&TURN WINDOW WITH INSECT SCREEN





ECO TM 62 FIXED WINDOW



FEATURES:

- Cost-efficient for light commercial applications
- Option for casement
- Minimal sightlines for enhanced visibility
- Concealed panel option





- Water Tightness: **15 psf**
- Designed Pressure: **CW 75 psf**
- Thermal Insulation: From 0.17 Btu/hft²F
- Acoustic Insulation: STC up to 46 dB
- Maximum Panel Weight: 660 lbs (300 kg)
- Maximum Panel Height: 10 ft (3m)
- Maximum Panel Width: 5 ft (1,5m)
- Glazing: Double and triple




DOORS

DISCOVER THE ARTISTRY OF OUR DOOR COLLECTION, WHERE INNOVATIVE DESIGN MEETS PRACTICAL ELEGANCE. EACH DOOR IN OUR RANGE IS A TESTAMENT TO MODERN ARCHITECTURE, BLENDING FUNCTIONALITY WITH STYLE. THEY ARE MORE THAN JUST ENTRANCES — THEY ARE STATEMENTS OF SOPHISTICATION AND SUSTAINABILITY, ENHANCING ANY SPACE WITH THEIR PRESENCE.










DOORS


MOREVIEW




ADVANCED DESIGN INTEGRATION
AND PRACTICAL ELEGANCE, TAILORED
FOR MODERN ARCHITECTURE.
EACH DOOR IS A FUSION OF FUNCTIONAL
EXCELLENCE AND STYLISTIC INNOVATION,
SERVING NOT ONLY AS AN ENTRANCE
BUT AS A SOPHISTICATED, SUSTAINABLE
ENHANCEMENT TO ANY SPACE.



MOREVIEW INWARD OPENED DOOR



MOREVIEW OUTWARD OPENED DOORS





FEATURES:

- Suitable for commercial applications
- Design as a replacement for steel doors
- Contemporary look
- Configurable window designs with mullion options


Adaptive designs for windows

- and balcony doors, supporting multiple threshold types
- Visible width minimized to 2.1 inches (56mm)
- LockBox with notched glass




TECHNICAL PARAMETERS:

- Water Tightness: 9 psf
- Designed Pressure: **LC 50 psf**
- Thermal Insulation: From 0.20 Btu/hft²F
- Acoustic Insulation: STC up to 42 dB
- Maximum Panel Weight: 300 lbs (150 kg)
- Maximum Panel Height: 10 ft (3m)
- Maximum Panel Width: 5 ft (1.5m)
- Glazing: **Double and triple**



DOORS


PASSIVE TM 102




THESE DOORS ARE A TESTAMENT
TO ENERGY-EFFICIENT DESIGN AND
ARCHITECTURAL HARMONY. REPRESENTING
THE IDEAL UNION OF CONTEMPORARY
AESTHETICS AND ECO-CONSCIOUSNESS,
EACH ENTRANCE BECOMES AN UPSCALE
LIVING EXPERIENCE.



PASSIVE TM 102 INWARD OPENED DOOR





PASSIVE TM 102 OUTWARD OPENED DOOR WITH TRESHOLD



FEATURES:


- Outstanding thermal insulation
- Option for 4 glass panes
- Available in single and double door designs
- Supports tall constructions using innovative techniques
- Integrated with side and top lights




TECHNICAL PARAMETERS:

- Water Tightness: 9 psf
- Designed Pressure: **CW 60 psf**
- Thermal Insulation: From 0.12 Btu/hft²F
- Acoustic Insulation: STC up to 45 dB
- Maximum Panel Weight: **550 lbs (250 kg)**
- Maximum Panel Height: 10 ft (3m)
- Maximum Panel Width: 4,5 ft (1,4m)
- Glazing: **Triple**

DOORS




PERFORMANCE TM 77 PRESTIGE




EXPERIENCE THE FUSION OF LUXURY AND TECHNOLOGY WITH PERFORMANCE PRESTIGE DOORS. MORE THAN JUST ENTRYWAYS, THESE DOORS REPRESENT A MARK OF REFINED TASTE AND ADVANCED INNOVATION. TAILORED FOR DISCERNING HOMEOWNERS, THEY COMBINE CUSTOMIZED DESIGN WITH SMART FUNCTIONALITY, TURNING EVERY ENTRANCE INTO AN EXTRAORDINARY MOMENT.





PERFORMANCE TM 77 PRESTIGE OUTWARD OPENED DOOR WITH TRESHOLD





FEATURES:

- Integrated with side and top lights
 - Customizable panel design
- with stainless steel appliqués and decorative mullions
- Wide selection of paints and finishes
- Versatile options for bespoke entrance doors
- Adhered glass option
- ADA compliant
- Automated opening functionality
- Superior water, air, thermal, and fire resistance
- Seamless integration with Yawal USA systems
- Dedicated hardware solutions
- Enhanced access control features



- Water Tightness: 9 psf
- Designed Pressure: **CW 60 psf**
- Thermal Insulation: From 0.12 Btu/hft²F
- Acoustic Insulation: STC up to 33 dB
- Maximum Panel Height: 10 ft (3m)
- Maximum Panel Width: 4,5 ft (1,4m)




DOORS

PERFORMANCE TM 77




STEP INTO THE WORLD OF PERFORMANCE
TM 77 WHERE GLASS EXUDES GRANDEUR.
THESE DOORS BLEND SLEEK DESIGN WITH
CUTTING-EDGE TECHNOLOGY, TRANSFORMING
SPACES INTO SANCTUARIES OF LIGHT AND
OPULENCE. PERFECT FOR THOSE DESIRING
TO MERGE INDOOR AND OUTDOOR SPACES,
PERFORMANCE TM 77 DOORS OFFER
MESMERIZING PANORAMIC VIEWS.









PERFORMANCE TM 77 OUTWARD OPENED DOOR WITH TRESHOLD




- Advanced thermal insulation
- Suitable for heavy commercial use
- Oversized dimensions
- Integrated with side and top lights
- Enhanced access control features
- Compatible
- with the "intelligent house" concept




TECHNICAL PARAMETERS:

- Water Tightness: 9 psf
- Thermal Insulation: From 0.15 Btu/hft2F
- Designed Pressure: CW 60 psf
- Acoustic Insulation: STC up to 44 dB
- Maximum Panel Weight: 550 lbs (250 kg)
- Maximum Panel Height: 10 ft (3m)
- Maximum Panel Width: 4,5 ft (1,4m)
- Glazing: Double and triple



DOORS


ECO TM 62




DISCOVER THE ECO TM 62 DOORS,
WHERE BEAUTY MEETS EFFICIENCY.
THESE PREMIUM DOORS EMBODY FINE
CRAFTSMANSHIP AND ECO-AWARENESS.



ECO TM 62 INWARD OPENED DOOR







ECO TM 62 INWARD OPENED DOOR WITH TRESHOLD



FEATURES:

- Ideal for commercial applications
- Fully integrated with storefront profiles
- Efficient installation process
- Advanced thermal insulation
- Integrated with side and top lights
- Enhanced access control features and panic devices




TECHNICAL PARAMETERS:

- Water Tightness: 9 psf
- Thermal Insulation: From 0.20 Btu/hft2F
- Acoustic Insulation: STC up to 42 dB
- Maximum Panel Weight: 550 lbs (250 kg)
- Maximum Panel Height: 10 ft (3m)
- Maximum Panel Width: 4,5 ft (1,4m)
- Glass Thickness: double and triple glazed
- Glazing: Double and triple


DOORS

INTERIOR PBI 50



CRAFTED FOR ELEGANT INTERIOR
SOLUTIONS, THE INTERIOR SYSTEM
EXCELS IN CREATING
NON-THERMALLY INSULATED
PARTITIONS AND STRUCTURES.







FEATURES:

- Suitable for light walls and high-performance internal partitions
- Allows creation of all-glass structures
- Option for crosspieces dividing the glazing
- Various contour profiles available, with walls settable at any angle
- Options for outward and inward opening doors, all-glass, single-panel, double-panel doors, and service windows
- Capability to manufacture smoke-proof constructions
- Simple installation process




TECHNICAL PARAMETERS:

- Acoustic Insulation: STC up to 48 dB
- Maximum Fix Partition Size: 10,1 ft (3100m)
- Maximum Single Panel Height: 3,9 ft (1,2m)
- Maximum Single Panel Width: **7,8 ft (2,4m)**
- Maximum Double Panel Height: **7,1 ft (2,2m)**
- Maximum Double Panel Width: 7,8 ft (2,4m)






OUR CURTAIN WALLS EMBODY THE PINNACLE OF MODERN ARCHITECTURAL DESIGN, FUSING GROUNDBREAKING ENGINEERING WITH VISUAL SPLENDOR. THESE FACADE SYSTEMS TRANSFORM SKYLINES AND ENHANCE LIVING SPACES, OFFERING A BACKDROP FOR ARCHITECTURAL CREATIVITY AND SUSTAINABLE, FUNCTIONAL DESIGN.











FA 50N DESIGN LINE



THE DESIGN LINE CURTAIN WALL SYSTEM STANDS AS A MARVEL OF ARCHITECTURAL INNOVATION, SEAMLESSLY COMBINING SLEEK AESTHETICS WITH SUPERIOR THERMAL, ACOUSTIC, AND ENVIRONMENTAL PERFORMANCE. IDEAL FOR COMMERCIAL AND UPSCALE RESIDENTIAL BUILDINGS, IT TURNS ANY FACADE INTO A VISUALLY CAPTIVATING MASTERPIECE.








- Supports diverse structures including turns, bends, and polygons
- Various cover cap options for different curtain wall aesthetics
- Superior thermal performance
- Optimal tightness with aesthetic excellence
- Efficient installation process



- Water Tightness: **15 psf**
- Designed Pressure: **CW 75 psf**
- Thermal Insulation: From 0.11 Btu/hft²F
- Acoustic Insulation: STC up to 53 dB
- Glazing: **Double and triple**






FA 50N SMOOTH LINE



THIS CURTAIN WALL SYSTEM INTEGRATES
QUICK ASSEMBLY WITH THE BEAUTY OF A
STRUCTURAL FACADE, STRIKING A PERFECT
BALANCE BETWEEN FORM AND FUNCTION.








- Unified large glass appearance for a semi-structural glazing look
- No size limitations
- Superior thermal performance
- Supports diverse structures, including turns, bends, and polygons
- Optimal tightness with aesthetic excellence
- Efficient installation process



- Water Tightness: **15 psf**
- Designed Pressure: CW 75 psf
- Thermal Insulation: From 0.14 Btu/hft²F
- Acoustic Insulation: STC up to 50 dB
- Glazing: **Double and triple**




PANORAMIC CW WINDOW



THIS MODERN SOLUTION BLENDS
CURTAIN WALL ELEGANCE WITH WINDOW
PRACTICALITY, FEATURING AN ,INVISIBLE'
FRAME FROM THE OUTSIDE FOR A SLEEK,
CONTINUOUS FACADE.








FEATURES:

- Options: Hopper, top-hung, casement, parallel windows
- Superior thermal performance
- Oversized dimensions
- Uniform surface visual, enhancing building aesthetics
- Efficient ventilation with sliding windows for facade uniformity
- Supports automated opening/closing actuators installation




TECHNICAL PARAMETERS:

- Water Tightness: 15 psf
- Designed Pressure: CW 65 psf
- Thermal Insulation: 0.15 Btu/hft²F
- Acoustic Insulation: STC up to 44 dB
- Maximum Panel Weight: 660 lbs (300 kg)
- Maximum Panel Height: 10 ft (3M)
- Maximum Panel Width: 6 ft (1,8M)
- Glazing: **Double and triple**




DESIGNED TO SEAMLESSLY INTEGRATE WITH ANY SETTING, THESE ADD-ONS ELEVATE THE OVERALL AESTHETIC WHILE ENSURING PRACTICALITY AND COMFORT.











SUNSHADES AND LOUVERS




OUR SUNSHADES AND LOUVERS
ARE DESIGNED FOR MAXIMUM SUN
CONTROL.





SUNSHADES



























FEATURES:

- PTAC louvers integrated with Yawal systems
- Multiple air conditioning flow options
- Options for automatic and motorized control
- Fixed and operable louver choices
- Vertical and horizontal sun protection
- Enhances unique brand appearance
- Improves indoor comfort by reflecting and diffusing light
- Increased work and life comfort with reduced sun exposure



TECHNICAL PARAMETERS:

- Designed Pressure: CW 50 psf
- Maximum Panel Height: 10 ft
- Maximum Panel Width: 6 ft




JULIET BALCONY



DESIGNED WITH STRONG, DURABLE ALUMINUM,
THESE BALCONIES PROVIDE SAFETY AND
AN ELEGANT ARCHITECTURAL ELEMENT, ADDING
A SENSE OF OPENNESS AND SOPHISTICATION.






JULIET BALCONY
WITH TILT&TURN WINDOW



JULIET BALCONY MULLION CONNECTION TO WINDOW





FEATURES:

- Modern external balustrades
- for high-opening windows and French balconies
- Robust profiles for optimal safety
- Compatible with all Yawal windows and doors
- Design option without upper safety strip
- Suitable for single-panel and double-panel configurations
- Enhances building acoustic insulation
- Adaptable for integration at any construction stage




FOR SINGLE PANEL:


- Maximum Panel Height: 4 ft (1,2M)
- Maximum Panel Width: 4 ft (1,2m)

FOR DOUBLE PANEL:

- Maximum Panel Height: 4 ft (m)
- Maximum Panel Width: 8 ft (m)



VERTILINE



TRANSFORM YOUR PROPERTY'S

APPEARANCE WITH OUR VERTILINE

ALUMINUM FAÇADE CLADDING.

ALIGNING WITH CONTEMPORARY

DESIGN TRENDS, THOSE SLATS OFFERS


A PERFECT COMBINATION OF STYLE AND


PRACTICALITY, WITH AN OPTION WITH LED


LIGHTING TO A COLOR OF YOUR CHOICE.




VERTILINE SECTION











- Adaptable for external and internal assembly, offering system flexibility
- Customizable shapes and colors to match architectural aesthetics
- Ensures facade uniformity for a contemporary look
- Durable, weather-resistant aluminum slats
- Maintenance-free, no repainting required
- Safe and eco-friendly,
 compliant with construction
 and environmental standards


ADDITIONAL ELEMENT:

VERTILINE PROFILE CORSS SECTIONS


- BASE PROFILE Z SHAPED
- SHORT SLAT H SHAPED
- WIDE SLAT FACE LED
- HIGH SLAT SIDE LED




- Maximum Panel Height: **Unlimited**
- Maximum Panel Width: Unlimited




INSECT SCREEN





WE OFFER A VARIETY OF FIX, RETRACTABLE AND ACCORDEON INSECTS SCREENS, WITH CONVENIENT OPTIONS OF COMBINING WITH SUNSHADES.



PERFORMANCE TM 77 WINDOW WITH INSECT SCREEN









FEATURES:


TECHNICAL PARAMETERS:

- Maintains full window functionality
- Robust design for long-lasting performance
- Available in various colors
- Option for integrated construction
- Environmentally friendly and harmless to insects

MAX PANEL HEIGHT MAX PANEL WIDTH

Fix: ■ 10ft (3m) ■ 5ft (1,5m) ■ 6.5ft (2m) Retractable: 8.2ft (2,5m) 20ft (6m) Accordeon: ■ 10ft (3m) 30ft (9,1m) Centor: 10ft (3m) ■ 10ft (3m) 20ft (6m) Sunscreen:






GLASS RAILINGS



IDEAL FOR BALCONIES AND TERRACES, OUR GLASS RAILINGS ARE DESIGNED FOR SAFETY AND AESTHETICS, REFLECTING CURRENT ARCHITECTURAL TRENDS WITH EXTENSIVE GLAZING.








- Simplified assembly process
- Clean, streamlined aesthetics
- Capability to position balustrade at a 90° angle
- Hassle-free installation and upkeep



- Maximum Panel Height: 3.6ft (1.1 m)
- Maximum Panel Width: Unlimited






LED PROFILE



BRIGHTEN YOUR ENVIRONMENT WITH OUR
LED PROFILES. COMBINING AESTHETIC APPEAL
WITH TECHNICAL EFFICIENCY, THESE PROFILES
ENHANCE THE LOOK AND FEEL OF YOUR DOORS
AND WINDOWS, ADDING A TOUCH OF ELEGANCE.









PERFORMANCE TM 77 DOOR WITH LED OUTSIDE




- Compatible to window, door, sliding system and curtain walls.
- Unlimited design flexibility in crafting entrance doors using the panel door system.
- Efficient and straightforward installation process.
- Clean design lines ensured by adhesive corner connections.





ECLIPSE 33




OFFERING A STYLISH AND PRACTICAL
ALTERNATIVE TO TRADITIONAL WOODEN
OPTIONS, ECLIPSE 33 SHUTTERS-AVAILABLE
IN PANEL AND FIXED LOUVRE VERSIONS
-ELEGANTLY PROTECT RESIDENTIAL
INTERIORS FROM EXCESSIVE SUNLIGHT WHILE
ENHANCING BUILDING FACADES.





ECLIPSE 33 FLAP PANEL




ECLIPSE 33 PANEL SHUTTER












ECLIPSE 33 SECTION



ECLIPSE 33 FIX LAMELLAR







FEATURES:


- Italian style window shutters
- Oversized dimensions
- Maintenance free
- Unlimited color option
- Complete blackout effect



TECHNICAL PARAMETERS:

- Maximum Panel Height: 7ft
- Maximum Panel Width: 7ft







LINEAR DRAINAGE



LINEAR DRAINAGE SYSTEMS, INSTALLED LEVEL WITH THE FLOOR, EFFICIENTLY MANAGE WATER EXPULSION SOLUTION.









FEATURES:

- Incorporates floor-level guttering for effective condensate drainage
- Frame-integrated for enhanced stability and durability
 - Compatible with Yawal systems:
- Moreview, Pano Lift'N'Slide, Prestige, Pano, Passive
- Facilitates customizable gutter shaping
- Inclined wall design ensures gravitational condensate outflow
- Features an aesthetically pleasing perforated INOX metal sheet



CONTACT US

HERE IS WHERE YOU CAN START THE CONVERSATION FOR MORE INFORMATION:

YAWAL USA

11 West Hudson Ave. Englewood, NJ 07631

+1 (551) 250 3614

office@yawalusa.com estimates@yawalusa.com support@yawalusa.com



Visit our website
WWW.YAWALUSA.COM

