



HELIOS[®] AS-1X3TSPLIT DIGITAL OPTICAL AUDIO SPLITTER



SALES 386-255-0234

PRODUCT OVERVIEW

This digital optical audio splitter allows the user to connect and distribute one digital optical output to three digital optical inputs without degradation. Ideal for connecting your TOSLINK audio source device to up to three device inputs, for use in home theaters, control rooms, production studios, A/V presentations, and meeting rooms.

- Splits one input signal to three SPDIF/TosLink output signals
- Supports LPCM2.0/DTS/Dolby-AC3 audio
- Supports signal retiming
- Uses fiber optic cable
- Over-voltage protection
- Plug-and-play ready

SPECIFICATIONS:

Supported Digital Audio Formats.....	LPCM 2.0/DTX/Dolby-AC3
Maximum Output Cable Distance.....	40 Meters
Power Supply Input.....	AC, 50Hz/60Hz, 100V - 240V
Power Supply Out.....	DC, 5V, 500 Ma
Maximum Current Draw.....	100 Ma
Operating Temperature Range.....	0 to 40 (C), 32 to 104 (f)
Dimension (L x W x H).....	54 x 54 x 23.5 (mm), 2.2 x 2.2 x .9 (in)
Weight.....	35 (grams), 1.24 (oz)

