

VEBSCONPRO



www.vebsconpro.com

VebsConPro

offers modern cement -based tile adhesives suitable for concrete, plastered, and tile- on- tile applications on interior and exterior walls. Our stone and tile adhesives are highly preferred for installing ceramic tiles, vitrified tiles, marble, granite, and mosaic tiles, among others, in small, medium, and large sizes. VebsConPro offers three types of tile adhesives for floor and wall tiling applications.

TECHNICAL DETAILS

Bulk Density	1600-1800 kg/m3
Pot Life & Open Time	20 min & 60 min
Water Requirement	20-25% (by weight)
Slip Resistance	≤ 0.5 mm
Shear Adhesion Strength (28 D)	1.1 1.25 1.5 1.5 N/mm ²
Tensile Adhesion Strength (28 D)	0.8 1.0 1.2 1.5 N/mm ²
Foot Traffic	24 Hours

*The above technical data is based on laboratory tests under standard conditions. Actual measured data at the site may vary due to circumstances beyond our control.

FEATURES & BENEFITS

- ❖ High Coverage
- ❖ Easy-to-Spread
- ❖ Excellent Bonding
- ❖ High Tensile Strength
- ❖ High Slip Resistance
- ❖ Good Shear Adhesion
- ❖ Non-Shrinkage Cracks

SUITABLE SURFACES

- ❖ AAC Blocks
- ❖ CLC Blocks
- ❖ Fly Ash Bricks
- ❖ Concrete Bricks
- ❖ Cellular Concrete Blocks
- ❖ Concrete Hollow Blocks
- ❖ RCC Column & Surface



VEBS Rebel 1001: C1 (TYPE 1) STONE & TILE ADHESIVE

For ceramic, (non-vitrified) marble, and granite for small tile on walls and floors



VEBS Marvel 1002: C1TE (TYPE 2) STONE & TILE ADHESIVE

For ceramic, (non-vitrified) marble, and granite for small-to-medium-sized tile on walls and floors



VEBS Vintage 1003: C2TE (TYPE 3) STONE & TILE ADHESIVE

Suitable for vitrified tiles, marble, granite, and mosaic (tile-on-tile) applications, particularly for medium-sized tiles on walls and floors



VEBS Ornamento 1003 FLEXA: C2TE FLEXA (TYPE 3 FLEXA) STONE & TILE ADHESIVE

For vitrified tiles, marble, granite, and mosaic (tile-on-tile) for larger size tiles on walls and floors

DIRECTIONS FOR USE

- Clean Surface:** Remove dirt, dust or loose particles.
- Add Water:** Pour the recommended amount of water into a container.
- Add Powder:** Add adhesive powder to the water and stir until well combined.
- Rest Mix:** Allow mixture to sit for 4-5 minutes.
- Mix Properly:** Thoroughly mix until a smooth consistency.
- Spread Adhesive:** Apply adhesive in equal layers on the surface.
- Create Grooves:** Use a notched trowel to create grooves.
- Back Butter:** Apply a thin layer of adhesive to the tile back.
- Place Tiles:** Position tiles onto the adhesive-coated surface.
- Press Firmly:** Press tiles into place for a strong bond.
- Remove Excess:** Wipe away any excess adhesive from joints.
- Cure Time:** Allow 24 hours for the surface to dry.

DO'S: Always prepare a fresh mixture as needed | Work from the base of the surface upwards | Use a notched trowel with smooth, even motions for a better finish | Use potable water for mixing. Apply only to cementitious substrates cured for 28 days | Maintain a consistent mixture proportion and consistency throughout the application.

DON'TS: Never use in a damp area | Never add excess water | Never add extra sand or cement | Don't exceed maximum layer thickness.

SAFETY & HEALTH

Use Safety Glasses, Safety Shoes, Face Mask, and Gloves. In the event of eye contact, rinse the affected area with clean water. Wash your hands before eating food. Keep out of reach of children.

Legal Notes: The information and advice provided by VebsConPro LLP are based on our current understanding of industry practices, knowledge, and experience. Any liability for damages resulting from the use of this information or the products it refers to is strictly limited by our standard safety and delivery conditions. Users are strongly advised to conduct a trial application to confirm the product's suitability before using it on a full scale. VebsConPro LLP bears no responsibility for any consequential damage arising from the improper application of these products.



VEBS Pacific Gel 1004 STONE & TILE ADHESIVE EN: C2TE S1 | IS: TYPE 4 | GEL TECHNOLOGY

Conquer Large Format Tiles with Ease! VEBS Pacific Gel 1004 (Type 4) is a revolutionary gel adhesive for large, heavy tiles. It is a flexible, non-slip formula that ensures superior bond strength. Perfect for reliable, long-lasting installations.

Quick Guide: Mix powder with 20-25% water. | Spread on the surface (max 2m²). | Maintain a joint width of 2 mm (indoor) / 5 mm (outdoor). | Grout after 24 hrs (walls) / 48 hrs (floors).

Packaging: 20 kg BOPP Bag | **Shelf Life:** 6 months from Mfg. Date **Coverage:** Approx. 50 Sq. Ft OR 4.65 m² (3 mm bed)

Ideal For: Tiles: Large-format, ceramic, porcelain, and natural stone. | **Areas:** Walls & floors (residential/commercial), kitchens, bathrooms, swimming pools, terraces, facades. | **Substrates:** Concrete, cement, plaster.

Key Features: Superior Strength & Flexibility | Enhanced Gel Workability | Reduced Tile Slippage | Water & Weather Resistant | Excellent Coverage & Bonding | Non-shrinkage cracks

VEBS KOSMOS 1005 TILE & STONE ADHESIVE

EN: C2TE S2 | PTGEL ULTRA | IS: TYPE 5
Unmatched Strength. Unwavering Hold.

VEBS KOSMOS 1005 is a premium, high-strength, non-sag cementitious tile adhesive. Designed for superior bonding of all tile types, it's ideal for challenging interior and exterior substrates, including metals.

Key Features: High Strength & Chemical Resistance | Two-component, easy mix & use | Bonds to diverse substrates, including metals | Water, freezing, and thermal shock resistant | Flexible & heat resistant.

Packaging: 20 kg BOPP Bag | **Substrates:** Concrete, masonry, plaster, metal, wood, cement backer boards, existing tiles, epoxy/PU resin surfaces, rubber, PVC.

Ideal For: Tiles of all types, including glass mosaics, engineered stone, and metal. | **Areas:** All interior & exterior floor and wall installations.

Quick Guide: Combine Part B with Part A using a low-speed mixer. | Apply with notched trowel; back-butter large tiles. | Set tiles into wet adhesive (within 10 mins). | Grout after 24 hours (21°C).



VEBSCONPRO 2-COMPONENT PU TILE ADHESIVE (TYPE 5)

EN: C2TE S2 | PTGEL ULTRA | IS: TYPE 5
Unmatched Strength. Unwavering Hold. For Specialized Applications.

Vebs 2-Component PU Tile Adhesive is a premium, high-performance, polyurethane-based adhesive engineered for the most demanding tile and stone installations. This robust, non-sag formula delivers unparalleled bond strength and exceptional flexibility, making it the ultimate choice for challenging interior and exterior substrates where maximum performance is critical.

**Vebs Single-Component PU Tile Adhesive (Type 5):
Coming Soon...!**

VEBS READY MIX PLASTER



Vebs Ready Mix Plaster is a modern dry mix plaster produced with high-quality raw materials, including graded sand, 53-grade OPC cement, and polymer additives. It offers excellent protection against external dampness, UV rays, rain, humidity, fire, and sound.

This plaster is designed for easy application with minimal wastage, providing higher coverage and an excellent, crack-free surface finish due to the addition of glass fibres. It's suitable for various substrates, such as AAC blocks, concrete blocks, and fly ash bricks, and can be used on both internal and external surfaces, including ceilings.

Also Available in Self-Curing Variety


VEBS BLOCK JOINTING MORTAR



Vebs AAC Block Jointing Mortar is a high-quality product formulated with German polymer, graded sand, cement, and selective additives. It allows you to replace conventional 10-12 mm-thick mortars with a mere 2-2mm thickness, significantly increasing construction speed while saving time, energy, and money.

This mortar provides excellent bonding, withstands robust structural loads, sets rapidly, and offers an **excellent pull-off adhesion strength of 0.55 to 0.8 N/mm²**. It provides higher coverage, high flexibility, and superior strength. It is perfect for various block types, including AAC, CLC, fly ash, concrete, and cellular concrete blocks.

VEBS TILE SPACERS



Achieve precise tile spacing and perfectly aligned installations with VEBS Tile Spacers. Our high-quality spacers ensure uniform grout lines, enhancing the overall aesthetic appeal of your tiling project.

VEBS NOTCHED TROWELS



Lay the Foundation for Perfect Tile Installations and ensure precise tile spacing and optimal adhesive coverage with VEBS Notched Trowels. Our range of trowels, designed for various tile sizes and applications, always guarantees professional results.



Contact Us Today for Dealership & Project Enquiries:

Kolhapur Head Office: VebsConPro LLP

Shop No. 1, Vasant Chhaya Apartments, 586, Shahupuri 1st Lane,
Kolhapur, Maharashtra – 416101

Pune Branch : VebsConPro LLP

Flat No. 103, Vasant Utsav Society Road, Hinjewadi, Pimpri-Chinchwad, Pune, Maharashtra - 411057.

+91 99229 94453

www.vebsconpro.com

enquiry@vebsconpro.com