

10000 LB EXTRA TALL/WIDE 2-POST LIFT

Manufacturer: Atlas Automotive Equipment Part #: ATEATTD-OHX10000X-FPD

Features and Benefits:

10,000 lb. Capacity

Commercial Grade

- Extra Tall & Extra Wide
- Overall height: 152? (12? 8?)
- · Symmetric arms
- Automatic Arm Restraints
- Padded Shut-Off Bar
- · Rubber Covers on Carriages
- Single Point Lock Release
- Dual Direct-Drive Cylinders
- Powder Coat Finish
- Free 12 Piece Truck Adapter Set
- Mounting Hardware Included
- Shipping Weight: 1,665 lbs
- 5 yr Structural � 2 yr Hydraulic Warranty � Parts Only
- This part number FREIGHT PREPAID





The Atlas OHX10000X two post commercial grade above ground lift is the perfect choice for those large commercial repair facilities or the Mr. Homeowner who demands the highest quality at the absolute best price. The Atlas OHX10X is a TRUE 10,000 lb. capacity two post lift that offers a great value to the customer. The Atlas OHX10000X was engineered and manufactured to lift vehicles ranging from Smart Cars to a one ton diesel dually. Extra lifting height and extra width between the columns allows the operator to work on all sizes of vehicles and offers a fudge factor of about 6 inches when of driving through to another part of the building or lifting the van or ladder truck . If you are over 6? 2?, the Atlas OHX10X has longer cylinders which allow the vehicle to be of lifted about 3 inches higher than many other lifts.

The Atlas OHX10X incorporates a single piece 12? 7? formed column and an extra long carriage that provides maximum column and arm strength to lift and support a 10,000 lb. vehicle. The single piece columns require the customer to have a ceiling of at least 13 feet to stand the column.

Atlas ATTD-OHX10000X Specifications

- Capacity 10,000 LB.
- Overall Height 152" (12♦ 8♦)
- Overall Floor Width 144 3/8" (12 3/8")
- Outside Column to Outside Column 136" (11� 4")
- Maximum Lift Height (Without Adapters) 74 3/4"
- Maximum Lift Height (With Adapters) 85 3/4"
- Minimum Arm Height 4 1/2"
- Inside Column 118 1/4 (9 10 1/4 4)
- Drive Thru 106 7/8 (8 10 7/8)
- Column Size 9 1/8" x 11"
- · Column Thickness of Steel 5mm
- Base Of Lift 18 1/2" x 21 1/2"
- Motor/Electrical Requirement 220 volt single (1) phase (A 30 amp breaker is recommended)
- Oil Requirement 3-5 Gallons AW32/AW46 (NOT INCLUDED)
- Shipping Weight 1,665 LBS.
- Adapter Heights 4 Each 2�, 3�, 6�
- Arm Hole/Adapter Peg Size 1.5�
- Requires a minimum of 4" of concrete with a 3000 psi. rating