


10000 LB HEAVY DUTY 2-POST LIFT (WILL CALL)

Manufacturer: Atlas Automotive Equipment Part #: ATEATTD-PV10PX

Features and Benefits:

- 10,000 lb. capacity
- · Commercial Grade
- Adjustable Height 11' 11 1/8" or 12'3"
- · Asymmetric/Symmetric Arms
- · Automatic Arm Restraints
- · "Padded" Shut-Off Bar
- Padded Carriages
- · Single Point Lock Release
- · Dual Direct-Drive Cylinders
- · Powder Coat Finish
- Free 12 Piece Truck Adapter Set
- Mounting Hardware Included
- Shipping Weight: 1,905 lbs.
- 5 yr Structural 2 yr Hydraulic Warranty Parts Only
- This part number WILL CALL ONLY



manufacturing the PV series two post above ground lifts for over a decade. Thousands sold! Descriptions such as "bulletproof", built like a brick outhouse, tougher than nails, and other such euphemistic phrases are used every day to describe any of the Atlas® PV series models. Whether you are an automotive shop or working on personal vehicles from your home, the PV10PX is the industry standard!

The commercial grade Atlas® PV10PX two post lift includes some modifications and improvements that make it one of the most popular above ground lifts in the world

This lift is the perfect choice for use in either a large commercial service department or for the "pole barn" owner who wants the "biggest and baddest" lift in the country. The Atlas® PV10PX is designed and engineered to safely lift (and work on) everything from a Smart Car® to a one ton diesel dually. This lift incorporates a padded shut-off bar to protect the top of the vehicle from contacting the crossbar. The carriages are equipped with rubber protective covers (size may vary) to help prevent the vehicle's doors from damage if opened into the columns or carriages. The PV10PX also includes a deluxe truck adapter set (12 pieces vs. the standard 8 pieces) and the rubber lift pad that has been reinforced to ensure a solid contact with the vehicle's lifting points.

Atlas® ATTD-PV10PX Specifications

- Capacity 10,000 LB
- Overall Height 143 1/8" (11' 11 1/8") or 146 7/8" (12' 2 7/8")
- Overall Floor Width 137 1/2" (11' 5 1/2")
- Outside Column to Outside Column 125" (10' 5")
- Maximum Lift Height (Without Adapters) 71 7/8"
- Maximum Lift Height (With Adapters) 82 7/8"
- Minimum Arm Height 4 3/8"
- Inside Column 110 3/8" (9' 2 3/8")
- Drive Thru 96" (8')
- Column Size 7 1/2" x 14 1/2"
- Column Thickness of Steel 6mm
- Base Of Lift 17 1/2" x 20 1/2"
- Motor/Electrical Requirement 220 volt single (1) phase (A 30 amp breaker is recommended)
- Oil Requirement 3-5 Gallons AW32/AW46 (NOT INCLUDED)
- Shipping Weight 1,905 LBS.
- Adapter Heights 4 Each 2", 3", 6"
- Arm Hole/Adapter Peg Size 1.5"
- Requires a minimum of 4" of concrete with a 3000 psi. rating

