

## 15000 LB COMMERCIAL 2-POST LIFT

Manufacturer: Atlas Automotive Equipment

Part #: ATEATTD-PV15PX-FPD

### Features and Benefits:

**\$8,599.00**

- 15,000 lb capacity
- Extra Tall & Extra Wide
- Commercial Grade
- Adjustable height 165? (13? 9?) or 177? (14? 9?)
- Special low height 152? (12? 8?) (REQUIRES PURCHASE OF EXTRA CABLES)
- Symmetric arms
- Automatic Arm Restraints
- Padded Shut-Off Bar
- Door Guards on Carriages
- Single Point Lock Release
- Dual Direct-Drive Cylinders
- Powder Coat Finish
- Free 12 Piece Truck Adapter Set
- Mounting Hardware Included
- Shipping weight: 2,490 lbs.
- 5 yr Structural 2 yr Hydraulic Warranty Parts Only
- This part number FREIGHT PREPAID



The Atlas PV series represents the absolute best value for the customer who demands a heavy duty professional grade two post lift at the lowest possible price. Atlas has been manufacturing the PV series two post above ground lifts for over a decade. Thousands sold! Descriptions such as bulletproof, built like a brick outhouse, tougher than nails, and other such euphemistic phrases are used every day to describe any of the Atlas PV series models.

The Atlas PV15PX is a commercial grade lift designed to accommodate everything from standard cars to heavy duty service trucks. The distance between the symmetrical columns is almost 123? with a drive through space of over 108?. The extra distance between the symmetrical columns will allow the widest of vehicles or vehicles with wide rearview mirrors to be lifted or driven through. The increased length of the symmetrical arms coupled with the additional height of the included peg style truck adapter set allows the operator to safely raise long wheel base trucks with a variety of running boards. The extra height means extra clearance allowing you to lift vans and box trucks without worry.

The Atlas ATTD-PV15PX features three height settings, the lowest setting of 152 inches or 12 foot 8 inches **REQUIRES THE PURCHASE OF EXTRA CABLES.**

### Atlas ATTD-PV15PX Specifications

- Capacity 15,000 LB.
- Overall Height 165" (13? 9?) or 177" (14? 9?)
- Special Low Height 152" (12? 8?) (Requires Purchase of Extra Cables)
- Overall Floor Width 151 3/8" (12? 7 3/8?)
- Outside Column to Outside Column 139 1/8" (11? 7 1/8")
- Maximum Lift Height (Without Adapters) 75 1/8"
- Maximum Lift Height (With Adapters) 86 1/8"
- Minimum Arm Height 7 1/4"
- Inside Column 123 1/2" (10? 3 1/2?)
- Drive Thru 109 7/8" (9? 1 7/8?)
- Column Size 7 1/2" x 14 1/2"
- Column Thickness of Steel 6mm
- Base Of Lift 17 1/2" x 20 1/2"
- Motor/Electrical Requirement 220 volt single (1) phase (A 30 amp breaker is recommended)
- Oil Requirement 3-5 Gallons AW32/AW46 (NOT INCLUDED)
- Shipping Weight 2,490 LBS.
- Adapter Heights 4 Each 2?, 3?, 6?
- Arm Hole/Adapter Peg Size 1.5?
- Requires a minimum of 6" of concrete with a 3000 psi. rating