

PLATINUM 10000 LB CERTIFIED 2-POST LIFT

Manufacturer: Atlas Automotive Equipment

Part #: ATEAP-PVL10-FPD

Features and Benefits:

\$5,995.00

- ALI Certified Lift
- 10,000 lb. Capacity
- Column design with special Double S bends increasing column strength
- Can be installed Symmetrically OR Asymmetrically
- Overall Height: 135 7/8" (11' 3 7/8") or 139 7/8" (11' 7 7/8") (Cylinder Height 12' 4")
- Padded Carriages
- 3-Stage Front Arms & 2-Stage Rear Arms
- Single-Point Lock Release
- Powder Coat Finish
- Includes Double Screw-up Adapters
- Free 8 Piece Truck Adapter Set
- Mounting Hardware Included
- Standard with Premium ALLY Power unit
- Shipping Weight: 1,850 lbs.
- 5 yr Structural ♦ 2 yr Hydraulic ♦ 2 yr Powerunit Warranty
- This part number Freight Prepaid



The Atlas ♦ Platinum PVL10 is a 2-post 10,000 lb. capacity ALI Certified commercial grade lift designed with the professional shop in mind. The Platinum PVL10 was engineered and built to offer a commercial grade above ground lift to those customers who have ♦ fallen in love ♦ with the reliability offered by the Double S column design and symmetric columns. Tens of thousands of above ground lifts incorporating the Double S column design have been sold worldwide over the past two decades. The Double S column design was so revolutionary, that it was protected by a patent. That patent has now expired.

The Atlas ♦ Platinum PVL10 can be installed with the columns positioned symmetrically or asymmetrically. When the columns are installed in an asymmetric configuration exiting and entering the vehicle is easier and reduces the chance of getting dings or scratches in the door. When the columns are installed in a symmetric configuration the width between the columns is wider, allowing wider trucks and SUVs to use the lifts with ease. Both column configurations offer easy vehicle access and superior vehicle lift point support due to the three stage front arm design.

The Atlas ♦ Platinum PVL10 features three (3) stage telescoping front arms, double screw rubber/metal adapters with truck height extensions, protective rubber pads mounted to the carriage, rubber column guards, and a price that cannot be matched.

This product also features an ALLY Hydraulic AL2850 Power Unit. This premium power unit is certified by MET Laboratories Inc. for electrical compliance in the United States and Canada. Extra heavy-duty armatures and more motor windings with increased silver metal included in the wires and connections create far less heat generation and allow ALLY Hydraulic power units to maintain constant torque through the lifting process. This power unit also carries an industry leading two-year limited warranty.

Atlas ♦ Platinum PVL10 Specifications

- Capacity 10,000 LB.
- Overall Height 135 7/8" (11 ♦ 3 7/8 ♦) or 139 7/8" (11 ♦ 7 7/8 ♦) (CYLINDER EXTENDS TO 12 ♦ 4 ♦)
- Overall Floor Width 139" (11 ♦ 7 ♦) Asymmetric/137 1/2" (11 ♦ 5 1/2 ♦) Symmetric
- Outside Column to Outside Column 130" (10 ♦ 10") Asymmetric/129 1/4" (10 ♦ 9 1/4") Symmetric
- Maximum Lift Height (Without Adapters) 72 1/2"
- Maximum Lift Height (With Adapters) 81 1/2"
- Minimum Arm Height 4"
- Inside Column 107 3/4" (8 ♦ 11 3/4 ♦) Asymmetric/ 112 1/2" (9 ♦ 4 1/2") Symmetric
- Drive Thru 91" Asymmetric/99 1/2" Symmetric
- Column Size 7" x 10 1/4"
- Column Thickness of Steel 6mm
- Base Of Lift 15" x 18"
- Motor/Electrical Requirement 220 volt single (1) phase (A 30 amp breaker is recommended)
- Oil Requirement 3-5 Gallons AW32/AW46 (NOT INCLUDED)
- Shipping Weight 1,850 LBS.
- Adapter Heights 4 Each 3 ♦, 6 ♦
- Arm Hole/Adapter Peg Size 2 ♦
- Requires a minimum of 4" of concrete with a 3000 psi. rating