



DOTTO TM DRUM SPEC

Brake Shoe Size	Drum PN	Brake face Diameter	Brake face Width	Overall Depth	Hub Pilot	Bolt Hole Circle	Bolt Holes No.	Bolt Holes Dia./in	Type	Weight /lbs	Remark
16.5 x 7	DRM-TM002	16.5	7.56	10.56	8.78	11.25	10	1	U	102	BAL



Production Facilities

Casting

- ▶ Hydraulic molding line
- ▶ Cupola + holding furnace
- ▶ Induction furnace
- ▶ Automatic pouring



Production Facilities

Machining

- ▶ CNC lathes
- ▶ VMCs
- ▶ Robots



FEATURES & BENEFITS:

- 1) Exceeds FMVSS-121 Minimum brake retardation ratio at all test air pressures.
- 2) Provides safe power stops with lower brake application pressures.
- 3) Exceeds federal thermal fade properties requirements.
- 4) Exceeds SAE J2686 durability requirements.

Cross Reference for other drum P/Ns available

DOTTO	PACCAR	WEBB	GUNITE	Reyco
DRM-TM002	TF1657BXN	56864B	3922X	60000-018
DRM-TM003	TF1657BN	66864B	3600AX	53033-018
DRM-TM004	TF3710X	65654B	3710X	54238-018
DRM-TM005	TF3721X	61527B	3721X	53075-018
DRM-TM006	TF3721AX	61528B	3721AX	54201-108
DRM-TM007	TF3800X	65548B	3800X	54293-018
DRM-TM008	TF3807A	66854F	3807A	54229-01

DOTTO AUTO TECH CANADA INC.

Address: Office 113, Suite 200, 135 Innovation Drive, Winnipeg, R3T 6A8, Manitoba, Canada

Email: info@dotto-tech.com

Tel: [204-698-1682](tel:204-698-1682)