



DOTTO-SRJG STEEL WHEELS

DOTTO PART#	Size	Nut hole	Nut dia. (mm)	Pilot type	PCD (mm)	Center bore (mm)	Offset (mm)	Load Capacity	Hand hole	Weight(lbs)	Qty/40HQ	Gross Wt (lbs)
DT9228226	22.5x8.25	10	Φ26	HUB	Φ285.75	Φ220	168	7400lbs	5	67.00	576	39725.00
DT8228219	22.5x8.25	10	Φ32	STUD	Φ285.75	Φ222	168	7400lbs	5	67.00	576	39725.00
DT9228228	22.5x8.25	10	Φ26	HUB	Φ285.75	Φ220	168	7400lbs	2	69.00	576	41949.00
DT8228218	22.5x8.25	10	Φ32	STUD	Φ285.75	Φ222	168	7400lbs	2	69.00	576	41949.00
DT3248229	24.5x8.25	10	Φ26	HUB	Φ285.75	Φ220	169	7400lbs	2	84.00	480	42966.00
DT8248219	24.5x8.25	10	Φ32	STUD	Φ285.75	Φ222	169	7400lbs	2	84.00	480	42966.00
DT4228205	22.5x8.25	Demountable Rims					121	7400lbs	no	68.00	580	43277.00

Remarks:

1. Valve stems included.

DOTTO-SRPL Forged Aluminum Wheel											
DOTTO Part#	Size	Hand Hole	Bolt	Bolt Dia	Pilot Type	P.C.D	Center Bore	Offset	Load Capacity	Weight	Qty/40"HC
DTA228227	22.5x8.25	10 round	10	26mm	Hub pilot	285.75mm	220mm	168.5mm	8000lbs	46.5lbs	532
DTA248221	24.5x8.25	10 round	10	26mm	Hub pilot	285.75mm	220mm	169mm	8000lbs	55lbs	486

Remarks:

1. Valve stems included.
2. Standard Polish both sides, Extra Polish, available.

DOTTO AUTO TECH CANADA INC.

Address: Office 113, Suite 200, 135 Innovation Drive, Winnipeg, R3T 6A8, Manitoba, Canada

Email: info@dotto-tech.com

Tel: [204-698-1682](tel:204-698-1682)