





INTRODUCTION

Broken Hill Operations Pty Ltd (BHOP) [a wholly owned subsidiary of CBH Resources Limited (CBH)] owns and operates the Rasp Mine (the Mine), which is located centrally within the City of Broken Hill on Consolidated Mine Lease 7 (CML7).

Mining has been undertaken within CML7 since 1885. The existing operations at the Rasp Mine include underground mining operations, a processing plant producing zinc and lead concentrates and a rail siding for concentrate dispatch. These operations are undertaken in accordance with Project Approval 07_0018 granted 31 January 2011, under Part3A of the Environmental Planning and Assessment Act 1979 (EP&A Act).

As the holder of an Environmental Protection Licence, 12559, BHOP is required, under Section 66(6) of the NSW *Protection of the Environment Operations Act 1997,* to publish pollution monitoring data. In addition BHOP is required to publish data in accordance with its Project Approval 07_0018 Schedule 4 Condition 9. These documents can be found on the Rasp Mine web site.

TABLE OF CONTENTS

1	AIR	R QUALITY	3
		•	
	1.1	HIGH VOLUME AIR SAMPLERS	
	1.2	TAPERED ELEMENT OSCILLATING MICROBALANCE SAMPLING (TEOM)	
	1.3	DUST DEPOSITION SAMPLING	
	1.4	VENTILATION OUTLETS AND BAG HOUSE MONITORING	14
2	NO	DISE	15
	2.1	BLASTING (VIBRATION AND OVERPRESSURE)	
	2.2	Noise	
3	WA	ATER	16
	3.1	Groundwater	
	3.2	Surface Water Sample Record	17
4	WE	EATHER DATA	19
5	DA	ATA LOG	22
6	co	ORRECTION LOG	22



1 Air Quality

The following pollutants as listed in the Project Approval (DA 07_0018 MOD10 December 2022) are required to be monitored in EPL 12559:

Long Term Criteria for Particulate Matter

Pollutant	Averaging Period	Criterion
Total solid particles (TSP)	Annual	90 μg/m³
Particulate matter < 10 µm (PM ₁₀)	Annual	25 μg/m³

Short Term Criterion for Particulate Matter

Pollutant	Averaging Period	Criterion
Particulate matter < 10 μm (PM ₁₀)	24 hour	50 μg/m³

Long Term Criteria for Deposited Dust

Pollutant	ollutant Averaging Period		Maximum Total Deposited Dust Level	
Deposited dust	Annual	2 g/m ² /month	4 g/m ² /month	

1.1 High Volume Air Samplers


There are four high volume air samplers used to measure ambient air quality at the Rasp Mine – HVAS (EPL10) and HVAS1 (EPL11) are located at the Silver Tank, central and to the south of the mine lease, and HVAS2 (EPL12) and HVAS3 (EPL57) are located adjacent to and north of Blackwood Pit. A map indicating these locations can be found on the Rasp Mine web site. HVAS and HVAS3 sample for total suspended particulates (TSP) and lead dust, and HVAS1 and HVAS2 sample for particulate matter less than 10 microns (PM₁₀) and lead dust.

HVAS (EPL10) - Silver Tank (On Site) Results for June 2023

DATE	TSP (μg/m³)	Lead (μg/m³)
03-June-23	23.4	0.07
09-June-23	29.5	0.12
15-June-23	42.9	0.13
21-June-23	36.9	0.14
27-June-23	15.2	0.08


HVAS (EPL10) is located on the southern boundary of Rasp Mine and while limit criteria do not apply at this point, they do apply at the closest residential location.





TSP dust results at HVAS for the month of June were consistent with previous months. The highest TSP result for June was 42.9 μ g/m³ on 15 June when winds were predominantly from the NW, suggesting dust has been generated by MOD6 works in Little Kintore Pit. Water carts apply water to site roads daily and dust suppressant is applied to free areas and unsealed roads. The annual rolling average for TSP at this location is 36.92 μ g/m³ at the end of June, above the average at the beginning of July 2022 which was 36.05 μ g/m³.

The annual rolling average for TSP is determined using data with extreme dust events included.




TSP Lead dust results at HVAS for the month of June were higher than results seen in previous months. The highest TSP Lead level for June was 0.14 $\mu g/m^3$ on 21 June when winds were predominately from the NE, suggesting contribution from off-site. Water carts apply water to site roads daily and dust suppressant is applied to free areas and unsealed roads. The rolling annual average for TSP Lead in June 2023 was 0.17 $\mu g/m^3$, lower than the rolling annual average of 0.18 $\mu g/m^3$ for TSP Lead in July 2022.



HVAS1 (EPL11) - Silver Tank (On Site) Results for June 2023


DATE	PM ₁₀ (μg/m³)	PM ₁₀ Lead (µg/m³)
03-June-23	6.0	0.01
09-June-23	9.0	0.03
15-June-23	6.9	0.01
21-June-23	3.7	0.02
27-June-23	2.7	0.01

HVAS1 (EPL11) is located on the southern boundary of Rasp Mine and while limit criteria do not apply at this point, they do apply at the closest residential location.



 PM_{10} dust results at HVAS1 for month of June were consistent with previous months. The highest PM_{10} dust level for June was 9.0 μ g/m³ on 9 June when winds were predominantly from the NW, suggesting dust has originated from MOD6 works in Little Kintore Pit. Water carts apply water to site roads daily and dust suppressant is applied to free areas and unsealed roads. The annual rolling average for PM_{10} dust at this location is 10.35 μ g/m³ at the end of June 2023, lower than the annual rolling average at the beginning of July 2022 which was 10.00 μ g/m³. External and extreme dust events are recorded in measurements.





 PM_{10} Lead dust results at HVAS1 in the month of June were consistent with previous months. The highest Lead PM_{10} result for June was 0.03 μ g/m³ on 9 June when winds were predominantly from the NW. It is likely that the dust measured on this day originated from MOD6 works in Little Kintore Pit. Water carts apply water to site roads daily and dust suppressant is applied to free areas and unsealed roads. The rolling annual average for PM_{10} Lead in June was 0.04 μ g/m³, consistent with the rolling annual average of 0.04 μ g/m³ in July 2022.

HVAS 2 (EPL12) - Blackwood Pit (On Site) Results for June 2023


DATE	PM ₁₀ (μg/m³)	PM ₁₀ Lead (μg/m³)
03-June-23	6.7	0.06
09-June-23	7.3	0.04
15-June-23	7.2	0.01
21-June-23	2.6	<0.007
27-June-23	2.8	0.02

HVAS2 (EPL12) is located on the northern boundary of Rasp Mine and while limit criteria do not apply at this point, they do apply at the closest residential location.


In June PM_{10} levels at HVAS2 were consistent with previous months. The highest recorded PM_{10} dust reading for June was 7.3 $\mu g/m^3$ on the 9 June when winds were from the NW suggesting contribution from off-site. The annual rolling average for PM_{10} dust at this location is 15.27 $\mu g/m^3$ at the end of June 2023, up from 11.11 $\mu g/m^3$ in July 2022. A TSF spray system is to be installed in 2023 and will improve dust control on the TSF surface.

The annual rolling average for PM₁₀ dust is determined using data with extreme dust events included.





 PM_{10} lead levels in June were consistent with previous months. The highest recorded PM_{10} Lead dust reading for June was 0.06 $\mu g/m^3$ on the 3 June when winds were from the NE suggesting some contribution of Lead dust from Blackwoods TSF2. A TSF spray system is to be installed in 2023 and will improve dust control on the TSF surface. The rolling annual average for PM_{10} Lead in June 2023 was 0.08 $\mu g/m^3$, down from 0.09 $\mu g/m^3$ in July 2022.



HVAS 3 (EPL57) - Blackwood Pit (On Site) Results for June 2023


DATE	TSP (μg/m³)	Lead (μg/m³)
03-June-23	17.4	0.15
09-June-23	13.6	0.16
15-June-23	13.7	0.30
21-June-23	6.6	0.02
27-June-23	9.6	0.09




HVAS3 (EPL57) was included in EPL 12559 on 14 March 2019 to provide for monitoring of TSP Dust on the northern boundary of the site at Blackwoods Pit TSF2.

TSP levels at HVAS3 were highest on 3 June with a result of 17.4 $\mu g/m^3$, when winds were from the NE, suggesting Blackwoods TSF2 was the likely source of the dust. A TSF spray system is to be installed in 2023 and will improve dust control on the TSF surface. The annual rolling average for TSP dust at this location is 48.36 $\mu g/m^3$ at the end of June 2023, $\mu g/m^3$ in July 2022.

The annual rolling average for TSP is determined using data with extreme dust events included.



TSP Lead levels in June were lower than previous months, with the highest result of $0.30~\mu g/m^3$ recorded on 15 June when winds were predominantly from the SSW suggesting contribution from Backwoods TSF2. The rolling annual average for TSP Lead in June was $0.31~\mu g/m^3$, down from $0.36~\mu g/m^3$ in July 2022. A TSF spray system is to be installed in 2023 and will improve dust control on the TSF surface.





1.2 Tapered Element Oscillating Microbalance Sampling (TEOM)

There are two Tapered Element Oscillating Microbalance (TEOM) sampling units used to measure ambient air quality at the Rasp Mine – TEOM1 (EPL13) is located off-site within the perimeter fence of Essential Water south of the mine lease, and TEOM2 (EPL14) is located on-site adjacent to Blackwood Pit to the north of the mine lease. A map indicating these locations can be found on the Rasp Mine web site. TEOM1 and TEOM2 are designed to operate continuously and sample for particulate matter less than 10 microns (PM₁₀) in size.

TEOM2 was temporarily decommissioned in 19 June 2019 due to Embankment 2 TSF2 construction works. The decommissioning is in accordance with dust management strategies agreed with the EPA which includes the operation of a real-time PM10 monitor north of the construction works. Both Project Approval and Environment Protection Licence criteria exclude dust storms and other extraordinary events.

Project Approval 07_0018 criteria apply at TEOM1 and TEOM2, with two criteria listed for PM10, a 24 hour average criteria of 50 ug/m³ and an annual average criteria of 25 ug/m³.

TEOM data is validated by third party consultants using Australian Standards and internal procedures, and is used to populate the table of TEOM monthly data provided below.



TEOM1 (EPL13) (Off Site) and TEOM2 (EPL14) (On Site) Validated Results for June 2023

Date	TEOM 1 (μg/m³)	Compliant with 50µg/m³ 24hr average?	TEOM 2 (μg/m³)	Compliant with 50µg/m³ 24hr average?
1-Jun-23	7.3	Υ	4.7	Υ
2-Jun-23	8.9	Υ	5.4	Υ
3-Jun-23	10.3	Υ	9.9	Υ
4-Jun-23	12.8	Υ	11.3	Υ
5-Jun-23	8.0	Υ	8.0	Υ
6-Jun-23	9.7	Υ	5.6	Υ
7-Jun-23	8.5	Υ	6.9	Υ
8-Jun-23	5.0	Υ	1.0	Υ
9-Jun-23	11.0	Υ	8.4	Υ
10-Jun-23	10.2	Υ	9.7	Υ
11-Jun-23	9.8	Υ	5.8	Υ
12-Jun-23	5.4	Υ	2.0	Υ
13-Jun-23	9.5	Υ	8.3	Υ
14-Jun-23	10.6	Υ	8.0	Υ
15-Jun-23	9.9	Υ	8.5	Υ
16-Jun-23	9.1	Υ	4.8	Υ
17-Jun-23	8.4	Υ	5.0	Υ
18-Jun-23	7.7	Υ	5.5	Υ
19-Jun-23	9.4	Υ	7.2	Υ
20-Jun-23	8.7	Υ	5.8	Υ
21-Jun-23	12.0	Υ	1.9	Υ
22-Jun-23	5.3	Υ	3.2	Υ
23-Jun-23	5.2	Υ	3.5	Υ
24-Jun-23	5.9	Υ	2.6	Υ
25-Jun-23	7.5	Υ	7.0	Υ
26-Jun-23	7.6	Υ	7.5	Υ
27-Jun-23	7.7	Υ	3.9	Υ
28-Jun-23	4.8	Υ	2.1	Υ
29-Jun-23	6.9	Υ	4.4	Υ
30-Jun-23	7.5	Υ	5.3	Υ


 PM_{10} dust levels at both TEOM units were low in the month of June, with neither site recording a daily average over the limit of 50 μ g/m³.


The rolling annual average for PM10 at TEOM1 with external dust events removed for the period July 2022 to June 2023 is 7.63 $\mu g/m^3$, down from 12.83 $\mu g/m^3$ at the beginning of the reporting period.

The rolling annual average for PM10 at TEOM2 with external dust events removed for the period July 2022 to June 2023 is $6.91 \, \mu g/m^3$, below the rolling annual average of $13.22 \, \mu g/m^3$ at the beginning of the reporting period.



The PM₁₀ 24-hour rolling annual average for both TEOM sites remain below the annual average criteria of 25 ug/m^3 .








1.3 Dust Deposition Sampling

There are seven dust deposition gauges to measure ambient air quality at the Rasp Mine – D1 to D7. D1 and D6 are located off-site, D1 near the St Johns training facility north of the Rasp Mine and D6 in Casuarina Avenue south of the Rasp Mine. D2 to D5 and D7 are located on the mine lease in various locations. A map indicating these locations can be found on the Rasp Mine web site. Dust samples are collected monthly and analysed for total deposited dust and deposited lead dust.

Dust Deposition Gauges D1 (EPL3) to D7 (EPL9) – Results for June 2023

Total Deposited Dust (g/m²/Month)							
Sample Period	D1 (off site)	D2 (off site)	D3 (on site)	D4 (off site)	D5 (on site)	D6 (off site)	D7 (on site)
June 2023	0.5	1.2	0.6	0.9	1.5	0.5	0.3
Annual Rolling Average	0.81	0.97	2.53	2.88	2.13	2.00	1.13
Background (2010)	-1	3.1	4.3	5.7	-1	5.8	-1

Note: "1" = background not available, N/A = not applicable as dust deposition unit is located on site, NS = No sample



The dust levels recorded in Dust Gauges in June 2023 were consistent with previous months. The highest dust levels were recorded in the D5 Silver Tank gauge. The predominant wind direction for June was from the NW as shown in the Wind Rose in Section 4. Contribution of dust on this date was likely from MOD6 works in Little Kintore Pit.


Dust Deposition Gauges that are located off-site must adhere to criteria for annually averaged deposited dust of 4 $g/m^2/m$ onth. All off-site Dust Deposition Gauges were compliant in the reporting period.



Total Deposited Lead (g	/m ^{2/} Month)						
Sample Period	D1 (off Site)	D2 (on site)	D3 (on site)	D4 (on site)	D5 (on site)	D6 (off Site)	D7 (on site)
June 2023	0.0004	<0.0001	0.0015	0.0012	0.0007	<0.0001	0.0006
Background (2010)	0.0034	0.005	0.005	0.006	-1	0.004	-1

Note: "1"= background not available, NS = No sample

There are no guidelines for deposited lead dust. Lead results in June 2023 were highest in the D3 Thompson Shaft gauge. The prominent wind direction for the month of June was from the NW, suggesting contribution from activity in the railyard. Dust suppressant is applied to unsealed areas of the site and roads are frequently watered using water carts in an attempt to control dust emissions. The waste dump adjacent to the rail loadout is treated with dust suppressant to capture any loose dust accumulating on the lower batters and on the upper surface.





1.4 Ventilation Outlets and Bag House Monitoring

There are two locations to measure pollutants from exhausts or stacks; these include the Primary Ventilation Shaft, measuring pollutants from underground firings, and the Baghouse Stack at the crusher measuring dust. Each are located on site; the Primary Ventilation Shaft is located centrally and to the north of the mine lease and the Primary Crusher Baghouse Stack is located within the area of the processing plant to the east of the lease. Shaft 6 (EPL56) was removed as a monitoring location with the variation of EPL12559 in March 2019 as it became an intake rather than an exhaust in April 2018. A map indicating these locations can be found on the Rasp Mine web site. Samples are collected quarterly and analysed for a number parameters listed in below. Reference to the item required in the Rasp Mine Environment Protection Licence (EPL) is provided below. Emissions monitoring is conducted quarterly.

The following criteria apply:

Primary Ventilation Shaft (EPL1)

	Unit	Criteria
Nitrogen Oxides	mg/m³	350
Volatile Organic Compounds	mg/m ³	40

Primary Ventilation Shaft (EPL1) and Crusher Baghouse (EPL2)

	Unit	Criteria
Total Suspended particles (TSP)	mg/m ³	20
Type 1 and Type 2 ¹	mg/m³	1

Note 1: "Type 1 substance" means the elements antimony, arsenic, cadmium, lead or mercury or any compound containing one or more of those elements.

"Type 2 substance" means the elements beryllium, chromium, cobalt, manganese, nickel, selenium, tin or vanadium or any compound containing one or more of those elements.

Primary Vent Shaft (EPL1) and Crusher Baghouse (EPL2) Results for June 2023

Monitoring was conducted at the Primary Vent Shaft (EPL1) and the Crusher Baghouse (EPL2) on 30 May 2023. The monitoring results for the Primary Vent Shaft and the Crusher Baghouse from this monitoring event were below the licence criteria.

Parameter	Unit	Primary Vent Shaft	Crusher Baghouse
Farameter	Oint	(EPL1)	(EPL2)
Nitrogen Oxides	mg/m³	0.647	NA
Volatile Organic Compounds	mg/m³	0.451	NA
Total Solid particles	mg/m³	3.76	6.41
Type 1 and Type 2 substances	mg/m³	0.104	0.122



2 Noise

2.1 Blasting (Vibration and Overpressure)

There are five compliance vibration monitors at various locations measuring for vibration and overpressure from blast firings. These include V1 to V5 which are located on-site and off-site. A map indicating these locations can be found on the Rasp Mine web site. In addition, there are a number of roving monitors which may be used to monitor vibration and overpressure at particular locations as required. Monitors operate continuously and are automatically triggered to record when a blast occurs. The following conditions apply as listed in the PA 07 0018 and EPL 12559:

Blasting Criteria (Western Mineralisation and Main Lodes excluding Block 7)

Location	Airblast Overpressure (dB(Lin Peak))	Ground Vibration (mm/s)	Allowable Exceedance (for production and development blasts)
Residence on privately			5% of the total number
owned land	115	5	of blasts over a 12-month
(7am-7pm)			period ¹
(7am-7pm)	120	10	0%
(7pm-10pm)	105	-	-
(10pm-7am)	95	-	-
Public Infrastructure	-	100	0%

Note 1: Does not apply until completion of Pollution Reduction Program on the EPL at the end of 2018. Applies to EPL criteria in the period for the Annual Return 3 Nov to 2 Nov the following year and to DPE criteria in the reporting period 1 Jul to 30 Jun each year.

Blasting Criteria (Block 7)

Location	Airblast Overpressure (dB(Lin Peak)	Ground Vibration (mm/s)	Allowable Exceedance (for production and development blasts)
Residence on privately owned land (7am-7pm)	115	3 (interim)	5% of the total number of blasts over a 12-month period ¹
(7am-7pm)	120	10	0%
(7pm-10pm)	105	-	-
(10pm-7am)	95	-	-
Broken Hill Bowling Club, Italio (Bocce) Club, Heritage Items within CML7	-	50	0%
Perilya Southern Operations	-	100	0%
Public Infrastructure	-	100	0%

Note 1: Applies to EPL criteria in the period for the Annual Return 3 Nov to 2 Nov the following year and to DPE criteria in the reporting period 1 Jul to 30 Jun each year.

In addition the following conditions also apply:

- Production blasts may occur between 6.45 am and 7.15 pm on any day
- 1 production blast per day, with 6 per week averaged over a calendar year
- 6 development blasts per day, with 42 per week averaged over a calendar year



Blasting Data Summary Results for June 2023 (annual period)

Total Blasts:

- 0 production blasts occurred before 6.45 am or after 7.15 pm
- The number of Production blasts averaged 1.98 per week over the previous calendar year
- The number of Development blasts averaged 23.04 per week over the previous calendar year

Western Mineralisation and Main Lodes (excluding Block 7):

- 0 Blast recorded >5 mm/s
- 0 Blasts recorded >10 mm/s
- 0 development blasts recorded an over pressure level over 95 dBL (10pm to 7am)
- 0 development blasts recorded an over pressure level over 105 dBL (7pm to 10pm)
- 0 Blasts recorded an over pressure level over 115dBL (7am to 7pm)
- 0 Blasts recorded an over pressure level over or 120 dBL at any time
- Percentage of development blasts over 5 mm/sec for the annual period = 0%
- Percentage of production blasts over 5 mm/sec for the annual period = 0%

Block 7:

- 1 Blasts recorded >3 mm/s
- 0 Blasts recorded >10 mm/s
- 0 Blasts recorded >50 mm/s at V6
- 0 development blasts recorded an over pressure level over 95 dBL (10pm to 7am)
- 0 development blasts recorded an over pressure level over 105 dBL (7pm to 10pm)
- 0 Blasts recorded an over pressure level over 115 dBL (7am to 7pm)
- 0 Blasts recorded an over pressure level over or 120 dBL at any time
- Percentage of development blasts over 3mm/sec for the annual period = 0%
- Percentage of production blasts over 3mm/sec for the annual period =100%

The have been no production blasts in the Western Mineralisation and Main Lodes producing vibration at monitors over 5 mm/sec for the 12-month period.

There has been one production blasts in Block 7 for the 12-month period and this blast produced vibration at one monitor of over 3 mm/sec.

2.2 Noise

Noise monitoring is undertaken as per the NSW Noise Policy for Industry at a frequency of once per annum. Annual noise monitoring was conducted during two consecutive night-time periods from 27 to 29 October 2022.

The monitoring assessment found that site LAeq, 15min noise contributions satisfied the relevant limits during the measurements at all assessment locations.

3 Water

3.1 Groundwater

There are eighteen sampling locations for groundwater. GW01 (EPL37) to GW16 (EPL52) are piezometers installed at various locations around the mine site and are sampled quarterly. There are also two sampling locations for water pumped from underground mining, Shaft 7 (EPL53) and Kintore Pit (EPL54), which are sampled monthly. A map indicating these locations can be found on the Rasp Mine web site. Groundwater monitoring is scheduled for



completion in March, June, September and December. No limits are applied in the EPL to the results from groundwater monitoring. GW10 has recorded elevated levels of Cadmium, Manganese and Zinc at times over the last year which may indicate seepage from Horwood Dam, although samples from Horwood Dam have not shown the same patterns. Elevated levels for these metals have not been replicated in nearby bores GW08 and GW09. Additional sampling will be conducted in GW10 if metals levels remain elevated.

Groundwater Monitoring Requirements

EPA Identification Number	Frequency	Parameters to be analysed
Shaft 7 EPL53	Monthly	alkalinity (calcium carbonate (CaCO ₃)), cadmium (Cd), calcium (Ca), — chloride (Cl), electrical conductivity (EC), iron (Fe), lead Pb),
Kintore Pit (U/G dewatering) EPL54	Monthly	magnesium (Mg), manganese (Mn), pH, sodium (Na), sulphate
Piezometers EPL37 (GW01) to EPL52 (GW16)	Quarterly	(SO4), total dissolved solids (TDS) and zinc (Zn)

Shaft 7 (EPL53) and Kintore Pit (EPL54) Results for June 2023

Sample Point	рН	EC (μS/cm²)	TDS (mg/l)	Alkalinity (CaCO ₃) (mg/l)	SO4 (mg/l)	CI (mg/I)	Ca (mg/I)	Mg (mg/l)	Na (mg/l)	Cd (mg/l)	Pb (mg/l)	Mn (mg/l)	Zn (mg/l)	Fe (mg/l)
Shaft 7 (EPL53)	5.84	14200	14000	5	5770	1890	500	382	1760	0.373	2.34	45.6	101	<0.05
Kintore Pit (EPL54)							Not pun	nping						

Groundwater Bores (EPL37 - EPL52) Results for June 2023

Sample Point	рН	EC (μS/cm²)	TDS (mg/l)	Alkalinity (CaCO ₃) (mg/l)	SO4 (mg/l)	CI (mg/I)	Ca (mg/l)	Mg (mg/l)	Na (mg/l)	Cd (mg/I)	Pb (mg/l)	Mn (mg/l)	Zn (mg/l)	Fe (mg/l)
GW01 (EPL37)	4.59	9800	9430	2	4950	941	294	446	1500	0.201	0.050	276	225	0.17
GW02 (EPL38)							Bore D	ry						
GW03 (EPL39)	5.53	14700	13100	<1	4970	2920	594	399	2380	0.552	3.62	434	362	0.50
GW04 (EPL40)	6.62	14700	11500	242	4790	2520	599	582	2480	0.0350	0.005	32.4	16.3	0.24
GW05 (EPL41	5.82	13400	11600	35	4770	2450	566	430	2220	2.91	0.511	231	252	0.30
GW06 (EPL42)	5.89	14100	12400	48	5030	2600	576	508	2380	0.988	0.069	283	185	0.33
GW07 (EPL43)	5.95	12500	11300	30	4930	1820	556	355	1930	2.44	1.28	294	370	<0.05
GW08 (EPL44)	5.93	12600	11500	4	4580	2250	574	351	1780	2.68	0.604	279	498	<0.05
GW09 (EPL45)	6.42	11000	9630	70	4490	1550	612	508	1520	0.948	0.001	88.4	130	<0.05
GW10 (EPL46)	6.15	16700	14600	84	5080	3430	664	615	2780	4.06	0.003	154	318	<0.05
GW11 (EPL47)	6.11	3150	2630	26	1450	290	326	78	350	1.15	0.576	9.04	53.2	<0.05



Sample Point	рН	EC (μS/cm²)	TDS (mg/l)	Alkalinity (CaCO ₃) (mg/l)	SO4 (mg/l)	CI (mg/I)	Ca (mg/l)	Mg (mg/l)	Na (mg/l)	Cd (mg/l)	Pb (mg/l)	Mn (mg/l)	Zn (mg/l)	Fe (mg/l)
GW12 (EPL48)						In	sufficient	sample						
GW13 (EPL49)							Bore D	ry						
GW14 (EPL50)							Bore D	ry						
GW15 (EPL51)							Bore D	ry						
GW16 (EPL52)							Bore D	ry						

3.2 Surface Water Sample Record

There are seven sampling locations for surface water, these include surface water basins located on the mine lease to capture and retain rainfall and two locations up and down stream of an ephemeral creek located south of the mine lease boundary. A map indicating these locations can be found on the Rasp Mine web site. Based on historical data, sampling is most likely to be undertaken in October (highest rainfall month as recorded by Bureau of Meteorology) and April.

Results for all locations were consistent with previous samples.

Surface Water Monitoring Requirements

Description	Frequency	Parameters to be Analysed
Federation Way Culvert EPL29/S31-1	2 x per year, six months apart	
Ryan Street Dam EPL31/S49	2 x per year, six months apart	cadmium (Cd), chloride (Cl), electrical
Adjacent Olive Grove EPL32/S1A	2 x per year, six months apart	conductivity (EC), lead Pb), manganese
Adjacent Bowls Club EPL33 /S9-B2	2 x per year, six months apart	(Mn), pH, sodium (Na), sulphate (SO4), total dissolved solids (TDS) and zinc (Zn)
Horwood Dam EPL34/S34	2 x per year, six months apart	
Upstream Bonanza St EPL35	2 x per year, six months apart	
Downstream Sydney Rd EPL36	2 x per year, six months apart	

Surface Water Monitoring Results for 5 June 2023

Sample Point	рН	EC (μS/c m²)	TDS (mg/l)	Alkalinit y (CaCO ₃) (mg/l)	SO4 (mg/l)	CI (mg/I)	Ca (mg/I)	Mg (mg/l)	Na (mg /I)	Cd (mg/l)	Pb (mg/l)	Mn (mg/l)	Zn (mg/l)	Fe (mg/I)
S9B-2 (EPL 33)	7.34	377	251	9	138	23	32	6	23	0.125	0.355	2.96	11.6	<0.05
S31-1 (EPL 29)	6.79	491	386	10	249	5	31	2	6	0.721	1.74	12.2	82.6	<0.05
S1A	7.47	243	166	8	85	8	27	2	10	0.0686	0.180	1.87	8.46	<0.05



Sample Point	рН	EC (μS/c m²)	TDS (mg/l)	Alkalinit y (CaCO ₃) (mg/l)	SO4 (mg/l)	CI (mg/I)	Ca (mg/I)	Mg (mg/l)	Na (mg /I)	Cd (mg/l)	Pb (mg/l)	Mn (mg/l)	Zn (mg/l)	Fe (mg/l)
(EPL 32)														
Upstream (EPL 35)	7.73	116	37	26	12	10	10	2	7	0.0043	0.048	0.181	0.765	<0.05
Downstream (EPL 36)						Ir	nsufficient	sample						
S49 (EPL 31)	7.18	411	294	8	191	27	36	3	6	0.225	0.176	11.2	28.0	<0.05
S44 (EPL 30)						lr	nsufficient	sample						
Horwood Dam (EPL 34)	6.83	13700	11800	13	5100	2200	475	385	1900	2.46	1.70	302	515	<0.05

4 Weather Data


The weather station continuously monitors the following parameters as per Point 55 of the Environmental Protection Licence.

The following parameters are required to be recorded each month as listed in the EPL 12559:

Rasp Mine Weather Station (EPL55) Monitoring Requirements

Parameter	Sampling method	Units of measure	Averaging period	Frequency
Temperature at 10 metres	AM-4	degrees Celsius	15 minutes	Continuous
Wind Direction at 10 metres	AM-4	degrees in a clockwise direction from True North	15 minutes	Continuous
Wind Speed at 10 metres	AM-4	metres per second	15 minutes	Continuous
Rainfall	AM-4	millimetres	1 hour	Continuous
Sigma theta	AM-2 & AM-4	degrees	15 minutes	Continuous





The wind rose provided above indicates that the prominent wind direction for the month of June was from the NW.



Weather Data Summary for June 2023

Date	Temperature @ 10m (°C)		Wind Speed @ 10m (km/hr)		Predominant Wind Direction @ 10m		Rainfall (mm)
	Min	Max	Min	Max	Cardinal	Degree	Total
01-Jun-2023	14.8	22.5	6.604	8.526	S	161.24	0.00
02-Jun-2023	15.1	22.3	10.254	13.545	ENE	64.10	0.00
03-Jun-2023	14.9	26	8.804	11.577	ESE	97.77	1.4
04-Jun-2023	14.1	22.9	12.064	16.099	ENE	64.50	13.1
05-Jun-2023	11.9	18.3	10.083	13.177	SSW	197.05	0.4
06-Jun-2023	13.1	21.3	12.514	16.591	ESE	92.83	4.1
07-Jun-2023	9.5	19.6	20.653	28.853	SW	220.68	2.9
08-Jun-2023	9.8	14.8	12.105	17.242	WNW	276.37	0.00
09-Jun-2023	9.8	15.3	6.32	7.906	sw	208.56	0.00
10-Jun-2023	9.7	16.2	5.833	7.19	ESE	91.21	0.00
11-Jun-2023	10.2	15.9	7.562	9.615	E	78.13	0.00
12-Jun-2023	8.2	17.2	12.544	17.129	wsw	246.24	0.00
13-Jun-2023	7.3	15.3	11.086	15.501	WNW	288.26	0.00
14-Jun-2023	8.4	14.2	7.369	10.367	WNW	275.92	0.00
15-Jun-2023	9.7	15.1	10.147	13.378	W	259.88	0.00
16-Jun-2023	9.1	15.6	15.167	20.839	S	178.46	0.00
17-Jun-2023	6.6	16.4	14.419	20.005	SW	213.35	0.1
18-Jun-2023	6.6	13.6	7.504	10.513	W	264.21	0.00
19-Jun-2023	6.5	14.7	10.062	13.568	SW	203.28	0.00
20-Jun-2023	4.8	11.1	7.686	9.876	ENE	67.28	0.00
21-Jun-2023	6	10.5	13.22	17.391	ENE	48.72	0.1
22-Jun-2023	6	14.9	20.063	28	w	252.23	0.8
23-Jun-2023	7	13.3	14.202	19.912	WSW	240.79	0.00
24-Jun-2023	7.3	15.7	17.337	24.267	WNW	280.04	0.00
25-Jun-2023	7	13.7	13.904	19.006	NW	297.13	0.00
26-Jun-2023	9.1	14.7	6.584	8.618	W	251.19	0.00
27-Jun-2023	8.5	11.2	8.236	10.871	SW	177.44	1.1
28-Jun-2023	6.3	9.7	10.701	13.637	SW	214.40	0.00
29-Jun-2023	4.9	10.4	8.299	10.564	WSW	236.38	0.00
30-Jun-2023	6.4	12.9	7.175	8.967	W	256.12	0.00

Rainfall of 24.00mm fell in June 2023.



5 Data Log

Sample	Result Received		
Hi Volume Samples	26-07-2023		
TEOM	28-07-2023		
Dust Deposition	26-07-2023		
Vents & Bag House	30-06-2023		
Noise	05-12-2022		
Water	17-07-2023		
Blast vibration and overpressure	07-07-2023		
Weather	21-07-2023		
Date posted to web site	17-08-2023		

6 Correction Log

No corrections.