



Rasp Mine  
Monthly Environmental Monitoring Report  
October 2024

## **INTRODUCTION**

Broken Hill Operations Pty Ltd (BHOP) [a wholly owned subsidiary of CBH Resources Limited (CBH)] owns and operates the Rasp Mine (the Mine), which is located centrally within the City of Broken Hill on Consolidated Mine Lease 7 (CML7).

Mining has been undertaken within CML7 since 1885. The existing operations at the Rasp Mine include underground mining operations, a processing plant producing zinc and lead concentrates and a rail siding for concentrate dispatch. These operations are undertaken in accordance with Project Approval 07\_0018 under Part3A of the Environmental Planning and Assessment Act 1979 (EP&A Act).

As the holder of an Environmental Protection Licence, 12559, BHOP is required, under Section 66(6) of the NSW *Protection of the Environment Operations Act 1997*, to publish pollution monitoring data. In addition BHOP is required to publish data in accordance with its Project Approval 07\_0018 Schedule 4 Condition 9. These documents can be found on the Rasp Mine web site.

## **TABLE OF CONTENTS**

<b>1</b>	<b>AIR QUALITY .....</b>	<b>3</b>
1.1	HIGH VOLUME AIR SAMPLERS .....	3
1.2	TAPERED ELEMENT OSCILLATING MICROBALANCE SAMPLING (TEOM).....	9
1.3	DUST DEPOSITION SAMPLING .....	12
1.4	VENTILATION OUTLETS AND BAG HOUSE MONITORING .....	14
<b>2</b>	<b>NOISE.....</b>	<b>16</b>
2.1	BLASTING (VIBRATION AND OVERPRESSURE) .....	16
2.2	NOISE .....	17
<b>3</b>	<b>WATER .....</b>	<b>18</b>
3.1	GROUNDWATER.....	18
3.2	SURFACE WATER SAMPLE RECORD .....	18
<b>4</b>	<b>WEATHER DATA .....</b>	<b>20</b>
<b>5</b>	<b>DATA LOG .....</b>	<b>22</b>
<b>6</b>	<b>CORRECTION LOG.....</b>	<b>22</b>

## 1 Air Quality

The following pollutants as listed in the Project Approval DA 07\_0018 are required to be monitored in EPL 12559:

### Long Term Criteria for Particulate Matter

Pollutant	Averaging Period	Criterion
Total solid particles (TSP)	Annual	90 µg/m <sup>3</sup>
Particulate matter < 10 µm (PM <sub>10</sub> )	Annual	25 µg/m <sup>3</sup>

### Short Term Criterion for Particulate Matter

Pollutant	Averaging Period	Criterion
Particulate matter < 10 µm (PM <sub>10</sub> )	24 hour	50 µg/m <sup>3</sup>

### Long Term Criteria for Deposited Dust

Pollutant	Averaging Period	Maximum Project Contribution	Maximum Total Deposited Dust Level
Deposited dust	Annual	2 g/m <sup>2</sup> /month	4 g/m <sup>2</sup> /month

### 1.1 High Volume Air Samplers


There are four high volume air samplers used to measure ambient air quality at the Rasp Mine – HVAS (EPL10) and HVAS1 (EPL11) are located at the Silver Tank, central and to the south of the mine lease, and HVAS2 (EPL12) and HVAS3 (EPL57) are located adjacent to and north of Blackwood Pit. A map indicating these locations can be found on the Rasp Mine web site. HVAS and HVAS3 sample for total suspended particulates (TSP) and lead dust, and HVAS1 and HVAS2 sample for particulate matter less than 10 microns (PM<sub>10</sub>) and lead dust.

#### ***HVAS (EPL10) - Silver Tank (On Site) Results for October 2024***

DATE	TSP (µg/m <sup>3</sup> )	Lead (µg/m <sup>3</sup> )
1-Oct-24	14.60	0.01
7-Oct-24	39.10	0.19
13-Oct-24	32.60	0.16
19-Oct-24	NS	NS
25-Oct-24	NS	NS
31-Oct-24	NS	NS

NS = no sample


## Rasp Mine Monthly Environment Monitoring Report



HVAS (EPL10) is located on the southern boundary of Rasp Mine and while limit criteria do not apply at this point, they do apply at the closest residential location.

TSP dust results at HVAS for the month of October were lower than in previous months. The highest TSP results for October were  $39.10 \mu\text{g}/\text{m}^3$  on 7 October when winds were predominantly from the SSW suggesting the dust had originated from off-site. HVAS TSP was unable to sample on 19, 25, and 31 October due to power outages. Water carts apply water to site roads daily and dust suppressant is applied to free areas and unsealed roads. The annual rolling average for TSP at this location is  $38.34 \mu\text{g}/\text{m}^3$  at the end of October, higher than the average at the beginning of November 2023 which was  $36.01 \mu\text{g}/\text{m}^3$ .

The annual rolling average for TSP is determined using data with extreme dust events included.



TSP Lead dust results at HVAS for the month of October were lower than in previous months. The highest TSP Lead level for October was  $0.19 \mu\text{g}/\text{m}^3$  on 7 October when winds were predominately from the SSW. It is likely that the

## Rasp Mine Monthly Environment Monitoring Report


TSP Lead sampled on 7 October has originated from off-site. HVAS TSP was unable to sample on 19, 25, and 31 October due to power outages. Water carts apply water to site roads daily and dust suppressant is applied to free areas and unsealed roads. The rolling annual average for TSP Lead in October 2024 was  $0.16 \mu\text{g}/\text{m}^3$ , consistent with the rolling annual average of  $0.16 \mu\text{g}/\text{m}^3$  for TSP Lead in November 2023.

### ***HVAS1 (EPL11) - Silver Tank (On Site) Results for October 2024***

DATE	PM <sub>10</sub> ( $\mu\text{g}/\text{m}^3$ )	PM <sub>10</sub> Lead ( $\mu\text{g}/\text{m}^3$ )
1-Oct-24	4.80	0.01
7-Oct-24	8.50	0.04
13-Oct-24	10.80	0.05
19-Oct-24	NS	NS
25-Oct-24	NS	NS
31-Oct-24	NS	NS


NS = no sample

HVAS1 (EPL11) is located on the southern boundary of Rasp Mine and while limit criteria do not apply at this point, they do apply at the closest residential location.



PM<sub>10</sub> dust results at HVAS1 for the month of October were higher than in previous months. The highest PM<sub>10</sub> dust levels for October were  $10.80 \mu\text{g}/\text{m}^3$  on 13 October when winds were predominantly from the NE suggesting contribution from on-site sources. HVAS1 was unable to sample on 19, 25, and 31 October due to power outages. Water carts apply water to site roads daily and dust suppressant is applied to free areas and unsealed roads. The annual rolling average for PM<sub>10</sub> dust at this location is  $10.6 \mu\text{g}/\text{m}^3$  at the end of October 2024, lower than the annual rolling average at the beginning of November 2023 which was  $13.6 \mu\text{g}/\text{m}^3$ . External and extreme dust events are recorded in measurements.

## Rasp Mine Monthly Environment Monitoring Report




PM<sub>10</sub> Lead dust results at HVAS1 in the month of October were higher than in previous months. The highest Lead PM<sub>10</sub> result for October was 0.05 µg/m<sup>3</sup> on 13 October when winds were predominantly from the NE suggesting contribution from on-site sources. HVAS1 was unable to sample on 19, 25, and 31 October due to power outages. Water carts apply water to site roads daily and dust suppressant is applied to free areas and unsealed roads. The rolling annual average for PM<sub>10</sub> Lead in October was 0.05 µg/m<sup>3</sup>, consistent with the average of 0.05 µg/m<sup>3</sup> in November 2023.

### ***HVAS 2 (EPL12) – Blackwood Pit (On Site) Results for October 2024***

DATE	PM <sub>10</sub> (µg/m <sup>3</sup> )	PM <sub>10</sub> Lead (µg/m <sup>3</sup> )
1-Oct-24	13.20	0.01
7-Oct-24	7.20	0.03
13-Oct-24	6.30	0.03
19-Oct-24	7.00	0.01
25-Oct-24	NS	NS
31-Oct-24	10.50	0.02

NS = no sample


## Rasp Mine Monthly Environment Monitoring Report



HVAS2 (EPL12) is located on the northern boundary of Rasp Mine and while limit criteria do not apply at this point, they do apply at the closest residential location.

In October the PM<sub>10</sub> levels at HVAS2 were consistent with previous months. The highest recorded PM<sub>10</sub> dust reading for October was 13.20 µg/m<sup>3</sup> on 1 October when winds were from the SSE suggesting contribution from on-site sources. HVAS2 was unable to sample on 25 October due to power outages. The surface of Blackwoods TSF2 is treated with dust suppressant and the TSF spray system has been installed. The annual rolling average for PM<sub>10</sub> dust at this location is 11.6 µg/m<sup>3</sup> at the end of October, down from 16.72 µg/m<sup>3</sup> in November 2023.

The annual rolling average for PM<sub>10</sub> dust is determined using data with extreme dust events included.




PM<sub>10</sub> lead levels in October were lower than previous months. The highest recorded PM<sub>10</sub> Lead dust reading for October was 0.03 µg/m<sup>3</sup> on 7 and 13 October when winds were from the SSW and NE, respectively, suggesting contribution from site activities on 7 October and off-site sources on 13 October. HVAS2 was unable to sample on 25 October due to power outages. The surface of Blackwoods TSF2 is treated with dust suppressant and the TSF spray

system has been installed. The rolling annual average for PM<sub>10</sub> Lead in October was 0.08 µg/m<sup>3</sup>, down slightly from 0.09 µg/m<sup>3</sup> in November 2023.

### ***HVAS 3 (EPL57) – Blackwood Pit (On Site) Results for October 2024***

DATE	TSP (µg/m <sup>3</sup> )	Lead (µg/m <sup>3</sup> )
1-Oct-24	47.00	0.01
7-Oct-24	33.80	0.20
13-Oct-24	29.40	0.20
19-Oct-24	21.60	0.08
25-Oct-24	NS	NS
31-Oct-24	33.40	0.08

NS = no sample




HVAS3 (EPL57) was included in EPL 12559 on 14 March 2019 to provide for monitoring of TSP Dust on the northern boundary of the site at Blackwoods Pit TSF2.

TSP levels at HVAS3 were highest on 1 October with a result of 47.0 µg/m<sup>3</sup>, when winds were from the SSE, suggesting the dust source was likely Blackwoods TSF2. HVAS3 was unable to sample on 25 October due to power outages. The surface of Blackwoods TSF2 is treated with dust suppressant and the TSF spray system has been installed. The annual rolling average for TSP dust at this location is 36.37 µg/m<sup>3</sup> at the end of October, down from 54.56 µg/m<sup>3</sup> in November 2023.

The annual rolling average for TSP is determined using data with extreme dust events included.





TSP Lead levels in October were consistent with previous months, with the highest result of 0.20 µg/m<sup>3</sup> recorded on 7 and 13 October when winds were from the SSW and NE, respectively, suggesting contribution from site activities on 7 October and off-site sources on 13 October. HVAS3 was unable to sample on 25 October due to power outages. The rolling annual average for TSP Lead in October was 0.31 µg/m<sup>3</sup>, up from 0.34 µg/m<sup>3</sup> in November 2023. The surface of Blackwoods TSF2 is treated with dust suppressant and the TSF spray system has been installed.

## 1.2 Tapered Element Oscillating Microbalance Sampling (TEOM)

There are two Tapered Element Oscillating Microbalance (TEOM) sampling units used to measure ambient air quality at the Rasp Mine – TEOM1 (EPL13) is located off-site within the perimeter fence of Essential Water south of the mine lease, and TEOM2 (EPL14) is located on-site adjacent to Blackwood Pit to the north of the mine lease. A map indicating these locations can be found on the Rasp Mine web site. TEOM1 and TEOM2 are designed to operate continuously and sample for particulate matter less than 10 microns (PM<sub>10</sub>) in size.

Project Approval 07\_0018 criteria apply at TEOM1 and TEOM2, with two criteria listed for PM<sub>10</sub>, a 24 hour average criteria of 50 µg/m<sup>3</sup> and an annual average criteria of 25 µg/m<sup>3</sup>. Both Project Approval and Environment Protection Licence criteria exclude dust storms and other extraordinary events.

TEOM data is validated by third party consultants using Australian Standards and internal procedures, and is used to populate the table of TEOM monthly data provided below.

***TEOM1 (EPL13) (Off Site) and TEOM2 (EPL14) (On Site) Validated Results for October 2024***

Particulate Matter <10 Microns 24Hr Average				
Date	TEOM 1 ( $\mu\text{g}/\text{m}^3$ )	Compliant with 50 $\mu\text{g}/\text{m}^3$ 24hr average?	TEOM 2 ( $\mu\text{g}/\text{m}^3$ )	Compliant with 50 $\mu\text{g}/\text{m}^3$ 24hr average?
1-Oct-24	11.2	Y	20.9	Y
2-Oct-24	8.5	Y	6.4	Y
3-Oct-24	36.9	Y	20.0	Y
4-Oct-24	8.8	Y	5.7	Y
5-Oct-24	14.6	Y	12.8	Y
6-Oct-24	12.9	Y	9.4	Y
7-Oct-24	13.2	Y	12.6	Y
8-Oct-24	8.5	Y	14.8	Y
9-Oct-24	10.6	Y	8.7	Y
10-Oct-24	15.9	Y	14.9	Y
11-Oct-24	17.4	Y	29.5	Y
12-Oct-24	10.0	Y	14.9	Y
13-Oct-24	12.5	Y	11.6	Y
14-Oct-24	13.4	Y	19.1	Y
15-Oct-24	20.1	Y	24.4	Y
16-Oct-24	11.7	Y	8.5	Y
17-Oct-24	19.2	Y	NA	N
18-Oct-24	8.8	Y	4.3	Y
19-Oct-24	11.9	Y	8.1	Y
20-Oct-24	8.3	Y	5.2	Y
21-Oct-24	NA	N	NA	N
22-Oct-24	NA	N	NA	N
23-Oct-24	15.3	Y	10.8	Y
24-Oct-24	13.1	Y	15.5	Y
25-Oct-24	NA	N	NA	Y
26-Oct-24	12.5	Y	7.5	Y
27-Oct-24	13.3	Y	11.8	Y
28-Oct-24	10.3	Y	19.5	Y
29-Oct-24	13.7	Y	19.6	Y
30-Oct-24	12.1	Y	8.2	Y
31-Oct-24	13.9	Y	16.6	N

NA - sample collected but data invalid; NS – no sample collected for day

PM<sub>10</sub> monthly average dust levels at both TEOM units in October were higher than in previous months and there were no exceedences of daily limits except due to external events. Data collection at TEOM1 was interrupted on 21, 22 and 25 October due to power outages. Data collection at TEOM2 was interrupted on 17, 21, 22 and 25 October due to power outages.

The rolling annual average for PM<sub>10</sub> at TEOM1 with external dust events and invalid data removed for the period November 2023 to October 2024 is 12.64  $\mu\text{g}/\text{m}^3$ , higher than the rolling annual average of 10.66  $\mu\text{g}/\text{m}^3$  at the beginning of the annual period.

The rolling annual average for PM10 at TEOM2 with external dust events and invalid data removed for the period November 2023 to October 2024 is 14.01  $\mu\text{g}/\text{m}^3$ , higher than the rolling annual average of 9.87  $\mu\text{g}/\text{m}^3$  at the beginning of the reporting period.

Six-monthly servicing of TEOMs was conducted from 25 to 27 June and included zero-testing which extends over two days. A portable PM<sub>10</sub> monitor was located adjacent to TEOM2 to provide real-time dust readings and dust level alerts whilst the TEOM was undergoing servicing and testing.

The PM<sub>10</sub> 24-hour rolling annual average for both TEOM sites remain below the annual average criteria of 25  $\mu\text{g}/\text{m}^3$ .




### 1.3 Dust Deposition Sampling

There are seven dust deposition gauges to measure ambient air quality at the Rasp Mine – D1 to D7. D1 and D6 are located off-site, D1 near the St Johns training facility north of the Rasp Mine and D6 in Casuarina Avenue south of the Rasp Mine. D2 to D5 and D7 are located on the mine lease in various locations. A map indicating these locations can be found on the Rasp Mine web site. Dust samples are collected monthly and analysed for total deposited dust and deposited lead dust.

#### *Dust Deposition Gauges D1 (EPL3) to D7 (EPL9) – Results for October 2024*

Total Deposited Dust (g/m <sup>2</sup> .Month)							
Sample Period	D1 (off site)	D2 (off site)	D3 (on site)	D4 (off site)	D5 (on site)	D6 (off site)	D7 (on site)
October 2024	0.7	0.5	1.0	1.4	1.4	2.5	1.0
Annual Rolling Average	0.81	1.08	1.02	2.82	1.71	1.79	0.72
Background (2010)	4.0	3.1	4.3	5.7	- <sup>1</sup>	5.8	- <sup>1</sup>

Note: "<sup>1</sup>" = background not available, N/A = not applicable as dust deposition unit is located on site, NS = No sample



The dust levels recorded in Dust Gauges in October 2024 were higher than previous months. The highest dust levels in October were recorded in the D6 Casuarina Avenue gauge. The predominant wind direction for October was from the South as shown in the Wind Rose in Section 4.

Dust Deposition Gauges that are located off-site must adhere to criteria for annually averaged deposited dust of 4 g/m<sup>2</sup>.month. All off-site Dust Deposition Gauges were compliant in the reporting period.


Dust suppressant is applied to unsealed areas of the site and roads are frequently watered using water carts in an attempt to control dust emissions. The waste dump adjacent to the rail loadout is treated with dust suppressant to capture any loose dust accumulating on the lower batters and on the upper surface.

# Rasp Mine Monthly Environment Monitoring Report

## Total Deposited Lead (g/m<sup>2</sup>.Month)

Sample Period	D1 (off Site)	D2 (on site)	D3 (on site)	D4 (on site)	D5 (on site)	D6 (off Site)	D7 (on site)
October 2024	0.0016	0.0005	0.0041	0.006	0.0018	0.0001	0.0058
Background (2010)	0.0034	0.005	0.005	0.006	-1	0.004	-1

Note: "1"= background not available, NS = No sample



There are no guidelines for deposited lead dust. Lead results in October 2024 were highest in the D7 Blackwoods Pit gauge. There were variable wind directions in October although the prominent wind direction for the month of October was from the South. The source of Lead in the sample was likely from on-site sources.

Dust suppressant is applied to unsealed areas of the site and roads are frequently watered using water carts in an attempt to control dust emissions. The waste dump adjacent to the rail loadout is treated with dust suppressant to capture any loose dust accumulating on the lower batters and on the upper surface.

## 1.4 Ventilation Outlets and Bag House Monitoring

There are two locations to measure pollutants from exhausts or stacks; these include the Primary Ventilation Shaft, measuring pollutants from underground firings, and the Baghouse Stack at the crusher measuring dust. Each are located on site; the Primary Ventilation Shaft is located centrally and to the north of the mine lease and the Primary Crusher Baghouse Stack is located within the area of the processing plant to the east of the lease. Shaft 6 (EPL56) was removed as a monitoring location with the variation of EPL12559 in March 2019 as it became an intake rather than an exhaust in June 2018. A map indicating these locations can be found on the Rasp Mine web site. Samples are collected quarterly and analysed for a number parameters listed in below. Reference to the item required in the Rasp Mine Environment Protection Licence (EPL) is provided below. Emissions monitoring is conducted quarterly.

The following criteria apply:

### Primary Ventilation Shaft (EPL1)

	Unit	Criteria
Nitrogen Oxides	mg/m <sup>3</sup>	350
Volatile Organic Compounds	mg/m <sup>3</sup>	40

### Primary Ventilation Shaft (EPL1) and Crusher Baghouse (EPL2)

	Unit	Criteria
Total Suspended particles (TSP)	mg/m <sup>3</sup>	20
Type 1 and Type 2 <sup>1</sup>	mg/m <sup>3</sup>	1

**Note 1:** "Type 1 substance" means the elements antimony, arsenic, cadmium, lead or mercury or any compound containing one or more of those elements.

"Type 2 substance" means the elements beryllium, chromium, cobalt, manganese, nickel, selenium, tin or vanadium or any compound containing one or more of those elements.

### ***Primary Vent Shaft (EPL1) and Crusher Baghouse (EPL2) Results for October 2024***

---

Emissions monitoring was conducted at the Primary Vent Shaft (EPL1) and the Crusher Baghouse (EPL2) on 13 August 2024. Results were within licence limits and are provided below.

Parameter	Unit	Primary Vent Shaft (EPL1)	Crusher Baghouse (EPL2)
Dry Gas Density	Kg/m <sup>3</sup>	1.29	1.29
Moisture	%	1.20	2.1
Molecular weight of stack gases	g/m <sup>3</sup>	1,288	1,288
Temperature	°C	24.0	23.0
Nitrogen Oxides	mg/m <sup>3</sup>	2.05	NA
Volatile Organic Compounds	mg/m <sup>3</sup>	0.490	NA
Total Suspended particles	mg/m <sup>3</sup>	1.24	4.47
Type 1 and Type 2	mg/m <sup>3</sup>	0.021	0.131
Velocity	m/sec	11.86	22.9
Volumetric Flowrate	m <sup>3</sup> /sec	189	9.0

## 2 Noise

### 2.1 Blasting (Vibration and Overpressure)

There are five compliance vibration monitors at various locations measuring for vibration and overpressure from blast firings. These include V1 to V5 which are located on-site and off-site. A map indicating these locations can be found on the Rasp Mine web site. In addition, there are a number of roving monitors which may be used to monitor vibration and overpressure at particular locations as required. Monitors operate continuously and are automatically triggered to record when a blast occurs. The following conditions apply as listed in the PA 07\_0018 and EPL 12559:

#### Blasting Criteria (Western Mineralisation and Main Lodes excluding Block 7)

Location	Airblast Overpressure (dB(Lin Peak))	Ground Vibration (mm/s)	Allowable Exceedance (for production and development blasts)
Residence on privately owned land (7am-7pm)	115	5	5% of the total number of blasts over a 12-month period <sup>1</sup>
(7am-7pm)	120	10	0%
(7pm-10pm)	105	-	-
(10pm-7am)	95	-	-
Public Infrastructure	-	100	0%

**Note 1:** Does not apply until completion of Pollution Reduction Program on the EPL at the end of 2018. Applies to EPL criteria in the period for the Annual Return 3 Nov to 2 Nov the following year and to DPE criteria in the reporting period 1 Jul to 30 Jun each year.

#### Blasting Criteria (Block 7)

Location	Airblast Overpressure (dB(Lin Peak))	Ground Vibration (mm/s)	Allowable Exceedance (for production and development blasts)
Residence on privately owned land (7am-7pm)	115	3 (interim)	5% of the total number of blasts over a 12-month period <sup>1</sup>
(7am-7pm)	120	10	0%
(7pm-10pm)	105	-	-
(10pm-7am)	95	-	-
Broken Hill Bowling Club, Italio (Bocce) Club, Heritage Items within CML7	-	50	0%
Perilya Southern Operations	-	100	0%
Public Infrastructure	-	100	0%

**Note 1:** Applies to EPL criteria in the period for the Annual Return 3 Nov to 2 Nov the following year and to DPE criteria in the reporting period 1 Jul to 30 Jun each year.

In addition the following conditions also apply:

- Production blasts may occur between 6.45 am and 7.15 pm on any day
- 1 production blast per day, with 6 per week averaged over a calendar year
- 6 development blasts per day, with 42 per week averaged over a calendar year



***Blasting Data Summary Results for October 2024 (annual period)***

---

**Total Blasts:**

- 0 production blasts occurred before 6.45 am or after 7.15 pm
- The number of Production blasts averaged 1.42 per week over the previous calendar year
- The number of Development blasts averaged 0.88 per week over the previous calendar year

**Western Mineralisation and Main Lodes (excluding Block 7):**

- 0 Blast recorded >5 mm/s
- 0 Blasts recorded >10 mm/s
- 0 development blasts recorded an over pressure level over 95 dBL (10pm to 7am)
- 0 development blasts recorded an over pressure level over 105 dBL (7pm to 10pm)
- 0 Blasts recorded an over pressure level over 115dBL (7am to 7pm)
- 0 Blasts recorded an over pressure level over or 120 dBL at any time
- Percentage of development blasts over 5 mm/sec for the annual period = 0%
- Percentage of production blasts over 5 mm/sec for the annual period = 0%

**Block 7:**

- 0 Blasts recorded >3 mm/s
- 0 Blasts recorded >10 mm/s
- 0 Blasts recorded >50 mm/s at V6
- 0 development blasts recorded an over pressure level over 95 dBL (10pm to 7am)
- 0 development blasts recorded an over pressure level over 105 dBL (7pm to 10pm)
- 0 Blasts recorded an over pressure level over 115 dBL (7am to 7pm)
- 0 Blasts recorded an over pressure level over or 120 dBL at any time
- Percentage of development blasts over 3mm/sec for the annual period = 0%
- Percentage of production blasts over 3mm/sec for the annual period =100%

The have been no production blasts in the Western Mineralisation and Main Lodes producing vibration at monitors over 5 mm/sec for the 12-month period.

There have been no production blasts in Block 7 for the 12-month period.

## **2.2 Noise**

Noise monitoring is undertaken as per the NSW Noise Policy for Industry at a frequency of once per annum. Attended environmental noise monitoring was done during the night period of 18 December 2023 at 14 monitoring locations. Noise levels from site complied with relevant limits at all monitoring locations during the December 2023 survey.

## 3 Water

### 3.1 Groundwater

There are eighteen sampling locations for groundwater. GW01 (EPL37) to GW16 (EPL52) are piezometers installed at various locations around the mine site and are sampled quarterly. There are also two sampling locations for water pumped from underground mining, Shaft 7 (EPL53) and Kintore Pit (EPL54), which are sampled monthly. A map indicating these locations can be found on the Rasp Mine web site. Groundwater monitoring is scheduled for completion in March, June, October and December. No limits are applied in the EPL to the results from groundwater monitoring. Levels for all parameters are stable.

#### Ground and Mine Water Monitoring Requirements

EPA Identification Number	Frequency	Parameters to be analysed
Shaft 7 EPL53	Monthly	alkalinity (calcium carbonate (CaCO <sub>3</sub> )), cadmium (Cd), calcium (Ca), chloride (Cl), electrical conductivity (EC), iron (Fe), lead Pb), magnesium (Mg), manganese (Mn), pH, sodium (Na), sulphate (SO <sub>4</sub> ), total dissolved solids (TDS) and zinc (Zn)
Kintore Pit (U/G dewatering) EPL54	Monthly	
Piezometers EPL37 (GW01) to EPL52 (GW16)	Quarterly	

#### *Shaft 7 (EPL53) and Kintore Pit (EPL54) Results for October 2024*

Sample Point	pH	EC (µS/cm <sup>2</sup> )	TDS (mg/l)	Alkalinity (CaCO <sub>3</sub> ) (mg/l)	SO <sub>4</sub> (mg/l)	Cl (mg/l)	Ca (mg/l)	Mg (mg/l)	Na (mg/l)	Cd (mg/l)	Pb (mg/l)	Mn (mg/l)	Zn (mg/l)	Fe (mg/l)
Shaft 7 (EPL53)	No pumping													
Kintore Pit (EPL54)	6.39	13700	14600	5	5770	1910	507	344	1900	3.14	2.53	418	1050	0.05

#### *Groundwater Bores (EPL37 - EPL52) Results for October 2024*

Groundwater monitoring not scheduled in October.

### 3.2 Surface Water Sample Record

There are seven sampling locations for surface water, these include surface water basins located on the mine lease to capture and retain rainfall and two locations up and down stream of an ephemeral creek located south of the mine lease boundary. A map indicating these locations can be found on the Rasp Mine web site. Based on historical data, sampling is most likely to be undertaken in October (highest rainfall month as recorded by Bureau of Meteorology) and April.

#### Surface Water Monitoring Requirements

Description	Frequency	Parameters to be Analysed
Federation Way Culvert EPL29/S31-1	2 x per year, six months apart	cadmium (Cd), chloride (Cl), electrical conductivity (EC), lead Pb), manganese (Mn), pH, sodium (Na), sulphate (SO <sub>4</sub> ),
Ryan Street Dam EPL31/S49	2 x per year, six months apart	
Adjacent Olive Grove EPL32/S1A	2 x per year, six months apart	
Adjacent Bowls Club EPL33 /S9-B2	2 x per year, six months apart	

Rasp Mine

Monthly Environment Monitoring Report

Horwood Dam EPL34/S34	2 x per year, six months apart	total dissolved solids (TDS) and zinc (Zn)
Upstream Bonanza St EPL35	2 x per year, six months apart	
Downstream Sydney Rd EPL36	2 x per year, six months apart	

Surface Water Results for October 2024

Sample Point	pH	EC (µS/cm <sup>2</sup> )	TDS (mg/l)	Alkalinity (CaCO <sub>3</sub> ) (mg/l)	SO4 (mg/l)	Cl (mg/l)	Ca (mg/l)	Mg (mg/l)	Na (mg/l)	Cd (mg/l)	Pb (mg/l)	Mn (mg/l)	Zn (mg/l)	Fe (mg/l)
Horwood (EPL34)	6.59	13000	14000	10	5040	1740	564	363	1870	2.33	1.9	330	513	0.05
S9B-2 (EPL33)	Insufficient sample													
Downstream (EPL36)	Insufficient sample													
S31-1 (EPL29)	6.31	1430	1530	2	955	38	131	9	26	2.08	2.2	51.4	232	0.05
S49 (EPL31)	6.59	742	670	5	351	23	91	6	10	0.46	0.455	18.3	58.4	0.05
S1-A (EPL31)	6.82	817	669	10	373	51	109	8	36	0.201	0.312	5.2	25	0.05
Upstream (EPL35)	Insufficient sample													

## 4 Weather Data


The weather station continuously monitors the following parameters as per Point 55 of the Environmental Protection Licence.

The following parameters are required to be recorded each month as listed in the EPL 12559:

**Rasp Mine Weather Station (EPL55) Monitoring Requirements**

Parameter	Sampling method	Units of measure	Averaging period	Frequency
Temperature at 10 metres	AM-4	degrees Celsius	15 minutes	Continuous
Wind Direction at 10 metres	AM-4	degrees in a clockwise direction from True North	15 minutes	Continuous
Wind Speed at 10 metres	AM-4	metres per second	15 minutes	Continuous
Rainfall	AM-4	millimetres	1 hour	Continuous
Sigma theta	AM-2 & AM-4	degrees	15 minutes	Continuous

The wind rose provided below indicates that the prominent wind direction for the month of October was from the South.



# Rasp Mine

## Monthly Environment Monitoring Report

### Weather Data Summary for October 2024

Date	Temperature @ 10m (°C)		Wind Speed @ 10m (km/hr)		Predominant Wind Direction @ 10m		Rainfall (mm)
	Min	Max	Min	Max	Cardinal	Degree	Total
01-Oct-18	10.1	20.8	3.2	34.2	SSE	156	0.02
02-Oct-18	12.7	22.4	1.1	33.1	ESE	112	0.04
03-Oct-18	14.5	28.3	1.8	50.4	NNE	23	0.89
04-Oct-18	16.9	25.0	1.4	42.1	North	6	0.04
05-Oct-18	14.4	23.7	0.7	54.0	WSW	249	0.02
06-Oct-18	13.3	25.7	0.7	32.4	WSW	245	0.00
07-Oct-18	18.9	28.9	0.4	29.2	SSW	205	0.02
08-Oct-18	11.9	20.8	2.2	40.0	SSE	159	0.01
09-Oct-18	8.8	22.5	1.1	28.4	SE	137	0.00
10-Oct-18	16.4	29.5	1.1	32.8	South	183	0.00
11-Oct-18	9.9	21.8	4.3	38.2	SSE	160	0.00
12-Oct-18	11.7	24.2	2.9	39.6	SE	132	0.00
13-Oct-18	16.6	27.5	0.7	24.5	NE	45	0.00
14-Oct-18	21.4	29.2	0.4	20.5	SSW	204	0.01
15-Oct-18	19.2	28.9	0.7	46.4	East	91	0.07
16-Oct-18	18.0	30.8	0.4	34.2	North	5	0.06
17-Oct-18	19.5	25.1	0.7	51.8	NE	42	26.68
18-Oct-18	16.0	23.9	1.8	50.4	SW	225	8.26
19-Oct-18	9.3	22.2	4.0	41.8	South	181	0.00
20-Oct-18	12.0	25.8	2.2	28.1	SSE	157	0.00
21-Oct-18	16.5	29.3	0.4	21.6	East	87	0.00
22-Oct-18	23.0	33.3	0.7	37.8	ENE	68	0.00
23-Oct-18	17.1	26.2	0.4	36.7	South	186	0.00
24-Oct-18	10.9	20.2	5.0	37.1	South	179	0.02
25-Oct-18	9.3	20.5	1.1	32.8	South	182	0.00
26-Oct-18	13.6	24.2	0.4	27.4	NE	48	0.00
27-Oct-18	18.9	29.7	0.4	33.5	NNE	24	0.00
28-Oct-18	12.7	24.5	2.9	41.8	South	181	0.00
29-Oct-18	12.3	26.0	1.1	32.4	South	180	0.00
30-Oct-18	19.1	29.6	0.4	31.3	ENE	68	0.00
31-Oct-18	17.0	24.7	2.3	21.8	South	180	2.52

Rainfall of 38.7 mm in October 2024.

## 5 Data Log

Sample	Result Received
Hi Volume Samples	15-11-2024
TEOM	28-11-2024
Dust Deposition	20-11-2024
Vents & Bag House	09-10-2024
Noise	05-02-2024
Water	15-11-2024
Blast vibration and overpressure	01-11-2023
Weather	01-11-2023
Date posted to web site	18-12-2024

## 6 Correction Log

No corrections.