

V-GUIDE AND CUSTOM EXTRUDED PROFILES

V-guide tracking profiles run along the top or bottom of the conveyor belt to provide additional belt tracking support. Available solid or notched.



100% made in USA
with USA
raw materials




White, Black, Blue
Custom colors
available



Standard spools
500 feet;
Custom lengths
available

Determining what Guide Size to Use

If measuring a pulley or slider bed groove, the groove should be approximately 8 to 10mm wider than the guide. For example, a K10 guide would be suitable for a pulley with an 18 to 20mm wide groove.



Minimum Pulley Recommendations* added to your belt's minimum pulley rating

SPEC	SOLID	NOTCHED
K6	1.00"	0.75"
K8	1.25"	1.00"
K10	2.00"	1.50"
A-MOD	2.50"	2.00"
A/K13	3.00"	2.50"
B/K17	4.00"	3.00"
C/K22	6.00"	5.00"

**A number of factors must be taken into consideration to determine a belt's minimum pulley. These are guidelines and each application must be evaluated on a case by case basis.*

Specifications

SPEC	BASE	TOP WIDTH	HEIGHT
K6	6mm	4mm	4mm
K8	8mm	5mm	5mm
O/K10	0.375"	0.250"	0.250"
A-MOD	0.500"	0.350	0.250"
A/K13	0.500"	0.312"	0.312"
B/K17	0.655"	0.406"	0.406"
C/K22	0.875"	5.00"	0.530"

PVC V-GUIDE IN STOCK

K6, K8, K10, A/K13,
A-MOD, B/K17, C/K22

- * FDA APPROVED
- * 75 SHORE A PVC
- * ANTI-MICROBIAL & METAL DETECTABLE AVAILABLE
- * WHITE, BLACK, BLUE IN STOCK
- * CUSTOM COLORS & LENGTHS AVAILABLE
- * MADE IN BATAVIA, NY

Contact Upson Maybach:

(585) 343-6211 / 662 E Main St, Batavia, NY 14020 / profiles@upsonmaybach.com / www.upsonmaybach.com

