

K4: 4 PLY SOLID WOVEN ARAMID (KEVLAR®)

Applications	High temperature conveying: ceramics, glass, aluminum extrusion, welding curtain, etc.
Material	100% Aramid (KEVLAR®)
Weight	3.2 KG/M2 / 0.75 LBS/SQFT - +/- 10%
Elongation	Up to 4%
Operating Temperature	Up to 500°C / 950°F
Thickness	4.5 MM / 0.177 IN - +/- 10%
Recommended Joining Methods	Laced: Viton Treated & Laced - U2, RS125 Sewn: Butt & Sewn, Step & Sewn
Air Permeability	Not Checked
Finish	Spun Fabric, Non-Slip
Standard Stock Widths in Inches	1.13, 1.5, 1.75, 3, 4, 5, 12, 18, 24, 36
Minimum Pulley Diameter	100 MM / 4 Inches



Representative sample of K4

Product Notes: Solid Woven Aramid belts are manufactured to common widths. Custom widths can be cut and overcast on demand at Upson Maybach's workshop. Woven to width special productions are 500-foot requirements. Woven fabrics are dynamic and can shrink and expand with changes in the environment.



(585) 343-6211



662 E Main St, Batavia, NY 14020



www.upsonmaybach.com