

## Specifications

	VPL-SH1-28"	VPL-SH1-52"	VPL-SH1-72"	VPL-SH1-105"
Standard Platform Sizes (inside measurements)	34" x 48.0" Custom Sizes Available*	34.0" x 48.0" or 34.0" x 54.0" Custom Sizes Available*	34.0" x 48.0" or 34.0" x 54.0" Custom Sizes Available*	34.0" x 48.0" or 34.0" x 54.0" Custom Sizes Available*
Maximum Lifting Height	28.0"	52.0"	72.0"	105.0"
Power Supply	24 VDC AC Operation*	115 AC or 24 VDC	115 AC or 24 VDC	115 AC or 24 VDC
Input Source	110-120 Volt, 4 A 60 Hz battery charger  Optional AC Operation*	110-120 Volt, 15 A 60 Hz dedicated service or 110-120 Volt, 4 A 60 Hz battery charger	110-120 Volt, 15 A 60 Hz dedicated service or 110-120 Volt, 4 A 60 Hz battery charger	110-120 Volt, 15 A 60 Hz dedicated service or 110-120 Volt, 4 A 60 Hz battery charger
Motor and Drive	1 HP, AC @ 1750 rpm and VDC @ 1500 rpm ACME Screw Drive with tooth belt reduction	1 HP, AC @ 1750 rpm and VDC @ 1500 rpm ACME Screw Drive with tooth belt reduction	1 HP, AC @ 1750 rpm and VDC @ 1500 rpm ACME Screw Drive with tooth belt reduction	1 HP, AC @ 1750 rpm and VDC @ 1500 rpm ACME Screw Drive with tooth belt reduction
Motor Controller	24 VDC relay control	24 VAC relay control	24 VAC relay control	24 VAC relay control
Speed (Maximum)	AC: 7.5 feet per minute DC: 6.8 feet per minute	AC: 7.5 feet per minute DC: 6.8 feet per minute	AC: 7.5 feet per minute DC: 6.8 feet per minute	AC: 7.5 feet per minute DC: 6.8 feet per minute
Safety	<ul style="list-style-type: none"> <li>✓ Emergency Stop</li> <li>✓ Safety Under-pan</li> <li>✓ Manual Lowering</li> </ul>	<ul style="list-style-type: none"> <li>✓ Emergency Stop</li> <li>✓ Safety Under-pan</li> <li>✓ Manual Lowering</li> </ul>	<ul style="list-style-type: none"> <li>✓ Emergency Stop</li> <li>✓ Safety Under-pan</li> <li>✓ Manual Lowering</li> </ul>	<ul style="list-style-type: none"> <li>✓ Emergency Stop</li> <li>✓ Safety Under-pan</li> <li>✓ Manual Lowering</li> </ul>
Ramp	Mechanical Auto	Mechanical Auto	Mechanical Auto	Mechanical Auto
Maximum Lift Capacity	750 lbs	750 lbs	750 lbs	750 lbs
What separates us from the rest	<ul style="list-style-type: none"> <li>✓ Light Weight</li> <li>✓ Easy to Install</li> <li>✓ Small foot print</li> <li>✓ Unique installation</li> <li>✓ Small tower</li> <li>✓ Polycarbonate side walls for added durability</li> </ul>	<ul style="list-style-type: none"> <li>✓ Light Weight</li> <li>✓ Easy to Install</li> <li>✓ Unique installation</li> <li>✓ Aluminum and stainless steel construction</li> <li>✓ Interchangeable 90° exit</li> <li>✓ Field reversible</li> <li>✓ Polycarbonate side walls for added durability</li> </ul>	<ul style="list-style-type: none"> <li>✓ Light Weight</li> <li>✓ Easy to Install</li> <li>✓ Unique installation</li> <li>✓ Aluminum and stainless steel construction</li> <li>✓ Interchangeable 90° exit</li> <li>✓ Field reversible</li> <li>✓ Polycarbonate side walls for added durability</li> </ul>	<ul style="list-style-type: none"> <li>✓ Light Weight</li> <li>✓ Easy to Install</li> <li>✓ Unique installation</li> <li>✓ Aluminum and stainless steel construction</li> <li>✓ Interchangeable 90° exit</li> <li>✓ Field reversible</li> <li>✓ Polycarbonate side walls for added durability</li> </ul>

\* - ask for additional details and availability in your location