

Sirius Aluminum Cargo Trailers

Model ALU	Internal dimensions lxbxh (cm)	Number of axles	Tare weight kg	Total weight kg	Tire size	Height tie-down cm
G255	251x141x190	1	650	1000/1300/1500	185-70R13 / 175-R14 / 195-65R15	100
G305	301x171x190	1	700	1000/1300/1500	185-70R13 / 175-R14 / 195-65R15	100
G305	301x171x190	2	750	2000/2500/3000/3500	185-70R13 / 195-65R15	100
G375	371x171x190	2	850	2000/2500/3000/3500	185-70R13 / 195-65R15	100
G455	451x171x190	2	950	2000/2500/3000/3500	185-70R13 / 195-65R15	100
G525	521x171x190	3	1050	2000/2500/3000/3500	185-70R13 / 195-65R15	100

Model ALU	Interior light	Tow hitch pressure empty/loaded kg	Door/ramp combination	Floor 18 mm wood	Loading platform height cm	Ventilating chassis	Anti-skid on ramp	Ramp with gas springs and running flush
G255	1	20 / 90	•	18mm	43 - 45	•	•	•
G305	2	20 / 90	•	18mm	43 - 45	•	•	•
G305	2	20 / 90	•	18mm	43 - 45	•	•	•
G375	2	20 / 90	•	18mm	43 - 45	•	•	•
G455	2	20 / 90	•	18mm	43 - 45	•	•	•
G525	2	20 / 90	•	18mm	43 - 45	•	•	•