

Sirius Refrigerated Cargo Trailers

Model ISO	Internal dimensions lxbxh (cm)	Number of axles	Tare weight kg	Total weight kg	Tire size	Height tie-down cm
G255	245x135x185	1	800	1000/1300/1500	185-70R13 / 175-R14 / 195-65R15	100
G305	295x165x185	1	850	1000/1300/1500	185-70R13 / 175-R14 / 195-65R15	100
G305	295x165x185	2	900	2000/2500/3000/3500	185-70R13 / 195-65R15	100
G375	365x165x185	2	1000	2000/2500/3000/3500	185-70R13 / 195-65R15	100
G455	445x165x185	2	1150	2500/3000/3500	185-70R13 / 195-65R15	100
G525	515x165x185	3	1300	2500/3000/3500	185-70R13 / 195-65R15	100
G305	295x165x235	2	975	2000/2500/3000/3500	185-70R13 / 195-65R15	100
G375	365x165x235	2	1025	2000/2500/3000/3500	185-70R13 / 195-65R15	100
G455	445x165x235	2	1250	2500/3000/3500	185-70R13 / 195-65R15	100
G525	515x165x235	3	1400	2500/3000/3500	185-70R13 / 195-65R15	100

Model ISO	Interior light	Tow hitch pressure empty/loaded kg	Door/ramp combination	Floor 18 mm wood	Loading platform height cm	Ventilating chassis	Anti-skid on ramp	Ramp with gas springs and running flush	Cooling, standard
G255	1	20 / 90	•	18mm*	43 - 45	•	•	•	1600 watt
G305	1	20 / 90	•	18mm*	43 - 45	•	•	•	1600 watt
G305	1	20 / 90	•	18mm*	43 - 45	•	•	•	1600 watt
G375	2	20 / 90	•	18mm*	43 - 45	•	•	•	1600 watt
G455	2	20 / 90	•	18mm*	43 - 45	•	•	•	2100 watt
G525	2	20 / 90	•	18mm*	43 - 45	•	•	•	2100 watt
G305	1	20 / 90	•	18mm*	43 - 45	•	•	•	2100 watt
G375	2	20 / 90	•	18mm*	43 - 45	•	•	•	2100 watt
G455	2	20 / 90	•	18mm*	43 - 45	•	•	•	2100 watt
G525	2	20 / 90	•	18mm*	43 - 45	•	•	•	2100 watt

* = The floor can be insulated on request