

收缩袋 Telescopic spout

Good durability, compact conformation, reliable performance, easy to operate and maintain, high loading and discharging efficiency, dustfree. Widely used in quick loading/ discharging bulk goods into/ from trucks, train, or ships, such as cement, lime, alumina, pulverized coal, foodstuff etc.



深层三维过滤材料,100%纯纤维以 针刺方法行程立体、高度蓬松的三维深 度、迂回曲折的过滤层。他的特点是 纤维组织疏松,高空隙率增加了杂质容载量。该种纤维材料系复式截留模式,有效清除固体及软性颗粒,较大的颗粒杂质被截留在纤维表面,而细微颗粒则被捕捉于滤材深层,确保使用中不会因压力增大而破损,具有较高过滤效率。此外高温表面热处理,应用瞬间烧结技术/压光处理,有效防止过滤时纤维受流体高速冲带而散失,既保证了无纤维脱离造成滤液污染现象,又避免了传统锟压造成滤孔堵塞而缩短滤袋寿命,同时压差小又不影响流速。备有聚丙烯、聚酯等材料的滤布,过滤精度1-200µm。

PP/PE 1-200µm liquid filtration cloth

- 1. Materials available: PE(polyester), PP(polypropylene)
- 2. Working temperature: < 150 C
- 3. Specialties: puffy fiber structure, high air permeability, repeat dust capture feature, better dust holding capacity, low fiber loss, no liquid contamination, long durability, low filtration resistance, liquid pressure dropping
- 4. Techniques used: needle punching & singeing/press polish
- 5. Specification: 1-200µm
- 6. Width: Dominated by customer within 2.2m
- 7. Application: liquid filtration

液体过滤袋

主要应用于:食品及饮料;生物工程 及医药;石化及化工;汽车制造;石油 及天然气;电子及电镀;涂料、油漆 油墨;核电与火电及废液过滤;摄影 胶片生产工艺液体过滤;日用化工 的液体和气体净化;机械加工及制冷 行业各种冷却液过滤;纺织、印染、 造纸行业的各种液体净化

滤袋沿口材料:不锈钢、镀锌钢圈及 聚丙烯塑料圈

Liquid filter bags

Widely used in industries such as food and beverage, bioengineering and pharmaceutical, auto mobile manufacturing, petroleum and natural gas, electronics and galvanization, coat, paint and ink, nuclear/thermal power plant and waste liquid filtration, fluid filtration in photographic film production process, fluid and gas purification in daily chemicals industry, filtration of various coolants in mechanical processing and refrigeration industries, purification of various fluids in textile, printing & dyeing and paper making industries.

Filter bag collar available: stainless steel collar, galvanized steel collar, PP plastic collar

Filtration precision: 1, 5, 10, 15, 25, 50, 75, 100, 150, 200 µm



液体滤袋沿口材料:不锈钢圈,镀锌钢圈以及聚丙烯塑料圈。	Sizes	尺寸 Dimension (INCH)	尺寸 Dimension (CM)
Filter bag collar available: stainless steel collar,	Size 1	Φ7 x 16	Φ 17.8 x 40.65
galvanized steel collar, PP plastic collar	Size 2	Φ7 x 32	Φ 17.8 x 81.3
Filtration precision: 1, 5, 10, 15, 25, 50, 75, 100,	Size 3	Φ 4 x 8.25	Φ 10.2 x 20.9
150, 200 μm	Size 4	Φ 4 x 14	Φ 10.2 x 35.5

产品规格 Specification(mm)	精度范围 Precision range (μm)	过滤面积 Filtering area(m²)	水通量 Water flux(T/h)
Ф180×420	1-200	0.23	17
Ф180x820	1-200	0.46	35