



# Heat Shrinkable Tubing

[www.hstubing.com](http://www.hstubing.com)

Type	Product	Shrink Ratio	Recovery Temp. (°C)	Operating Temp. (°C)	Voltage (V)	Flame Retardant	Adhesive	UL File No.	MIL Spec.	Available Colors																	
										Black	White	Yellow	Red	Blue	Green	Gray	Violet	Orange	Brown	Clear	Yellow/Green	Rust					
Single Wall Polyolefin	DUNBAR-1625GT	2:1	80	-55 ~ 125	600	✓	✗	E319303	✗																		
	DUNBAR-1635F		90			✓	✗			AS23053/5																	
	DUNBAR-1635F YL/GN		130			✓	✗		✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗		
	DUNBAR-1635S	3:1	90			✓	✗	E319303	✗																		
	DUNBAR-3635			4:1			✓		✗		AS23053/5																
	DUNBAR-4635						✓	✗	E319314																		
Dual Wall Polyolefin (Adhesive Lined)	DUNBAR-1625W	2:1	120	-55 ~ 110	600	✓	✓	E319314	AS23053/4 C2																		
	DUNBAR-2690NW	3:2		-35 ~ 90		✗	✓		✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗		
	DUNBAR-3625WS	3:1	125			✓	✓	E319314	AS23053/4 C1																		
	DUNBAR-3635W		120	-55 ~ 110		✓	✓		AS23053/4 C3																		
	DUNBAR-4635W	4:1	130	-55 ~ 130		✓	✓		AS23053/4																		
	DUNBAR-4635WS			-55 ~ 110		✓	✓		✗																		
	DUNBAR-4635WT			120		-55 ~ 110	✓	✓	AS23053/4																		
	DUNBAR-4650WS			130		-55 ~ 150	✓	✓	✗																		
Medium & Heavy Wall Tubing	DUNBAR-CATV	3:1	120	-55 ~ 125	1000	✗	✓	E19303	✗																		
	DUNBAR-PHWT-FR					AS23053/15 C1																					
	DUNBAR-PMWT-FR					AS23053/15 C2																					
	DUNBAR-CMWT-FR					✗																					
	DUNBAR-CHWT-FR					✗																					
Specialty Tubing	DUNBAR-FK150	2:1	150	-55 ~ 150	600	✓	✗	E19303	AS23053/18 C2																		
	DUNBAR-1675		175	-55 ~ 175		✓	✗		AS23053/8																		
	DUNBAR-CRFR	2:1	135	-70 ~ 121		✓	✗		✗	AS23053/1																	
	DUNBAR-DRET			-75 ~ 120		✓	✗		✗	AS23053/16																	
	DUNBAR-DR150			-75 ~ 150		✓	✗		✗																		
	DUNBAR-V200			100		-40 ~ 200	✓		✗	✗	AS23053/13																

**Certifications:**

Rev. March 2017



ISO 9001:2008  
AS9100 Rev C Registered



Underwriters Laboratories Inc.  
TUV (R86603)



RoHS2



ABS  
Certificate of Type Approval



DNV  
Type Approval Certificate



1302 Champion Circle  
Carrollton, TX 75006

Tel: (469) 568-0800  
Fax: (469) 568-0808



# Heat Shrinkable Tubing

www.hstubing.com

Type	Product	Shrink Ratio	Recovery Temp. (°C)	Operating Temp. (°C)	Voltage (V)	Flame Retardant	UL File No.	MIL Spec.	Available Colors																	
									Black	White	Natural	Yellow	Red	Blue	Green	Gray	Violet	Orange	Brown	Clear	YellowGreen					
Specialty Tubing	DUNBAR-BB1K	2.5:1	120	N/A	1000	✓	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗			
	DUNBAR-BB10K				10000	✓	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	
	DUNBAR-BB25K				25000	✓	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗
	DUNBAR-BB35K				35000	✓	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗
Teflon	FEP1.3	1.3:1	210-221	-75 ~ 200	2000	✓	E64007	AS23053/11 C1	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗			
	FEP1.6	1.6:1	210-221	-75 ~ 200	2000	✓	E64007	AS23053/11 C2	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗			
	PTFE2H	2:1	350	-75 ~ 260	1400	✓	✗	AS23053/12 C1	TRANSPARENT TO OPAQUE WHITE																	
	PTFE2S					✓	AS23053/12 C2																			
	PTFE2T					✓	E103313	AS23053/12 C3																		
	PTFE2L					✓	AS23053/12 C4																			
	PTFE4	4:1	✓	✗	AS23053/12 C5																					
	ETFE1.5	1.5:1	175	-75 ~ 150	2000	✓	✗	AS23053/14	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗			
FEP Roll Cover	1.25:1	-75 ~ 200		✓		✗	✗	TRANSLUCENT																		
Double Wall Teflon	PTFE/FEP (SW)	✗	360	-75 ~ 231	✗	✓	✗	✗	TRANSLUCENT TO OPAQUE WHITE																	
	PTFE/FEP (LW)	✗			✗	✓	✗	✗																		
Non Heat Shrinkable	DUNBAR-EIT-600	N/A	✗	-55 ~ 125	600	✓	E319314	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗			
	PTFE0H	N/A	✗	-75 ~ 260	1400	✓	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗			
	PTFE0S	N/A	✗			✓	✗	MIL-DTL-221129-C	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗			
	PTFE0T	N/A	✗			✓	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗		
	PTFE0L	N/A	✗			✓	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗		
	PTFE Spiral Wrap	N/A	✗	✗	✓	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗				
	Convolutd PTFE	N/A	✗	-67 ~ 260	✗	✓	✗	AS81914/1	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗			
	Convolutd PTFE	N/A	✗		✗	✓	✗	AS81914/2	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗			
	Convolutd FEP	N/A	✗	-75 ~ 205	✗	✓	✗	AS81914/3	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗			
	Convolutd FEP	N/A	✗		✗	✓	✗	AS81914/4	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗			
	Convolutd FEP	N/A	✗		✗	✓	✗	AS81914/5	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗			
	Convolutd ETFE	N/A	✗		-67 ~ 150	✗	✓	✗	AS81914/6	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗		

**Certifications:**

Rev. March 2017



ISO 9001:2008  
AS9100 Rev C Registered



Underwriters Laboratories Inc.  
TUV (R86603)



RoHS2



ABS  
Certificate of Type Approval



DNV  
Type Approval Certificate



1302 Champion Circle  
Carrollton, TX 75006

Tel: (469) 568-0800  
Fax: (469) 568-0808