Paraffinic Base Oil

Crystal 70^{Clear} is a high quality, environmentally friendly, hydrotreated, highly re-refined mineral oil. Exceeds industry standards for base oil stocks being utilized in construction, grease, machinery and production fuilds, explosives and lowering blending costs other compounding requirements.

Physical Properties Test Method Typical Viscosity, cSt @ 100°C ASTM D4455 3.0 Viscosity, cSt @ 40°C ASTM D4455 12.7 Viscosity Index ASTM D2270 94 Specific Gravity, API @ 60°F **ASTM D4052** 0.849 Pounds per Gallon @20°C ASTM D4052 7.50 Flash Point, °C (°F) ASTM D92 196 (384) Color **ASTM D1500** < 0.5 Pour Point, °C **ASTM D5949** - 21°C Polycyclic Aromatics, wt % IP346 <3.0 **ASTM D 1500** L 0.5 Color Appearance Visual Clear & Bright Sulfur Content (mg/kg) **ASTM D4294** <300

Refer to the Safety Data Sheet prior to use.

This warranty and guarantee are expressly in lieu of all others, express or implied, including any implied warranty of merchantability or fitness for a particular purpose and may not be extended by representatives or any persons, written sales information, or drawing in any manner whatsoever. While the manufacturer recommends uses for the product based on tests believed reliable, no warranties, express or implied, or guarantee can be given as to particular methods of use or application, nor can performance be warranted, expressly or impliedly, or guaranteed under special conditions. Distributors, salespersons or company representatives are not authorized to extend or vary any warranties or guarantees beyond those outlined herein nor may the manufacturer's or seller's, limitation of liability be waived or altered in any manner whatsoever. Values shown above are representative of current production and may vary within modest ranges

The information in this document relates only the named product. The user is solely responsible for all determination regarding any use and any process.

Production Sites: Two US locations