

VT Asphalt Extender

Asphalt^{EXT} is a high quality, highly refined from re-refining waste oils. Exceeds industry standards for VTAEs being utilized in construction paving and roofing binders, temperature enhancers, production fuels, higher viscosity lubricants, and other compounding requirements.

Physical Properties	Test Method	Typical
Viscosity, cSt @ 100°C	ASTM D455	80
Pounds per Gallon	Conversion	7.85
Gravity, API @ 60°F	ASTM D4042	18.6
Flash Point, COC, °C (F)	ASTM D92	520 (968)
Specific Gravity	ASTM D4042	0.9430
Appearance	Visual	black

Refer to the Safety Data Sheet prior to use.

This warranty and guarantee are expressly in lieu of all others, express or implied, including any implied warranty of merchantability or fitness for a particular purpose and may not be extended by representatives or any persons, written sales information, or drawing in any manner whatsoever. While the manufacturer recommends uses for the product based on tests believed reliable, no warranties, express or implied, or guarantee can be given as to particular methods of use or application, nor can performance be warranted, expressly or impliedly, or guaranteed under special conditions. Distributors, salespersons or company representatives are not authorized to extend or vary any warranties or guarantees beyond those outlined herein nor may the manufacturer's or seller's, limitation of liability be waived or altered in any manner whatsoever.

The information in this document relates only the named product. The user is solely responsible for all determination regarding any use and any process.

Production Sites: United States