

BRISTOL LS^{White}

Paraffinic Fuel Oil

Bristol LS^{White} is a high quality, environmentally friendly, hydrotreated, light color and low odor, highly re-refined petroleum distillate derived from contaminated waste oil resources. Exceeds industry standards for fuel oil stocks being utilized in construction, grease, machinery and production fluids, explosives and other compounding requirements.

Physical Properties	Test Method	Typical
Viscosity, SUS	Calculated	34
Gravity, API @ 60°F	ASTM D5057	>36.0
Flash Point, PMCC °F	ASTM D93	Minimum: >100 Typical: 170
Color	ASTM D1500	<0.5
Heat Content, BTU / lb.	ASTM D 1533	>18000
Appearance		Clear, No sediment, No free water
Total Metals - others (wt%)	ASTM 5185-09	<50
Sulfur Content (wt%)	ASTM 5185-09	<.05

Refer to the Safety Data Sheet prior to use.

This warranty and guarantee are expressly in lieu of all others, express or implied, including any implied warranty of merchantability or fitness for a particular purpose and may not be extended by representatives or any persons, written sales information, or drawing in any manner whatsoever. While the manufacturer recommends uses for the product based on tests believed reliable, no warranties, express or implied, or guarantee can be given as to particular methods of use or application, nor can performance be warranted, expressly or impliedly, or guaranteed under special conditions. Distributors, salespersons or company representatives are not authorized to extend or vary any warranties or guarantees beyond those outlined herein nor may the manufacturer's or seller's, limitation of liability be waived or altered in any manner whatsoever.

The information in this document relates only the named product. The user is solely responsible for all determination regarding any use and any process.

Production Sites: United States