

CONTENTS





UL&EN FIRE DOOR



MN -DSF-1

MONU fire door meets and exceeds UL/EN/BS standard, complying these criteria as UL 10B, UL10C,, EN-1634-1, BS-476-22. Doors are with UL/EN certificate.UL/EN/BS 20 minutes up to 3 hours fire rating Available with fire proof glazing and top light Widely applied to Industrial, Commercial, Chemical, Nuclear and Medical Industries.

Frame

Various kinds design of frame profiles are available, suitable for different installation environment.

Hardware Available

UL/Non-UL panic bar, external level trim, door closer, hinge, flush bolt, vision glass, magnetic door holder, coordinator, smoke seal, handle lock, automatic door bottom seal etc.

Option

Door and frame surface finish could be customized according to RAL color chart.

UL&EN STEEL FIRE DOOR 📆 🤇 E











MN -DSF-2

Certified with UL/EN/BS

20 minutes up to 3 hours fire rating

Single Door customized max size: 4*8 feet

Available with fire-proof window

Certified with UL/EN/BS

20 minutes up to 3 hours fire rating

Double Door customized max size: 8*8 feet

Available with fire-proof window



MN -SSF-1

UL&EN STEEL FIRE DOOR 📆 🤇 E 😑



MN -SSF-2

Certified with UL/EN/BS

20 minutes up to 3 hours fire rating

Single Door customized max size: 4*8 feet

Available with press bar



Certified with UL/EN/BS

Available with handle lock

20 minutes up to 3 hours fire rating

Single Door customized max Size: 4*8 feet

UL&EN STEEL FIRE DOOR 📆 (🗲 🖼



MN -DSF-3

Certified with UL/EN/BS

20 minutes up to 3 hours fire rating

Double Door customized Max Size: 8*8 feet

Available with fire proof louver

Available with handle lock



20 minutes up to 3 hours fire rating

Single Door customized Max Size: 4*8 feet

Available with louver

Available with handle lock



MN -SSF-4

FIRE DOOR CROSS SECTION VIEW . ♠ C € 😁

STEEL DOOR SKIN:

16GA(1.5mm),18GA(1.1mm),20GA(0.9mm)

A40 Galvanized Or Cold-rolled Steel Skins Construction is 1-3/4 " (45mm)Thickness

Hinge, closer, lock and strike plate reinforcements shall be provided.

Hinge reinforcement: 10GA(3.5mm)

Closer reinforcement:12GA(2.5mm)

Lock reinforcement:16GA(1.5mm)

Strike plate reinforcement:16GA(1.5mm)

The top,bottom and side closures are fabricated from 16GA(1.5mm) thick channel shaped steel sections welded to the front and back door skins.


Flush top channel:16GA(1.5mm)

Laser-welded side-seamed edge.

Widths up to and including 4 ' 0 "


Heights up to and including 8 ' 0 "

Available with polystyrene core or honeycomb core.




FIRE DOOR FRAME CONSTRUCTION VIEW ☼ C € 😁

MASONRY/STUD CONSTRUCTION FRAME



DRYWALL FRAME




Compression Anchor

Snap in sill Anchor

| Jamb Depth | 4-3/4 " | 5-7/8 " | 6-1/4 " | 6-5/8 " | 7-1/4 " | 7-3/4 " | 8-1/4 " |
|----------------|---------|---------|---------|---------|---------|---------|---------|
| Throat Opening | 3-3/4 " | 4-7/8 " | 5-1/4 * | 5-5/8 " | 6-1/4 " | 6-3/4 * | 7-1/4 * |

Frame Profiles




MONUsteel fire doors conform or exceed SDI/HMMA industrial standards, fire tested and certified with UL,Intertek/WH from 20Min up to 3hrs fire rating,complying criteria as NFPA252,UBC7-2,UL10(b),UL10(c)

OPEN DIRECTION INDICATOR

INTERIOR DOOR

The direction of opening the door can be based on customer need







INTERIOR DOOR



MN-1





INTERIOR DOOR





MN-4 MN-5





MN-6 MN-7

PAINTED WOODEN DOOR













DOOR ARCHITRAVE TYPE













MNIC-B



MNIC-D

MNIC-E

MNIC-F

POPULAR STYLE









MN-25

HOSPITAL DOOR SERIES







STEEL WARD DOOR








INDUSTRIAL CLEAN ROOM DOOR



INDUSTRIAL CLEAN ROOM DOOR





ROLLER SHUTTER DOOR





ROLLER SHUTTER DOOR



PANIC EXIT DEVICES SERIES



OTHER HARDWARE

