

SCHOCK DESIGN

SCHOCKINTERIORS.COM

INFO@SCHOCKINTERIORS.COM

317-696-2502

Project Name

Enter address here

Owner

Project number	Project Number
Date	Issue Date


CLIENT APPROVAL

SIGNATURE: _____
DATE: 5/9/2025 1:13:26 PM

A200

Scale 1/4" = 1'-0"

Elevations



1 South
A200 1/4" = 1'-0"

GENERAL FLOOR PLAN NOTES:

1. ALL INTERIOR WALLS ARE 2X-1 OR 2X-2, AS SHOWN. EXTERIOR WALLS ARE 2X1 OR 2X-2, W/ ONE LAYER OF 1/2" SHEATHING. ALIGN EXTERIOR OF SHEATHING WITH FOUNDATION WALL. ALL ANGLED WALLS ARE 15 DEGREES FROM ADJACENT WALL UNLESS OTHERWISE NOTED.
2. CONFIRM ALL HEADER HEIGHTS AND SIZES PRIOR TO START OF FRAMING. ALL OPENINGS ARE TO BE 1" FROM ADJACENT WALL UNLESS NOTED OTHERWISE.
3. VERIFY ALL TYPES AND SIZES OF WINDOW UNITS AND DOORS WITH OWNER/BUILDER. NOTIFY BUILDER OF ANY DISCREPANCIES.
4. VERIFY LOCATION, TYPES AND SIZES OF VENTS AND EXTERIOR TRIM WITH OWNER/BUILDER.
5. INSULATE HIDDEN AREAS OR ASSEMBLIES BEFORE COVERING.
6. BUILDER/LUMBER SUPPLIER SHALL SPECIFY SIZES OF DIMENSIONAL LUMBER FOR FLOOR AND ROOF SYSTEMS. NOTIFY BUILDER/LUMBER SUPPLIER IMMEDIATELY OF ANY DISCREPANCIES.
7. STEEL LINTELS OR WOOD BEARING AREAS PROPERLY SIZED, ARE TO BE PROVIDED OVER ALL OPENINGS TO SUPPORT MASONRY VENEER.
8. ALL ROOF AND WALL INTERSECTIONS SHALL BE FLASHED WITH ALUMINUM OR BETTER MATERIAL.
9. ALL BEDROOM EGRESS WINDOWS TO MEET MIN. CLEAR OPENING OF 5.1 FT2 UNLESS NOTED OTHERWISE. ONE WINDOW MINIMUM NEEDED PER BEDROOM.

NOTE
IT IS THE BUILDER/ OWNERS RESPONSIBILITY TO VERIFY THE PROPER AIR SPACE BETWEEN ALL BRICK AND WOOD WALLS WITH HOUSE WRAP. TO PREVENT WATER INFILTRATION. BUILDER/OWNER SHOULD SEEK THE ASSISTANCE OF A QUALIFIED ENGINEER FOR THE PROPER SIZING OF ALL STRUCTURAL HEADERS, RAFTERS, SUPPORT BEAMS, LAMINATED BEAMS, JOISTS, FOOTINGS, ETC. IT IS THE BUILDER/ OWNERS RESPONSIBILITY TO VERIFY ALL DIMENSIONS/DESIGN OF THESE DOCUMENTS FOR ACCURACY.