



How Pinnacle Differs from Other Brands

Traditional market competitors typically rely on mechanical clamps on breaker handles or bulky and costly apparatuses that are easily lost or misplaced when not in use. Pinnacle's devices shift away from those methods in several unique ways:

Feature	Pinnacle Safety Products	Standard Market Brands
Installation Method	Tool-free adhesives use strong industrial acrylic tape. No drilling, modifications, or additional hardware is required.	Multiple clamp-on screw devices, clamp around attachments, or permanent hardware is required.
Speed of Deployment	Guaranteed to install in under 3 minutes via a simple QR-code guided process.	Can take longer depending on matching specific clamp sizes or tightening of custom hardware.
Breaker Protection	Secures the entire hinged panel door or sets up adjacent barriers with a single device rather than clamping individual toggles.	Attaches directly to individual breaker toggles, which can cause handle stress or breakage.
Adjacent Switch Safety	Prevents the status change or accidental flipping of non-targeted circuit breakers.	Bulky individual toggle locks can crowd or accidentally trip adjacent switches during installation.
Complex Group LOTO	Naturally facilitates group LOTO by holding the device key captive inside a group box for complex configurations.	Relies heavily on separate multi-lock hasps attached directly to the single cramped point of isolation.
Removal Process	Designed as a consumable item and is easily removed cleanly using our specialized plastic, non-marring PSRT tool.	Permanent metal modifications remain, or individual clamp devices must be unscrewed manually every time.