



# Spherical Sequencer SSA1 & SSA2

## Prefabricated Designs

### Hardware Specifications AZZA Case

- 4-Dual Core Processors 2.7GHz
- 8 Channel TrueSPL-SSA1
- 12G RAM
- Installation
- Configuration
- OS Licensing
- Control Software Licensing
- 2 Year Online Class
- 2 Year Support
- TrueSPL Licensing
- Sequencing Licensing
- \*VST Packages and Licensing



### Inputs and Outputs

\*Custom Machined Panels

TrueSPL-SSA1	TrueSPL-SSA2
4-Fixed HDMI Detachable Monitors	Monitor Package Required
4-HDMI Show Ports	8-HDMI ports
4-USB C	4-USB C
4-USB A	4-USB A
8-RCA	8-RCA
4-3.5 Stereo Mini	4-3.5 Stereo Mini
1-Cat6	1-Cat6
MIDI I/O	MIDI I/O
4-XLR (optional)	4-XLR
	Firewire SPL Link
	SPIDIF
	12 Volt Link

#### Power Supply

Switch IEE Female 120v 60Hz 350w power supply

32W AC/DC enclosed switching power supply 5 Volts 4 Amps (channel 1) 12 Volts 1 Amp (channel 2) specifications: size (LxWxH) (inches): 3.9 x 3.2 x 1.4 ripple and noise (mV p-p): 80 load regulation: 0.5 percent line regulation: 0.5 percent input: 88-264vac 47-63hz 5G vibration able to withstand 300VAC surge input for 5 seconds short-circuit/overload/overvoltage protection 3-year warranty certifications: UL/cul/TUV/CE/CB for more 12 Volt power supplies. Detailed specifications: primary output voltage (VDC): 5 output current (a): 4 maximum output power (W): 32 family: supplier specialized-35 additional output voltages (VDC): 12 input voltage (VAC): 88 to 264 input frequency: 47 to 63 maximum input current (a): 0.8 output connector Type: screw terminal block number of outputs: 2 product Type: AC to DC power supply efficiency ( percent ): 79 minimum isolation voltage: 3000V operating temperature-min (CEL): -25 operating temperature-max (CEL): 70 Length (inch): 3.9 width (inch): 3.2 height (inch): 1.4 agency approvals: UL/cul/TUV/CE/CB Type: auto switching style: multiple output.

Sound Pressure Laboratory, LLC → soundpressurelabs.com  
Northern CA 707.496.7165 → Southern CA 310.701.7750

**The NAMM Show**  
April 13/15 2023 California