



AN SERIES PREMIUM WI-FI CLIENTS




Aigean Wi-Fi Clients

Wi-Fi clients are routed wireless bridges that are used as the primary connection interface for communicating with external, land-based wireless networks. Aigean's Wi-Fi clients are designed to improve signal strength and quality when connecting to marina, hotel, home, and business networks.

Hardwire any Aigean Wi-Fi Client to an existing local area network or use Aigean Marine Access Points to provide local wireless coverage for any vessel, big or small.

Premium Wi-Fi Clients are the most powerful and capable of the Aigean family of wireless clients. With generally higher power CPUs and radios, they also come standard with Comrod antennas, for maximum performance.

AN Series Highlights



Fast CPUs



High-Gain Antennas



High Throughput



Gigabit Ethernet*



Dual Band*



MIMO Capable*



aigean.com
754-223-2240 / info@aigean.com



AN Series Models



AN-2000

Band	2.4GHz
CPU	400MHz
Radio	800mW
Ethernet	10/100
Antenna	4' Comrod



AN-700

Band	2.4/5 GHz
CPU	600MHz
Radio	500mW
Ethernet	10/100
Antenna	4' Comrod



AN-7000

Band	2.4/5GHz
CPU	600MHz
Radio	1000mW
Ethernet	10/100/1000
Antenna	2x 4' Comrod

Package Contents

- AN-7000 device
- 2x Comrod marine antenna *4 ft / 121 cm*
- 2x Secondary rubber antenna *5 in / 12 cm*
- 2x LMR-400 low loss cable *25 ft / 762 cm*
- 2x LMR-400 N-Male connector
- Power cable *6ft / 182 cm*
- Quick Start Guide
- Warranty Information



Compatibility

Modern Web Browsers

Chrome, Safari, Mozilla Firefox, Opera, Microsoft Internet Explorer 10 and newer, Microsoft Edge, Safari, and many others



Wi-Fi Networks

All standard 802.11a/b/g/n Wi-Fi networks:

- Unsecured (Open)
- Standard encryption (WEP, WPA, WPA2)
- Hidden Networks (Masked SSID)



aigean.com

754-223-2240 / info@aigean.com



* Available only on some models.

Disclaimer: All products, product specifications and data are subject to change without notice to improve reliability, function, design or otherwise.

Performance Notice: Actual performance may vary. The standard transmission rates described are the physical data rates and actual data throughput will be lower. Factors affecting signal strength and quality include localized radio frequency interference, obstacles impeding clear line-of-sight, antenna positioning, access point hardware/configuration, and atmospheric conditions, among many others.

Regulatory Compliance: The specified transmit (Tx) power is the maximum output power the radio hardware is capable of producing. The device's firmware controls power limits based on established country-specific regulations to ensure safe and legal operation around the world. All devices are defaulted by the factory to operate in the United States of America, in compliance with all applicable FCC rules and regulations.

August 2017