

## **Content List:**

-TDS for CB200J

-TDS for CB300J

-TDS for CB400J

-TDS for CB500J



# Product Technical Specification 200 Joule/M<sup>2</sup>

Product Type	Core board paper
Available width	Reels from 550 upto 225mm or ribbons slitted from 70mm upto 250mm as per customer red
Roll Diameter	From 900 mm upto 1300 mm
Availlable Core Diameter	3 inch
Goods packaging	Wrapped on pallets

PLYBOND (J/M²)	200
WEIGHT(G/M²)	200 to 550 gsm
Caliber mm	0.58 to 0.60
EXPECTED BULK RANGE (CM³/G)	
EXPECTED MOISTURE (%)	5-7 %
BURSTindex (KPA/G)	1.0



# Product Technical Specification 300 Joule/M<sup>2</sup>

Product Type	Core board paper
Available width	Reels from 550 upto 225mm or ribbons slitted from 70mm upto 250mm as per customer red
Roll Diameter	From 900 mm upto 1300 mm
Availlable Core Diameter	3 inch
Goods packaging	Wrapped on pallets

PLYBOND (J/M²)	300
WEIGHT(G/M²)	200 to 550 gsm
Caliber mm	0.58 to 0.60
EXPECTED BULK RANGE (CM³/G)	1.25 - 1.50
EXPECTED MOISTURE (%)	5-7 %
BURSTindex (KPA/G)	1.1



# Product Technical Specification 400 Joule/M<sup>2</sup>

Product Type	Core board paper
Available width	Reels from 550 upto 225mm or ribbons slitted from 70mm upto 250mm as per customer red
Roll Diameter	From 900 mm upto 1300 mm
Availlable Core Diameter	3 inch
Goods packaging	Wrapped on pallets

PLYBOND (J/M²)	400
WEIGHT(G/M²)	200 to 550 gsm
Caliber mm	0.58 to 0.60
EXPECTED BULK RANGE (CM³/G)	1.25 - 1.50
EXPECTED MOISTURE (%)	5-7 %
BURSTindex (KPA/G)	1.4



# Product Technical Specification 500 Joule/M<sup>2</sup>

Product Type	Core board paper
Available width	Reels from 550 upto 225mm or ribbons slitted from 70mm upto 250mm as per customer red
Roll Diameter	From 900 mm upto 1300 mm
Availlable Core Diameter	3 inch
Goods packaging	Wrapped on pallets

PLYBOND (J/M²)	500
WEIGHT(G/M²)	200 to 550 gsm
Caliber mm	0.58 to 0.60
EXPECTED BULK RANGE (CM³/G)	1.25 - 1.50
EXPECTED MOISTURE (%)	5-7 %
BURSTindex (KPA/G)	1.7