







Sample Room

NIRO Report – Geometry, Positions & Treatments

Table of Contents	Page
Layout	<u>2</u>
Treatment Recommendation	<u>3</u>
Reflection Analysis & Diffusor Recommendation	<u>5</u>
Low-frequency Response	<u>6</u>
Temporal Decay	<u>7</u>
Pressure Distribution	<u>9</u>




Listening positions:

- Mix 1 Pos.: X: x.xx, Y: x.xx, Z: x.xx [m]
- Mix 2 Pos.: X: x.xx, Y: x.xx, Z: x.xx [m]
- Producer Pos.: X: x.xx, Y: x.xx, Z: x.xx [m]

Loudspeaker positions:


- Mains: X: ± x.xx, Y: x.xx, Z: x.xx [m] | Polarity: (+, +)

① Positions
Listener and speaker positions





③ Floorplan View

② Front View





④ Section View








Finished face of treatment: XXX
Plate thickness (plywood): x.xx [mm] | x.xx”
Hole diameter/spacing: x.xx [mm] holes spaced x.xx [mm] on-center
Porous material type and thickness: XXX - x.xx [mm]
Flow resistivity of porous material: x.xx [rayls/m]
Air gap depth: x.xx [mm]
Total treatment depth: x.xx [mm]’
Surface Area: x.xx [m²]




① Perforated Resonator





Finished face of treatment: XXX
Plate thickness (plywood): x.xx [mm] | x.xx”
Hole diameter/spacing: x.xx [mm] holes spaced x.xx [mm] on-center
Porous material type and thickness: XXX - x.xx [mm]
Flow resistivity of porous material: x.xx [rayls/m]
Total treatment depth: x.xx [mm]’
Surface Area: x.xx [m²]




② Perforated Resonator





Finished face of treatment: XXX
Plate thickness (plywood): x.xx [mm] | x.xx”
Hole diameter/spacing: x.xx [mm] holes spaced x.xx [mm] on-center
Porous material type and thickness: XXX - x.xx [mm]
Flow resistivity of porous material: x.xx [rayls/m]
Air gap depth: x.xx [mm]
Total treatment depth: x.xx [mm]’
Surface Area: x.xx [m²]




③ Perforated Resonator



Finished face of treatment: XXX
Plate thickness (plywood): x.xx [mm] | x.xx”
Hole diameter/spacing: x.xx [mm] holes spaced x.xx [mm] on-center
Porous material type and thickness: XXX - x.xx [mm]
Flow resistivity of porous material: x.xx [rayls/m]
Total treatment depth: x.xx [mm]’
Surface Area: x.xx [m²]



④ Perforated Resonator



Optional fabric covering

Perforated plate

Porous material

Air gap

Rigid backing

Finished face of treatment: XXX

Plate thickness (plywood): x.xx [mm] | x.xx"

Hole diameter/spacing: x.xx [mm] holes spaced x.xx [mm] on-center

Porous material type and thickness: XXX - x.xx [mm]


Flow resistivity of porous material: x.xx [rayls/m]

Air gap depth: x.xx [mm]


Total treatment depth: x.xx [mm]'

Surface Area: x.xx [m²]


Absorption Coefficient (α)



— Diffuse Incidence (0° - 78°)
- - Normal Incidence
... Resonance at 250.0 Hz



⑤ Perforated Resonator



Fabric covering

Porous material

Rigid backing

Finished face of treatment: XXX


Porous material type and thickness: XXX - x.xx [mm]

Flow resistivity of porous material: x.xx [rayls/m]


Total treatment depth: x.xx [mm]'

Surface Area: x.xx [m²]


Absorption Coefficient (α)



— Diffuse Incidence (0° - 78°)
- - Normal Incidence
... Resonance at 1895.0 Hz



⑥ Fabric Panel



Fabric covering

Porous material

Air gap

Rigid backing

Finished face of treatment: XXX

Porous material type and thickness: XXX - x.xx [mm]


Flow resistivity of porous material: x.xx [rayls/m]

Air gap depth: x.xx [mm]


Total treatment depth: x.xx [mm]'

Surface Area: x.xx [m²]


Absorption Coefficient (α)



— Diffuse Incidence (0° - 78°)
- - Normal Incidence



⑦ Fabric Panel



Insulation

Rigid backing


Model:

Units:


Total width:

Height:


Depth:




Random Incidence Performance Data



... Absorption
— Diffusion
- - Scattering



⑧ Diffusor






SAMPLE DOCUMENT

Treatment Recommendation


www.rediacoustics.com

[Learn more](#)


4






① Specular Reflections
1st and 2nd order




② Reflection-Free Zone
Frequency dependent reflectogram & RFZ Depth



③ Reverberation Time




① Low-frequency Response
20 to 200 Hz




① Low-frequency Temporal Decay & Reverberation Time

Without treatments at Mix 1 Position




① Low-frequency Temporal Decay & Reverberation Time
With treaments at Mix 1 Position



① Arcturus (Mains)

Without treatments



② Arcturus (Mains)

With treatments