

SUPPLEMENT TO

Parts Manuals No. D-363 and No. D-391

IMPORTANT

BE SURE TO INSERT IN ABOVE MANUALS FOR FUTURE REFERENCE

MANUAL NO. D-363

PAGE 5

Old Instructions shown in Manual

The following Lubricants have been approved as satisfactory:

Chassis Lubricants—Summer (any good standard brand).

Outboard Motor Gear Box Grease.

Or any similar lubricant of equal water repellent characteristics.

Replaced by New Instructions

The following Lubricants have been approved as satisfactory:

Chassis Lubricant—Texaco Multifax #2 water repellent grease or any good brand of **short fiber water repellent grease**.

PAGE 10

Old Instructions shown in Manual

7. Remove $\frac{1}{8}$ Pipe Plugs (B) and fill both ends with a good grade of outboard gear box lubricant—See Lubrication Instructions.

Replaced by New Instructions

7. Remove $\frac{1}{8}$ Pipe Plugs (B) and fill both ends with a good grade of Texaco Multifax #2 water repellent grease or any good brand of **short fiber water repellent grease**. — See Lubrication Instructions.

MANUAL NO. D-391

PAGE 5

Old Instructions shown in Manual

10. Be sure to fill both ends of roller with a good grade of outboard motor gear box grease, through filler plugs (B). Repeat every 25 hours of operation.

Replaced by New Instructions

10. Be sure to fill both ends of roller through filler plugs (B) with Texaco Multifax #2 water repellent grease or any good brand **short fiber water repellent grease**. Repeat every 25 hours of operation.

CAUTION—DO NOT APPLY GREASE UNDER PRESSURE

Worthington Mower Company

STROUDSBURG, PENNSYLVANIA