

Motor: Rear Hub Motor, BAFANG, 750W

Throttle: Throttle on Demand

Pedal Sensor: Torque / Cadence

Pedal Assist: 5 PAS Levels

Speed: 20 MPH

Display: C010 BAFANG E-system TFT Display (Find My, Sensor Selection Function)

Certification: UL2849

Shifter: Shimano 8 Speed

Rear Derailleur: Shimano 8 Speed

Cassette: 8 Speed, 11-32T

Chain: 8 Speed

Crankset: 46T Chainring

Battery: 48V 14Ah

Cells: LG

Charging Time: About 5 H to a Full Charge

Range: Up to 60 miles

Lighting: Front Light / Rear Light / Integrated Rear Turn Lights

Horn: Yes

Fender: Front And Rear Fender

Rack: Rear MIK Rack

Frame: 6061 Single-Butted Aluminum Alloy Frame

Fork: 6061 Single-Butted Aluminum Alloy Fork

Dimensions: 1809 × 685 × 1120 mm

Weight: 56.6 lbs / 25.22 kg

Payload Capacity: 320 lbs / 145 kg

Kickstand: Aluminum Alloy Kickstand

Pedals: PP

Brake: Tektro Hydraulic Disc 203 mm Brakes

Tires: 27.5" × 2.1

Rims: Double Wall Aluminum Alloy

Spokes: Black Stainless

Tubes: Butyl Rubber

Saddle: AIMA Enlarged Comfort Saddle

Seatpost: Aluminium Alloy 30.9mm (Suspension)

Seat Clamp: 34.9mm Quick Release

Stem: Threadless (Adjustable)

Handlebars: Aluminium Alloy 680mm

Grips: Ergonomic Comfort

Headset: Sealed Bearing Headset