

VELOTRIC



Ride like the wind.

VELOTRIC BREEZE¹

- ✓ **Easy Handling:**
 - Lightweight at 48 Lbs
 - Precise & Smooth Steering
 - No Ghost-Pedaling
- ✓ **Velotric ComfortMax™**
 - Upright Riding Position
 - Ergonomic Seat & Grips
 - 380 Mm Low Step-Through
- ✓ **Go Strong, Go Far, Go Free:**
 - 750 W (Peak 1150 W)
 - 70 Miles Range
 - SensorSwap™

SIZE
Step-Through Frame
Regular: 4'11" – 5'8"
Large: 5'6" – 6'4"



Ocean Mist



Slate Gray



Violet Haze



Satin White



Classic Scarlet



 **Power**
750 W (Peak 1150 W)
65 Nm

 **Max Range**
70 Miles

 **Brake**
SHIMANO
Hydraulic
Disc Brake

 **Grips**
Durable
Ergonomic
Grips, Lockable

 **Drivetrain**
SHIMANO
8-Speed

 **Pedal Assist**
3 Riding Modes ×
5 PAS Levels

 **Class 1/2/3**
20 Mph Default
(Speed Limit 12–28Mph,
Removable Throttle)

 **Phone App**
IOS, Android

 **Security**
Apple Find My™

 **Waterproof Level**
IPX6
(Battery IPX7)

VELOTRIC BREEZE 1 SPECIFICATIONS

SIZE GUIDE		Bike Size	Regular/Large			
		Color	Violet Haze, Satin White, Ocean Mist, Classic Scarlet, Slate Gray			
		User Height Range	Regular: 4'11"–5'8" Large: 5'6"–6'4"			
FRAMESET		Frame	Triple-Butted Aluminum Alloy			
		Fork	Aluminum Alloy			
ELECTRONICS		Motor	750 W, 1150 W Peak, 65 Nm			
		Battery	48 V, 627 Wh, IPX7, Certificated by UL 2271			
		Cell	18650 Cell, Certified by UL 2580			
		Charger	48 V, 3A Fast Charger			
		SensorSwap™	Torque/Cadence			
		Display	3.5" Full Color, High Brightness, Bluetooth			
		USB Port	USB Type-C			
		Throttle	Trigger-Control, Removable			
		Pedal Assist	3 Riding Modes × 5 PAS Levels			
		Front Light	400 Lm High-Output Integrated LED, Adjustable Angle			
		Rear Light	Brake Highlight, Turn Signal			
		Water Resistant	IPX6			
SPEED & RANGE		Max Speed (Default)	20 Mph			
		Max Speed Adjustable Range	12–28 Mph			
		Class	1/2/3			
		Throttle Range	55 Miles			
		Pedal Assist Range	70 Miles			
DRIVETRAIN		Chainrings	46 T, Narrow Wide Chainring			
		Crankset	Aluminum Alloy, 170 Mm			
		Cassette	8-Speed			
		Rear Derailleur	SHIMANO 8-Speed			
		Shift Lever	SHIMANO 8-Speed			
		Chain	KMC 8-Speed			
BRAKE	Brake	Tektro Hydraulic Disc Brake		WHEEL	Rims	Double-Wall Aluminum Alloy
	Rotors	180 Mm Front and Rear			Front Hub	NOVATEC Aluminum Alloy, 15 × 110 Mm Thru-Axle
	Brake Levers	Aluminum Alloy, with Power Cutoff			Tire	KENDA 27.5 × 2.2" Ebike Puncture Resistant Tires
COCKPIT		Handlebar	Aluminum Alloy, Φ 31.8 Mm, 660 Mm(R)/680 Mm(L)			
		Grips	Durable Ergonomic Grips, Lockable			
		Stem	Adjustable, Aluminum Alloy			
		Saddle	Velotric Comfortable & Ergonomic Seat			
		Seatpost	Aluminum alloy, Φ 30.9 Mm, 350 Mm			
		Clamp	Aluminum Alloy, Quick Release			
SUPPORTS		Pedals	Plastic			
		Kickstand	Aluminum Alloy, Included, Rear Mount			
WEIGHT & LOAD		Bike Weight	48 Lbs			
		Rear Rack Load Capacity	66 Lbs			
		Max Bike Load Capacity	330 Lbs			
CERTIFICATION		UL Certification	UL 2849			
		ISO Standard	ISO 4210			