

VELOTRIC



The Next-Generation Folding Ebike.

VELOTRIC
FOLD 1 PLUS

- ✓ Top-Tier Riding Experience:

 - SensorSwap™
 - Premium Torque Sensor
 - 3 Riding Modes × 5 PAS Levels
- ✓ Velotric ComfortMax™

 - Upright Riding Position
 - 390 Mm Low Step-Through
 - Suspension Fork + 3.0-Inch Tire
- ✓ All-Rounded Performance:

 - 68 Miles Range
 - 750 W, 75 Nm Torque Motor
 - 450 Lbs Payload
- ✓ Unfold a New Era of Folding Ebikes!

SIZE

One Size:
4'9"-6'5"



Electric Blue



Stone Gray



Pearl White



Mango



Power
750 W
75 Nm



Max Range
68 Miles



Brake
Hydraulic
Disc Brake



Fork
Coil Suspension
60 Mm Travel with
Lock-Out



Drivetrain
SHIMANO
7-Speed

Pedal Assist
3 Riding Modes ×
5 PAS Levels

Class 1/2/3
20 Mph Default
(Speed Limit 12–28 Mph,
Removable Throttle)

Phone App
IOS, Android

Security
Apple Find My™

Waterproof Level
IPX6
(Battery IPX7)

VELOTRIC FOLD¹ PLUS SPECIFICATIONS

Building A Better Ride.



| | | | | | | |
|---------------|--------------|-----------------------------------|---------|---|------------------|--|
| SIZE GUIDE | | Bike Size | | One Size | | |
| | | Color | | Electric Blue/Pearl White/Stone Gray/Mango | | |
| | | Folding Size | | 37.8" L × 19.7" W × 33.5" H | | |
| | | User Height Range | | 4'9"–6'5" | | |
| FRAMESET | | Frame | | Aluminum Alloy | | |
| | | Fork | | Coil Suspension 60 Mm Travel with Lock-Out | | |
| ELECTRONICS | | Motor | | 750 W, 75 Nm | | |
| | | Battery | | 48 V, 13 Ah, IPX7, Certificated by UL 2271 | | |
| | | Cell | | 18650 Cell, Certificated by UL 2580 | | |
| | | Charger | | 48 V, 2A Fast Charger | | |
| | | SensorSwap™ | | Torque/Cadence | | |
| | | Display | | 3.5" Full Color, High Brightness, Bluetooth, Adjustable Angle | | |
| | | USB Port | | USB Type-C | | |
| | | Security | | Apple Find My™ | | |
| | | Throttle | | Thumb-Control, Removable | | |
| | | Pedal Assist | | 3 Riding Modes × 5 PAS Levels | | |
| | | Walk Mode | | 2.9 Mph | | |
| | | Front Light | | 400 Lm High-Output Integrated LED, Adjustable Angle | | |
| | | Rear Light | | Brake Highlight, Turn Signal | | |
| | | Water Resistant | | IPX6 | | |
| SPEED & RANGE | | Max Speed (Default) | | 20 Mph | | |
| | | Max Speed Adjustable Range | | 12–28 Mph | | |
| | | Class | | 1/2/3 | | |
| | | Throttle Range | | 45 Miles | | |
| | | Pedal Assist Range | | 68 Miles | | |
| DRIVETRAIN | | Chainrings | | 52 T | | |
| | | Crankset | | Aluminum Alloy, 170 Mm | | |
| | | Cassette | | 7-Speed | | |
| | | Rear Derailleur | | SHIMANO 7-Speed | | |
| | | Shift Lever | | SHIMANO 7-Speed | | |
| | | Chain | | 7-Speed | | |
| BRAKE | Brake | Hydraulic Disc Brake | | WHEEL | Rims | Single-Wall Aluminum Alloy |
| | Rotors | 180 Mm Front and Rear | | | Front Hub | Aluminum Alloy, Nuted |
| | Brake Levers | Aluminum Alloy, with Power Cutoff | | | Tire | 20 × 3.0" Ebike Puncture Resistant Tires |
| COCKPIT | | Handlebar | | Aluminum Alloy, Φ 31.8 Mm, 660 Mm(R)/680 Mm(L) | | |
| | | Grips | | Durable Ergonomic Grips, Lockable | | |
| | | Saddle | | Velotric Comfortable & Ergonomic Seat | | |
| | | Seatpost | | Aluminum Alloy, Φ 30.9 Mm, 350 Mm | | |
| | | Clamp | | Aluminum Alloy, Quick Release | | |
| SUPPORTS | | Fenders | | Steel, Front, and Rear, Full Coverage | | |
| | | Rear Rack | | Aluminum Alloy, Integrated with Frame | | |
| | | Pedals | | Plastic, Foldable | | |
| | | Kickstand | | Aluminum Alloy, Included, Rear Mount | | |
| WEIGHT & LOAD | | Bike Weight | 63 Lbs | CERTIFICATION | UL Certification | UL 2849 |
| | | Rear Rack Load Capacity | 120 Lbs | | ISO Standard | ISO 4210 |
| | | Max Bike Load Capacity | 450 Lbs | | | |