

HS-FINISH AD TECHNICAL DATA SHEET

TDS SHEET I HYDRA S

Product Specification

Product Description : HS-Finish Aid

HS-Finish Aid is a concrete finishing aid that can be used in-place of water during the screeding, panning,or finishing process to increase workability, enhance the surface strength and reduce permeability making a higher performing surface with less work.

Benefits:

Densifies the Surface Helps fight Wind, Sunlight, low humidity, Cold Increases Workability Makes Shake-On Hardeners easier to install Replaces Water Reduces Permeability Reduces Moisture Vapor Transmission Reduces Curling / Shrinkage

Usage:

PARKING GARAGES

EXTERIOR PAVEMENTS

STRUCTURAL WALL COLUMNS

FOOTINGS / MASS FOOTINGS

INFRASTRUCTURE - SLAB ON DECK & SLAB ON GRADE

Application:	Spray on concrete while placing & finishing.
Appearance:	Odorless, transparent liquid
VOC:	O g/L
Shelf life:	1 year after opening
Solvent:	Water based

Packaging Specification

Product #	Shipping Wt.	Container
3-FA50-1	10 lbs	1 GAL
3-FA50-5	45 lbs	5 GAL
3-FA50-55	490 lbs	55 GAL
3-FA50-275	2,200 lbs	275 GAL

Coverage:

Screeding & Floating - 600 - 1000 sf per gallon

Finishing - 800 - 1500 sf per gallon



Mixing & Application:

- Can be applied anytime during the pre-finish and finishing stages, key for maximum performance is to immediately agitate (screed, float, finish, etc) to work into surface.
- Apply based on coverage rates above, and as needed during finishing, do not apply over 300 sf per gallon per application.

TDS SHEET | HYDRA S

Storage & Shelf Life:

Should be kept in the original container, with the lid fastened tightly. Store in a cool, dry place raised off the floor. Keep in a temperature range of 40–100°F or 4–38°C and DO NOT allow FREEZE. Seal container again after each use. Keep out of reach of children. Do not mix with other chemicals.

Cleanup:

Any solution that cannot be reclaimed and reused should be cleaned with water and disposed of according to local, state and federal regulations.

Phy	sical	Pro	perties:
гну	Sicai	L L D	heines.

Appearance	Odorless clear liquid
VOC Content	0 g/l – free
Freeze point	32°F - 0°C

VOC Compliance:

VOC compliant with national, state and district regulations at 0 g/L.

WARNING & SAFETY INFORMATION:

KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY. BEFORE USING THIS PRODUCT PLEASE READ THE SAFETY DATA SHEET IN ITS ENTIRETY! Safety Data Sheets (SDS) can be provided by calling 833-585-ADEO (2336).

WARRANTY INFORMATION:

The information contained herein is believed to be reliable. This information is based on laboratory testing and results. Because of variations in methods, conditions and equipment, each user must test this product to make a judgment of performance. Applicator is responsible for testing material for effectiveness and performance. Manufacturer obligation is limited to the refund of purchase price or replacement of material if proven to be defective. Claims must be made in writing and received within one year from date of product sale to original buyer.