



Universal Industries

P1300

BUCKET ELEVATORS

up to 1,382 ft³/h
(38.7 m³/h)
/1,110 BPH

SPECIALLY DESIGNED TO PREVENT SPLITS, CRACKS AND SCARS THAT LOWER PRODUCT VALUE



(Guards removed for photos only)

SPECIFICATIONS

Model	P1300-60	P1300-90
Capacity - Free Flowing Material @ 85% Bucket fill	765 BPH 952 ft ³ /h 27 m ³ /h	1,110 BPH 1,382 ft ³ /h 39 m ³ /h
Short TPH @ 50lbs/ft ³	23.8 TPH	34.6 TPH
Short TPH @ 75lbs/ft ³	37.5 TPH	51.8 TPH
Chain Speed	60 FPM	90 FPM
Headshaft RPM	16.9 RPM	24.4 RPM
Bucket Spacing	6"	6"
Head Casing	11 gauge	
Headshaft Dia.	Determined by discharge height - Consult factory	
Headshaft Bearing	Ball bearing, four bolt flange	
Buckets	11" x 6" HDPE	
Chain	C2060H	
Trunking	14 gauge single trunk	
Boot Casing	11 gauge	
Bootshaft	1 7/16" diameter	
Bootshaft Bearing	Ball bearing, four bolt flange	
Construction	Carbon steel (Consult factory for other options)	
Drive Package	Optional	
Motor	Optional	

THE TRADITION OF EXCELLENCE CONTINUES!

MODEL P1300

