



P2800

**SLOWER HANDLING SPEEDS  
PROVIDE MINIMAL  
DAMAGE TO FRAGILE  
PRODUCTS**

**BUCKET  
ELEVATORS**

*up to 2,879 ft<sup>3</sup>/h  
(81.5 m<sup>3</sup>/h)  
/2,313 BPH*



## **SPECIFICATIONS**

Model	P2800-60	P2800-90
Capacity - Free Flowing Material @ 75% Bucket fill	1,555 BPH 1,936 ft <sup>3</sup> /h 54.8 m <sup>3</sup> /h	2,313 BPH 2,879 ft <sup>3</sup> /h 81.5 m <sup>3</sup> /h
Short TPH @ 50lbs/ft <sup>3</sup>	48.4 TPH	72 TPH
Short TPH @ 75lbs/ft <sup>3</sup>	72.6 TPH	108 TPH
Chain Speed	60 FPM	90 FPM
Headshaft RPM	14.7 RPM	21.8 RPM
Bucket Spacing	8"	8"
Head Casing	11 gauge	
Headshaft Dia.	Determined by discharge height - Consult factory	
Headshaft Bearing	Ball bearing, four bolt flange	
Buckets	18" x 8" HDPE	
Chain	C2080H	
Trunking	12 gauge single trunk	
Boot Casing	11 gauge	
Bootshaft	1 15/16" diameter	
Bootshaft Bearing	Ball bearing, four bolt flange	
Construction	Carbon steel (Consult factory for other options)	
Drive Package	Optional	
Motor	Optional	

(Guards removed for photos only)

**THE TRADITION OF  
EXCELLENCE CONTINUES!**

# MODEL P2800

