TECHNICAL DATA SHEET



Reaction time
Works when mixed and during operation

Application
All diesel and petrol engines

Consumption
1:400 fuel mix ratio:
25ml for 10 L,
50ml for 20 L,
100ml for 40 L etc.

Frequency
Every service as routine preventive care or on-demand when problem arises

AUSTRALIAN MADE AND OWNED

INJECTORMATE® ALMIGHTY

Application

Injector Cleaning: **Add directly to fuel at a 1:400 mix ratio (i.e. 25ml for 10L of fuel). WARNING: Do not overdose.**

Recommended for all petrol and diesel engines, especially in cases of cold-start problems due to moisture in the tank or poor exhaust values resulting from sludge deposits. Works during operation.

For older, high-mileage cars, check the fuel filter condition before use.

In difficult cases, cleaning should be performed by applying the product directly onto the surface to be cleaned, using specialised cleaning equipment.

Description

F4TUNE **InjectorMate** Almighty was specifically designed to provide excellent injector and other complex cleaning in all types of engines. Only a clean fuel system ensures clean and powerful combustion, as well as efficient engine performance.

Advantages

No extra effort, easy application. **InjectorMate** eliminates operational contamination throughout the entire fuel injection system. It enhances engine performance and delivers robust, stable combustion, optimising fuel consumption and exhaust emissions. Significantly extends the engine's lifespan, preventing costly repairs and ensuring smooth operation. It works by dissolving and removing deposits that build up on fuel injectors, improving fuel atomisation and combustion.

Recommendation

InjectorMate is recommended for use at every service as routine preventive care to maintain a clean fuel system, ensure clean, powerful combustion, and support efficient engine performance, as well as on demand when a problem arises.

Compatibility

Mixable with all kinds of fuel. Recommended for all petrol and diesel engines.

Safety instructions

Follow the application instructions on the technical data sheet (TDS). Read safety instructions in the Safety Data Sheet (SDS) before using this product. Please keep out of reach of children. If medical advice is needed, have product container or label at hand and call poison centre/doctor.

Disposal

Dispose of this product and container according to local, regional, national and international regulations.

Packing size

500 ml

Properties

Physical state	liquid
Color	light brown
Density	>1
Flash point	>23 °C
Viscosity	<20.5 mm²/s (@ 40 °C)

Almighty applications for petrol and diesel engines

Intake Cleaning: Almighty is also suitable for conventional cleaning of the entire intake system, including the EGR, intake manifold, valves, injector nozzles, and piston crown, without disassembly.

Dosage: 200 ml per application.

DPF Cleaning: Almighty can be used to remove accumulated soot and ash from a diesel particulate filter, restoring its functionality and eliminating issues such as reduced engine performance or potential damage.

Dilute 250ml of InjectorMate with water in a 1:1 ratio (500ml total) and spray it into the DPF.

Catalytic (CAT) Converter Cleaning: Almighty can be used to remove accumulated soot and ash from a catalytic converter, restoring its functionality and eliminating issues like reduced engine performance or potential damage.

Dilute 250ml of InjectorMate with water in a 1:1 ratio (500ml total) and spray it in the CAT.

Radiator Coolant System Cleaning: Almighty can be used to clean oil contamination from a radiator coolant system. Drain the existing coolant, flush with water, and then use **InjectorMate** to emulsify and remove the oil.

Dosage: 50ml per application for 10 L

Combustion Chamber Cleaning: Almighty removes carbon deposits and other contaminants from the tops of pistons and the engine's combustion chamber. This cleaning is crucial for maintaining combustion chamber capacity, ensuring engine performance, fuel efficiency, and longevity.

Warm the engine to its optimal temperature, then remove the spark plugs and add 50ml of **InjectorMate** per piston for 10-20 minutes in each spark plug hole.

Can be used with the stream machine device and suitable adapters.

F4TUNE
Phone: 1300 F4TUNE **Web:** https://f4tune.com.au **Instagram:** https://www.instagram.com/f4tune/
Sales - Alex Triaskine 0412 059 628 alex@f4tune.com.au **Finance and Operations - Elena Vereskova** 0401 167 649 elena@f4tune.com.au