Metal Tower Stand Setup Instructions





At no time shall 360 Hunting Blinds be liable for any accidents due to falls from the hunting blind. We recommend that you follow standard safety procedures when entering and exiting the blind, such as the use of safety harnesses, climbing ropes, etc.

Arrange parts so you can make sure you have all the pieces and can find them easily as you build.



2

Attach top base brackets as shown.



This is the correct way to attach the bracket.

This is the wrong way to attach the brack-

et.



Repeat for all four legs.



6

5

Find the two legs with a set of holes drilled close to the top.

Position them as shown.



7

Attach the platform mounting bracket as shown.





Repeat for the second leg as shown.





Attach the base feet to the bottom of each leg as shown.

Note: be sure to use the feet that have holes for anchor stakes.

If you purchased a 4' extention, attach the feet to the extention section instead.





Repeat for each leg.



Attach the ladder handrail to the platform as shown.





11

Attach ladder sections as shown.



13

Fasten the steps to the ladder handrail sections as shown.



14

Attach feet to bottom of ladder as shown.

Be sure to use the feet that do not have anchor stake holes.

If you purchased a 4' extension, put the feet on the extention instead.





Find the two legs that are setup for the ladder bracket and position them like this on each side of the widest side of your 360 tower floor.





This layout is incorrect.





Securely fasten the legs to the tower floor.

Use sixteen, 2" lags (4 per leg).



18

Use the included hardware to attach the braces between each of the legs as shown.

Use eight, 3/4" bolts.



19

Slide the ladder attachment pipe through the ladder mounting brackets on the tower stand legs as shown.





use the included hardware to keep the ladder attachment pipe from sliding out of the brackets.

Use one, 4" bolt.



21

Gently tip the assembled tower stand onto it's side.



22

Flip the tower stand upright and adjust it on it's future site as needed.





Place a level on the braces between each of the legs to determine if the stand needs to be leveled. Wooden shims, or rocks can be used to build up the low sides. Alternately you can use a shovel to dig away soil under the stand foot that needs to be lowered.





Hook each included cable brace onto the tabs as shown here.





Grab the adjustable hook end of each cable brace and hook it into the hole designed for it on the oposite corner.

When finished the cable braces should create an X on each side of the tower stand.



22

Tighten each of the adjustable hooks on the cable braces equally with a sturdy tool until cables are snug. Be careful not to over-tighten.





Use a heavy sledge hammer to secure the tower stand in place with the included stakes which should be driven through the holes provided in each towner stand foot.



24

Move the ladder into postion on the stand so it fits snugly into place against the ladder attachment pipe. The included u-bolts should be used to fasten the ladder platform to the ladder attachment pipe on the tower stand.

Use two U bolts and four flat washers.





Refer to your 360 Hunting Blind Assembly manual to setup your wall panels before proceeding to the next step.



Attach the hand rails to the ladder platform.





Use the included hardware to securely fasten each of the handrails to the ladder platform as shown.

Use four, 1 ³⁄₄" bolts.





Finished product.





www.360huntingblinds.com