



## Iiyama ProLite LH6562MTS 65" Touchscreen LCD

<b>DISPLAY</b>	
Diagonal	65"
Touch Technology	infrared, multitouch (6 compatible touch points – HID, supported only under Windows® 7/8), activated by finger or pen
Panel	MVA
Display area h x w	803.52 x 1428.48 mm; 31.6" x 56.2"
Response time	8 ms
Contrast	5000 : 1 typical
Brightness	500 cd/m <sup>2</sup> typical
Viewing zone	horizontal/vertical: 178°/ 178°; right/left: 89°/89°; up/down: 89°/ 89°
Display colour	1.073 G (8bit+Hi-FRC)
Pixel pitch h x v	0.744 x 0.744 mm
Native resolution	Full HD 1080p, 1920 x 1080 ( 2.1 megapixel)
Horizontal sync	30 – 83 KHz
Vertical sync	50 – 76 Hz

Synchronization	Separate Sync
Aspect ratio	16 : 9
PIP (Picture in Picture)	PIP, PBP
Max. non-stop operating time	20 hours/day (IRFM on)
<b>Interfaces &amp; connectors</b>	
Analogue input connector	VGA (D-Sub), RCA (VIDEO), S-Video
Digital input connector	DVI-D, HDMI
Audio-signal-input	PC-Audio, RCA L/R
Output connector	RS232C, RCA (L/R), VGA (D-Sub), RCA (VIDEO)
Inputs	RS232C
	D-Sub, DVI-D, HDMI
<b>Special features</b>	
Plug & Play	VESA DDC2B™
Controls	On-Screen-Display in 7 languages (EN, FR, ES, NL, DE, PL, RU) controlled by back controls or a remote control
User controls	picture (picture mode, backlight, contrast, brightness, chroma, phase, sharpness, colour temp., noise reduction, film mode, rest), sound (sound mode, treble, bass, balance, surround, speaker, audio source, reset), screen (PAP setting, display wall, aspect, adjust screen, freeze), setting (language, schedule, power save, control setting, network settings, set monitor ID, HDMI control, advanced, information, reset all)
Speakers	2 x 12 W (Stereo)
Safety	CE, TÜV-Bauart, CB, GOST-R
VESA mounting	400 x 400 mm
Colour	Black
Remote control	yes
Orientation	landscape

<b>Accessories</b>	
Driver	Windows 95 / 98 / 2000 / ME / XP / Vista / 7 / 8
Included accessories	power cable, VGA (D-Sub) signal cable, DVI-D signal cable, remote control, iiyama logo sticker, quick start guide, safety guide
<b>Power management</b>	
Power supply	AC 100 – 240 V, 50 / 60 Hz
Power Supply Unit	internal
Power usage	550 W typical; max. 1 W in Power management mode
Power management	VESA DPMS
<b>Dimensions &amp; Weight</b>	
Dimensions w x h x d	1523.5 x 891.5 x 125 mm
Weight	71 kg