



2024 GENERAL BUILDING RULES

ENGINE/TRANSMISSION:


- 1) STEEL OEM blocks or aftermarket blocks only. No aluminum blocks allowed.
- 2) All steel blocks; any stroke allowed
- 3) LS engine: 4.8, 5.3 or 6.0 only, cast iron blocks only; 7200 chip; 10" blade max (must use 8" sides)
- 4) 602 or 604 FACTORY sealed crate: 7200 chip max; 10" blade max (must use 8" sides)
- 5) 4.125 and larger bore: 7200 chip max; 8" spoiler max
- 6) Smaller than 4.125 bore: 7800 chip max; 8" spoiler max
- 7) Engine must have oil in oil pan on engine only; no remote oil tanks
- 8) Engine cannot be set back farther than 6" from the center of ball joint to #1 spark plug hole
- 9) Cast or aluminum heads - 23 degree Chevrolet/20 degree Ford/18 degree Mopar heads only
(must match factory valve angle for that make)
- 10) One spark plug per cylinder. Two valves per cylinder max
- 11) No mags; HEI style distributors are okay. Secondary MSD box okay; **SINGLE PICKUP ONLY**
(BACKUPS MUST BE UNHOOKED AND CLEARLY MARKED/TAPED)
- 12) Bert or Brinn transmissions okay

BODY/TIRES/ETC:

- 1) 103" wheel base minimum
- 2) All weights **MUST** be painted white with car number and cannot be mounted to any moving part and **MUST** be securely mounted using weight clamps and/or (2) bolts per piece.
- 3) No weight added to bumpers, bumper mounts, or above deck
- 4) Spoilers: 8" tall max; 72" wide max; with no more than three forward braces no taller than spoiler and 18.5" at attachment point on car ; no longer than 22.5" overall from end to end
- 5) No wedge bodies. Conventional late model style body; no fins or raised lips along length of body
- 6) No wings or walls
- 7) Rear bumpers must be constructed in a way not to cause any undue damage to other cars
- 8) Basic dirt late model style roll cage required; no clip/stub cars
- 9) Only adjustable thing from your cockpit will be the brake adjuster
(Nothing remote adjustable anything, manually or in any other way)
- 10) No MSD or like in driver's compartment **(within reach of driver)**
- 11) No traction control of any kind - if we find it you will be banned from series competition
- 12) Must weigh 2300# minimum after race; 602/604/LS 2200# minimum after race
- 13) Hoosier 1350 or harder; American Racer PRO2 or SD46; May run Hoosier NLMT2 on **FRONT** only
- 14) Transponders mandatory at tracks where they are in use



DIAGRAMS/ CHARTS



LATE MODEL / E-MOD / STREET STOCK DIRT TIRE COMPOUND CHART

		D40				A40		WRS-2	H40	
		FT200		D21	D28	D35		USA55	D55	IMCA
				1350	2400		1450	2500	WRS	2700
		TUSA Soft	USA21	TUSA Med		HTWD	TUSA			500 FIRM
SOFT	1100	1200	1300	1325	1400	1425	FT400		1600	D70
			RC1			RC3		RC4		FT600
		SOFT	MED100			MEDIUM			HTW55	STOCKER
	M10		M20			M30		M40	W35	

LEGAL TIRE COMPOUNDS ADDED FOR 2024
HOOSIER NLMT2 FRONT ONLY
HOOSIER LMT3/4
AMERICAN RACER SD46 OR PRO2

LEGAL TIRE COMPOUNDS