SV-WMT-001T

Venus UHF Transferable RFID Tag

With its high-performance and high-security features, the VENUS Windshield Tag delivers superior performance. It is designed and tuned for use on the glass windscreen of the vehicles.

The VENUS WIndshield Tag is constructed to be transferrable from vehicle to vehicle with material graded for automotive applications are used in the manufacturing of this tag.

The VENUS Windshield Tag utilizes an H3 IC chip that has a flexible memory architecture and provides for the optimum allocation of memory. It is ideal for use in high-performance/security applications such as Secure Parking, and Access Control.

High-Performance Windshield RFID
Tag for Automatic Vehicle
Identification Applications

FEATURES

860 – 960 Mhz

Great Read Performance

Long read range

Transferrable/Removable

Alien H3 Chip

Tuned for Glass

EPC C1/G2

ISO 18000 6C



Width 1.5 Inches

Length 4.0 Inches

Transfer Substrate Vinyl Film

Inlay Substrate Special PET (Non-shrink)

Antenna Material Silver Conductive Ink



SPECIFICATIONS:

ISO 18000-6C

860 - 960 Mhz

Read/Write Functions

Data Transfer Rate up to 640 kps


MEMORY SIZE

Alien HIGGS 3 chip

On chip memory 800 bits

EEPROM Write Endurance:

100,000 cycles at 25 C



Environmental Specifications:

ESD – HBM/CDM

Operating Temperature (Installed)

Relative Humidity (RH) (Installed)

*Storage Temperature

Recommended Shelf Life

+/- 3kV

-50°C to +85°C (-58°F to 185°F)

100% condensing humidity

-40°C to + 100°C (-40°F to 212°F)

Less than or equal to 12 Months



Part Number

SV-WMT-001T

Description

Clear Interior Mount Windshield Tag

Transferable Cling

1 Piece with H3 Chip

UV Protection

1 year warranty

50 Min. Order Quantity

This product is available in exclusively through:



818-923-5132