




ASTRONERGY

Special for Australian Market



ASTRO N7s


CHSM54RN_s(DGT)(BLH)/F-BH
Bifacial Series

455W

Warranty

30 30-year Product Warranty
(Specified for rooftop market)

30 30-year Linear Power Warranty
(Only to the front-side of modules)



Key Features

- High efficiency n-type TOPCon cells
- Elegant Zero Busbar design
- Dual glass for improved durability
- Manufacturing with AI technology
- Suitable for residential systems
- Easy to install and transport



ISO 9001:2015:ISO Quality Management System
ISO 14001:2015:ISO Environment Management System
ISO 45001:Occupational Health and Safety



Tier 1
BloombergNEF



455W

POWER RANGE

±5W


POWER SORTING

22.8%MAX MODULE
EFFICIENCY**≤ 1.0%**FIRST YEAR
POWER DEGRADATION**≤ 0.4%**YEAR 2-30
POWER DEGRADATION

Mechanical Specifications

Outer dimensions (L x W x H)	1762 x 1134 x 30 mm
Cell type	n-type mono-crystalline
No. of cells	108 (6*18)
Frame technology	Aluminum, black anodized
Front / Back glass	1.6+1.6 mm
Cable length (Including connector)	Portrait: (+)350 mm,(-)250 mm; Customized length
Cable diameter (IEC/UL)	4 mm ² / 12 AWG
① Maximum mechanical test load	5400 Pa (front) / 2400 Pa (back)
Connector type (IEC/UL)	PV-HCB40 (Chint New Energy) or PV-KST4-EVO2A/xy,PV-KBT4-EVO2A/xy (Stäubli)
Module weight	21.5 kg
Packing unit	36 pcs / box
Weight of packing unit (for 40'HQ container)	820 kg
Modules per 40' HQ container	936 pcs (Subject to sales contract)

① Refer to Astronergy crystalline installation manual or contact technical department.
Maximum Mechanical Test Load=1.5×Maximum Mechanical Design Load.



Electrical Specifications CHSM54RNs(DGT)(BLH)/F-BH-XXX(XXX=455)

STC: Irradiance 1000W/m², Cell Temperature 25° C, AM=1.5

Rated output (P _{mpp} / Wp)	455
Rated voltage (V _{mpp} / V)	33.56
Rated current (I _{mpp} / A)	13.56
Open circuit voltage (V _{oc} / V)	39.60
Short circuit current (I _{sc} / A)	14.36
Module efficiency	22.8%

Tolerance: P_{mpp} ±3%, V_{oc} ±3% and I_{sc} ±4%.**BNPI:** Irradiance: front 1000W/m², rear 135W/m², Cell Temperature 25° C, AM=1.5

Rated output (P _{mpp} / Wp)	500
Rated voltage (V _{mpp} / V)	33.11
Rated current (I _{mpp} / A)	15.10
Open circuit voltage (V _{oc} / V)	39.40
Short circuit current (I _{sc} / A)	15.94

Bifaciality(P_{mpp}/I_{sc}) : 80±5 %, Bifaciality(V_{oc}) : 98±2 %

Electrical characteristics with 10% Bifacial Gains

Rated output (P _{mpp} / Wp)	501
Rated voltage (V _{mpp} / V)	33.56
Rated current (I _{mpp} / A)	14.91
Open circuit voltage (V _{oc} / V)	39.60
Short circuit current (I _{sc} / A)	15.80

Operating Parameters

No. of diodes	3
Junction box IP rating	IP 68
Max. series fuse rating	30 A
Max. system voltage (IEC/UL)	1500V _{DC}


Fire performance: Class C

Temperature Ratings (STC)


Temperature coefficient (P _{mpp})	-0.29%/°C
Temperature coefficient (I _{sc})	+0.043%/°C
Temperature coefficient (V _{oc})	-0.25%/°C

Curve


Current-Voltage (455W)



Power-Voltage (455W)



Current-Voltage (455W)



Made in China, Made in Turkey.

© Chint New Energy Technology Co., Ltd. Reserves the right of final interpretation. please contact our company to use the latest version for contract.

<http://www.astronergy.com.au>

202411